Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	DDEL ENGINE FAMILY		ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST	SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6		
TEAR			SIZES (L)		PROCEDURE	CLASS	TBI, TC, CAC, ECM, EGR, TWC,	EMD+		
2016	GCEXH0540	GCEXH0540LBF 8.9		CNG/LNG	Diesel	MHDD	HO2S	EIVIDT		
PRIMARY ENGINE'S IDLE							5	77007		
EMISSIO	NS CONTROL 3			ADDI	TIONAL IDLE EN	IISSIONS CO	NTROL			
E	EXEMPT N/A									
ENGINE (NE (L) ENGINE MODELS / CODES (rated power, in hp)									
8.9	See attachment for engine models and ratings									
* =not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; L=liter; hp=horsepower; kw=kilowatt; hr=hour;										
14 ' '				ed petroleum gas; E85=85% etha	anol fuel; MF=mult	i fuel a.k.a. BF	=bi fuel; DF=dual fuel; FF=flexible fuel;			
CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel; L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;										
ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/ super charger, CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series;										
ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS = internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);										
EMD=e	EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);									

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

NMHC		NOx		NMHC+NOx		co		PM		нсно	
FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
0.14	0.14	0.20	0.20	*	*	15.5	15.5	0.01	0.01	*	*
0.05	0.02	0.13	0.01	*	*	7.5	6.1	0.002	0.001	*	*
0.21		0.30		*		19.4		0.02		*	
	67P 0.14 0.05	FTP SET 0.14 0.14 0.05 0.02	FTP SET FTP 0.14 0.14 0.20 0.05 0.02 0.13	FTP SET FTP SET 0.14 0.14 0.20 0.20 0.05 0.02 0.13 0.01	FTP SET FTP SET FTP 0.14 0.14 0.20 0.20 * 0.05 0.02 0.13 0.01 *	FTP SET FTP SET FTP SET 0.14 0.14 0.20 0.20 * * 0.05 0.02 0.13 0.01 * *	FTP SET FTP SET FTP SET FTP 0.14 0.14 0.20 0.20 * * 15.5 0.05 0.02 0.13 0.01 * * 7.5	FTP SET FTP SET FTP SET FTP SET 0.14 0.14 0.20 0.20 * * 15.5 15.5 0.05 0.02 0.13 0.01 * * 7.5 6.1	FTP SET FTP SET FTP SET FTP 0.14 0.14 0.20 0.20 * * 15.5 15.5 0.01 0.05 0.02 0.13 0.01 * * 7.5 6.1 0.002	FTP SET FTP SET FTP SET FTP SET FTP SET 0.14 0.14 0.20 0.20 * * 15.5 15.5 0.01 0.01 0.05 0.02 0.13 0.01 * * 7.5 6.1 0.002 0.001	FTP SET FTP

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET= Supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: The manufacturer has demonstrated compliance with the Greenhouse Gas Emission Standards as specified in Title 13 CCR 1956.8 and the incorporated "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy Duty Diesel-Engines and Vehicles" (HDDE Test Procedures) adopted Dec. 12, 2002, as last amended Oct. 21, 2014 using the 2014 model year National Heavy-Duty Engine and Vehicle Greenhouse Gas Program as specified in Section 1036.108 of the HDDE Test Procedures. The manufacturer has submitted the required information and therefore has met the criteria necessary to receive a California Executive Order based on the Environmental Protection Agency's Certificate of Conformity for the above listed engine family.

	EPA CERTIFICATE	OF CONFORMITY	PRIMARY INTENDED SERVICE CLASS TRACTOR / VOCATIONAL				
	CEX-ONHV	Y-16-04					
In	co		CH4	N.O.			
g/bhp-hr	FTP	SET	CH ₄	N₂O			
STD	576	487	0.10	0.10			
FCL	484	418	*	*			
FEL	499	431	2.36	*			
CERT	463	408	1.97	0.06			

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; STD = standard or emission test cap; FEL=family emission limit; FCL=family certification level; CERT=certification level; CO₂=carbon dioxide; CH₄=methane; N₂O=nitrous oxide; VOCATIONAL=vocational engine; TRACTOR=tractor engine

BE IT FURTHER RESOLVED: That the listed engine family is certified to the Alternate Phase-in CO₂ Emission Standards as specified in 13 CCR 1956.8 and section 40 CFR 1036.150 (e) as incorporated in the "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy Duty Diesel-Engines and Vehicles" adopted Dec. 12, 2002, as last amended Oct. 21, 2014.

BE IT FURTHER RESOLVED: Certification to the FEL(s) / FCL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) / FCL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971 (engine manufacturer diagnostic) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of October 2015.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

Engine Model Summary Template

EO#: A-021-0631

10-7-2015

Attachment: Page 1 of 1

Eng	jine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque		9.Emission Control PeDevice Per SAE J1930
GCE	XH0540LBF	3517;FR93274	ISL G 320	320@2100	N/A	N/A	1000@1300	N/A	N/A	H02S, PCM, TW¢,
GCE)	XH0540LBF	3517;FR93277	ISL G 300	300@2100	N/A	N/A	860@1300	N/A	N/A	HQ2S, PCM, TWC,
GCE	XH0540LBF	3517;FR93280	ISL G 280	280@2200	N/A	N/A	900@1300	N/A	N/A	H026, PCM, TWC,
GCE	XH0540LBF	3517;FR93283	ISL G 260	260@2200	N/A	N/A	660@1300	N/A	N/A	H02S, PCM/TWC,
GCE)	XH0540LBF	3517;FR93285	ISL G 250	250@2200	N/A	N/A	730@1300	N/A	N/A	HO2S, PCM, TWC,
GCE	XH0540LBF	3517;FR94378	ISL G 320	320@2100	N/A	N/A	1000@1300	N/A	N/A	H02S, PCM, TWC,
GCE)	XH0540LBF	3517;FR94381	ISL G 300	300@2100	N/A	N/A	860@1300	N/A	N/A	H02S, PCM TWC,
GCE	XH0540LBF	3517;FR94384	ISL G 280	280@2200	N/A	N/A	900@1300	N/A	N/A	H025, PCM, TWC,
GCE	KH0540LBF	3517;FR94387	ISL G 260	260@2200	N/A	N/A	660@1300	N/A	N/A	HO2S, PCM, TVC,
GCE)	XH0540LBF	3517;FR94389	ISL G 250	250@2200	N/A	N/A	730@1300	N/A	N/A	HO2S, PCM, TWO

TBI, TC, CAC, ECM, EGR, TWC, HO2S