**⊘** Air Resources Board

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL ENGINE FAMILY		ENGINE SIZES (L)	FUEL TYPE 1	& TEST	SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 5			
		` ` `	0110	PROCEDURE	CLASS	ECM. TWC. SFI, HO2S	EMD+			
2017	17 HEL3E06.8BW6 6.8		CNG	Otto	HDO					
	PENGINE'S IDLE POS CONTROL 4		ADDI	TIONAL IDLE EN	IISSIONS CO	NTROL 4				
	N/A	N/A								
ENGINE (	L)		ENGINE MODE	LS / CODES (ra	ted power, in	hp)				
6.8				3 Valve / 1 (32	5)					

=not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz, 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; L=liter; hp=horsepower; kw=kilowatt; hr=hour

CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=ffexible fuel;

L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;

ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) = warmup catalyst; DPF=diesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k., universal or linear oxygen sensor); WR-HO2S=wide range oxygen sensor; TBI=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/ super charger; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallet; (2) (suffix)=in sensor;

ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);

EMD=engine manufacturer diagnostic system; OBD(F) / (P) / (\$)=full / partial / partial with fine / on-board diagnostic

(2012-08-20)

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diésel" CO, SET and NTE certification compliancé may háve been démonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in	NMHC		NOx		NMHC+NOx		co		PM		нсно	
g/bhp-hr	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
STD	0.14	*	0.20	*	•	*	14.4	*	0.01	*	0.01	*
CERT	0.04	*	0.05		*	*	2.1	*	0.002	w	0.000	*
NTE	*			*	*		*		*		*	

g/bhp-hr=grams per brake horsepower-hour, FTP=Federal Test Procedure, SET= supplemental emissions testing, NTE=Not-to-Exceed emission limit, STD=standard or emission test cap; FEL=family emission limit; CERT=certification level, NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;)

BE IT FURTHER RESOLVED: The manufacturer has demonstrated compliance with the Greenhouse Gas Emission Standards as specified in Title 13 CCR 1956.8 and the incorporated "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy Duty Otto Cycle Engines and Vehicles" (HDOE Test Procedures) adopted Dec. 27, 2000, as last amended Oct. 21, 2014 using the 2014 model year National Heavy-Duty Engine and Vehicle Greenhouse Gas Program as specified in Section 1036.108 of the HDOE Test Procedures. The manufacturer has submitted the required information and therefore has met the criteria necessary to receive a California Executive Order based on the Environmental Protection Agency's Certificate of Conformity for the above listed engine family.

	EPA CERTIFICATI	E OF CONFORMITY	PRIMARY INTENDED SERVICE CLASS  Vocational				
	HEL3E06	8BW6-002					
In	C	O <sub>2</sub>	CH,	N₂O			
g/bhp-hr	FTP	SET	CH4				
STD	w	*	*	*			
-CL	*	*	*	*			
FEL	*	*	*	*			
CERT	*	*	*	*			

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; STD = standard or emission test cap; FEL=family emission limit; TRACTOR=tractor engine FCL=family certification level; CERT=certification level; CO₂=carbon dioxide; CH<sub>4</sub>=methane; N2O=nitrous oxide VOCATIONAL=vocational engine;

Air Resources Board

**BE IT FURTHER RESOLVED:** The manufacturer has demonstrated compliance with the Greenhouse Gas Emission Standards as specified in Title 13 CCR 1956.8 and the incorporated "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy Duty Otto Cycle Engines and Vehicles" (HDOE Test Procedures) adopted Dec. 27, 2000, as last amended Oct. 21, 2014 using the Interim Provisions as specified in Section 1036.150(d) of the HDOE Test Procedures.

**BE IT FURTHER RESOLVED:** For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 2035 et seq. (emission control warranty) and 13 CCR 1971.1 (on-board diagnostic).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

\_\_ day of June 2017.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

## **Engine Model Summary Template**

				4.Fuel Rate:	5.Fuel Rate:		7.Fuel Rate:		
			3.BHP@RPM	mm/stroke @ peak HP	(lbs/hr) @ peak HP	6.Torque @ RPM	mm/stroke@peak	8.Fuel Rate:	9.Emission Control
Engine Family	1.Engine Code	2.Engine Model	(SAE Gross)	(for diesel only)	(for diesels only)	(SEA Gross)	torque	(lbs/hr)@peak torque	Device Per SAE J1930
HEL3E06.8BW6	1	3 Valve /	325@ 4700			450 @ 2100	329.88	96.88	TWC, HO2S,
									ECM, STI