California	rnia Environmental Protection Agency		
GE A:	P Rosou	reas R	aard

.

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL ENGINE FAMILY		ENGINE FAMILY ENGINE SIZES (L)		FUEL TYPE	STANDARDS & TEST	SERVICE	ECS & SPECIAL FEATURES	DIAGNOSTIC 6
YEAR				PROCEDURE	CLASS 2	DDI, TC, CAC, ECM, EGR, OC,		
2017	2017 HDDXH14.8EAD		14.8	Diesel	Diesel	HHDD	PTOX, SCR-U, AMOX	OBD(\$)
C. C	ENGINE'S IDLE			AI	DDITIONAL IDLE EN	ISSIONS CO	NTROL ⁵	
	30g				N	/A		
ENGINE (L	-)			ENGINE MO	DELS / CODES (ra	ted power, in	hp)	
14.8				See attachm	nent for engine m	odels and ra	atings	-
L=liter, hp=	horsepower; kw=kill	owatt; hr	=hour;				R 86.abc=Title 40, Code of Federal Regulation	s, Section 86 abc;

pmpressed/liquefied natural das: LPG Inanol fuel; MF L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;

ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction - urea / - ammonia; WU (prefix) =warmup catalyst; DPF=diesel particulate filler; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; ID/DDI=indirect/direct diseal injection; TC/SC=urbo/ super charger; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series;

ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=axempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel system; N/A=not applicable (e.g., Otto engines and vehicles); EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD(F) / (P) / (\$)=full / partial / partial with a fine / on-board diagnostic;);

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in g/bhp-hr	NMHC		NOx		NMHC+NOx		CO		PM		нсно	
	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
STD	0.14	0.14	0.20	0.20	*		15.5	15.5	0.01	0.01	*	
FEL		*	*	*	*	· · ·	*	*	*	-26		*
CERT	0.000	0.001	0.10	0.01	*		0.3	0.01	0.001	0.000	*	*
NTE	0.21		0.	30		*	19).4	0.	02		*

⁴ g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: The manufacturer has demonstrated compliance with the Greenhouse Gas Emission Standards as specified in Title 13 CCR 1956.8 and the incorporated "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy Duty Diesel-Engines and Vehicles" (HDDE Test Procedures) adopted Dec. 12, 2002, as last amended Oct. 21, 2014 using the 2014 model year National Heavy-Duty Engine and Vehicle Greenhouse Gas Program as specified in Section 1036.108 of the HDDE Test Procedures. The manufacturer has submitted the required information and therefore has met the criteria necessary to receive a California Executive Order based on the Environmental Protection Agency's Certificate of Conformity for the above listed engine family.

	EPA CERTIFICAT	E OF CONFORMITY	PRIMARY INTENDED SERVICE CLASS				
	HDDXH14	.8EAD-003	TRACTORIVOCATIONAL				
in CO		O ₂	CH				
g/bhp-hr FTP	FTP	SET	CH.	N ₂ O			
STD	555	460	0.10	0.10			
FCL	518	455	•				
FEL	533	469	0,10	0.10			
CERT	513	444	0.02	0.02			

FCL=family certification level; CERT=certification level; CO1=carbon dioxide; CH4=methane; N1O=nitrous oxide; VOCATIONAL=vocational engine; TRACTOR=tractor engine **BE IT FURTHER RESOLVED:** Certification to the FEL(s) / FCL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) / FCL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: The listed engine models are conditionally certified in accordance with 13 CCR Section 1971.1(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the heavy-duty on-board diagnostic (HD OBD) system of the listed engine models has been determined to have 3 deficiencies. The listed engine models are approved subject to the manufacturer paying a fine of \$25 per engine for the third deficiencies in the listed engine family that is produced and delivered for sale in California. On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of engines produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2017 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$5000 per engine pursuant to HSC Section 43154.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____ day of December 2016.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

Engine Model Summary Template A-290-0161

ATTACH MENTIOF 1

12/7/2016

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak lorque	8.Fuel Rate: (lbs/hr)@peak torqu	9.Emission Control eDevice Per SAE J1930
		-	400@1625	000.4			000.4	100.0	FON TO ONO
HDDXH14.8EAD	4	DD15	400@1625	229.4	123.8	1750@1075	298.1	106.6	ECM, TC, CAC
HDDXH14.8EAD	11	DD15	455@1625	260.4	138.2	1550@1075	264.0	94.5	EGR, PTOX
HDDXH14.8EAD	ш	DD15	455@1625	260.4	138.2	1650@1075	280.2	100.2	DDI, OC
HDDXH14.8EAD	IV	DD15	455@1625	260.4	138.2	1750@1075	298.1	106.6	AMOX, SCR-U
HDDXH14.8EAD	V	DD15	475@1625	272.8	147.5	1650@1075	280.2	100.2	(all ratings)
HDDXH14.8EAD	VI	DD15	505@1625	291.0	157.6	1650@1075	280.2	100.2	
HDDXH14.8EAD	VII	DD15	475@1625	272.8	147.5	1650@1075	280.2	100.2	
HDDXH14.8EAD	VIII	DD15	505@1625	291.0	157.6	1650@1075	280.2	100.2	
HDDXH14.8EAD	IX	DD15	505@1625	291.0	157.6	1750@1075	298.1	106.6	