⊘ Air Resources Board

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

2017 HNVXH07570SB 12.4 Diesel Diesel Diesel DI, TC(2), CAC(2), ECM, EGR, DC, PTOX, SCR-U, AMOX PRIMARY ENGINE'S IDLE EMISSIONS CONTROL 30g N/A ENGINE (L) ENGINE MODELS / CODES (rated power, In hp) 12.4 See attachment for engine models and ratings * =not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; L=liter; hp=horsepower; kw=kilowatt, hr=hour; CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel; L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto; ECS=emission control system; TWC/OcT-hree-welyckoldizing catalyst; NAC=NOX adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) = warm-upc atalyst; DPF=diesel particulate filter; PTOX=perioldic trap oxidizer; H025/02S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SF/IMFlessquenflat/multi-port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/ super charge; CAC=charge air cooler; EGR / EGR-Ce=xharust gas recirculation / coole GR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series; AMOX=ammonia oxidation catalyst ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(K)(T); X9=70 g/hr NOX (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(K)); Exempt=exempted per 13 CCR 1956.8(a)(6)(K)) (FR PS = internal combustion avxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(K)); Exempt=exempted per 13 CCR 1956.8(a)(6)(K)) (FR PS = internal combustion avxiliary power system; ALT=alte	MODEL ENGINE FA		AMILY ENGINE SIZES (L)		FUEL TYPE 1	STANDARDS & TEST	SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 5	
PRIMARY ENGINE'S IDLE EMISSIONS CONTROL ADDITIONAL IDLE EMISSIONS CONTROL ADDITIONAL IDLE EMISSIONS CONTROL ADDITIONAL IDLE EMISSIONS CONTROL N/A ENGINE (L) ENGINE MODELS / CODES (rated power, In hp) 12.4 See attachment for engine models and ratings * =not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; L=liter; hp=horsepower; kw=kilowatt; hr=hour; CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel; LIM/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDD=heavy duty Otto; 3 ECS=emission control system; TWC/OC=three-way/void/disp catalayst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) =warm-up catalyst; DFP=diesel particulate filler, PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=hrottie body fuel injection; SFI/MFI=sequential/multi-port fuel injection; DGI=direct gasciline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/ super charge; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulses/descondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series; AMOX=ammonia oxidation catalyst ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOX (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(C); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);	· ·				Diagal	PROCEDURE	CLASS -	DDI, TC(2), CAC(2), ECM, EGR,	ODD (4)	
EMISSIONS CONTROL 30g N/A ENGINE (L) ENGINE MODELS / CODES (rated power, In hp) 12.4 See attachment for engine models and ratings * =not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; L=litler; hp=horsepower; kw=kilowatt; hr=hour; CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel; L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto; ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; PTOX=periodic trap oxidizer; HO25/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/MF1=sequential/multi-port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct/direct diesel injection; OSCR=gaseous carburetor; DI/DDI=indirect/direct	2017	HNVXH0757	0SB	12.4	Diesei	Diesel	HHDD	DOC, PTOX, SCR-U, AMOX	OBD (\$)	
ENGINE (L) ENGINE MODELS / CODES (rated power, In hp) 12.4 See attachment for engine models and ratings * =not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; -	5 1				ADDI	TIONAL IDLE EN	issions co	NTROL ⁵		
*=not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; L=liter; hp=horsepower; kw=kilowatt; hr=hour; CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel; L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto; ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) =warm-up catalyst; DFF=diesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/mill-injection; TG/SC=turbo/ super charge; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series; AMOX=ammonia oxidation catalyst ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(B)); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);		30g		·		N	/A		4	
=not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; 1-eliter; hp=horsepower; kw=kllowatt; hr=hour; CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel; L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto; ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) =warm-up catalyst; DPF=dlesel particulate filler; PTOX=periodic trap oxidizer; HO25/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throtitie body fuel injection; SFI/MF!=sequential/multi-port fuel injection; DE-direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/ super charger; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series; AMOX=ammonia oxidation catalyst ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A);); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS=internal combustion auxiliary power system; ALT=alternative method [per 13 CCR 1956.8(a)(6)(B)); Exempt=exempted per 13 CCR 1956.8(a)(6)(C); Exempt=exempted per 13 CCR 1956.8(a)(6)(C); APS=internal combustion auxiliary power system; ALT=alternative method [per 13 CCR 1956.8(a)(6)(C); Exempt=exempted per 13 CCR 1956.8(a)(6)(C); APS=internal combustion auxiliary power system; ALT=alternative method [per 13 CCR 1956.8(a)(6)(C); APS=internal combustion auxiliary power system; ALT=alternative method [per 13 CCR 1956.8(a)(6)(C); APS=internal combustion auxiliary power system; ALT=alternative method [per 13 CC	ENGINE (L)	.		ENGINE MODE	LS / CODES (ra	ted power, In	hp)	4.5	
L=litter; hp=horsepower; kw=kilowatt; hr=hour; CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel; L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto; ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) =warm-up catalyst; DPF=cdlesel particulate filter; PTOX=periodic trap oxidizer; HOZ5/OZS=heated/oxygen sensor; HAFS/AFS=heated/alt-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/MFI=sequential/multi-port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/super charge; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series; AMOX=ammonia oxidation catalyst ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method [per 13 CCR 1956.8(a)(6)(B); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);	12.4	See attachment for engine models and ratings								
EMD=engine manufacturer diagnostic system; OBD(F) / (P) / (\$)=full / partial with fine / on-board diagnostic; , (2012-08-20)	L=liter; hp 1 CNG/LI 2 L/M/H H 3 ECS=ei up catalyst; TBI=throttle super charg control mod ESS=ei (per 13 CC	-horsepower; kw=k Moseompressed/liquidD=light/medium/himslon control syste DPF-diesel partict, a body fuel injection; yer; GAC=charge aidule; EM=engine mongine shutdown syste R 1956.8(a)(6)(D); E 1956.8(a)(6)(D);	ilowatt; hi efied natu eavy heav m; TWC// late filter; SFI/MFI= cooler; Edification; em (per 13 exempt=e	r=hour; rags; LPG=liquef y-duty dlesel; UB=u OC=three-wayloxldi; PTOX=periodic trar; sequentlal/multi-por EGR / EGR-C=exha: 2 (preffx)=parallel; 8 CCR 1956.8(a)(6)(, xempted per 13 CCf.	ied petroleum gas; E85=85% eth irban bus; HDO=heavy duty Otto; ing catalyst; NAC=NOx adsorpti o oxidizer; HO2S/O2S=heated/ox t fuel injection; DGI=direct gasoli ist gas recirculation / cooled EGR (2) (suffix)=in series; AMOX=ar A)(1); 30g=30 g/hr NOx (per 13 C R 1956.8(a)(6)(B) or for CNG/LNG	anol fuel; MF=mult on catalyst; SCR-L ygen sensor; HAF; ne injection; GCAR; ; PAIR/AIR=pulsec mmonia oxidation c CCR 1956.8(a)(6)(C tuel systems; N/A	I fuel a.k.a. BF I / SCR-N=sele S/AFS=heated/ B=gaseous car I/secondary alr atalyst); APS =intern =not applicable	=bl fuel; DF=dual fuel; FF=flexible fuel; ctive catalytic reduction – urea / – ammonia; W air-fuel-ratio sensor (a.k.a., universal or linear or rouretor; IDI/DDI=indirect/direct diesel injection injection; SPL=smoke puff limiter; ECM/PCM= al combustion auxiliary power system; ALT=al	/U (prefix) =warm- xygen sensor); ; TC/SC=turbo/ =engine/powertrain ternative method	

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in	NMHC		NOx		NMHC+NOx		CO		PM		нсно	
g/bhp-hr	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
STD	0.14	0.14	0.20	0.20	*	*	15.5	15,5	0,01	0.01	*	*
CERT	0.03	0.02	0.14	0.05	*	*	0.3	0.04	0.000	0.001	*	*
NTE	0.21		0.3	30	*		19.4		0.02			k

4 g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET= supplemental emissions testing; NTE=Not-to-Exceed emission limit; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: The manufacturer has demonstrated compliance with the Greenhouse Gas Emission Standards as specified in Title 13 CCR 1956.8 and the incorporated "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy Duty Diesel-Engines and Vehicles" (HDDE Test Procedures) adopted Dec. 27, 2002, as last amended Oct. 21, 2014 using the 2014 model year National Heavy-Duty Engine and Vehicle Greenhouse Gas Program as specified in Section 1036.108 of the HDDE Test Procedures. The manufacturer has submitted the required information and therefore has met the criteria necessary to receive a California Executive Order based on the Environmental Protection Agency's Certificate of Conformity for the above listed engine family.

	EPA CERTIFICAT	E OF CONFORMITY	PRIMARY INTENDED SERVICE CLASS				
	HNVXH0757	'0SB-001-R01	TRACTOR / VOCATIONAL				
in	C	O ₂	CH₄	N.O.			
g/bhp-hr	FTP	SET	Un₄	N₂O			
STD	555	460	0.10	0.10			
FCL	540	474	*	* .			
FEL	556	488	0.10	0.10			
CERT	535	474	0.02	0.09			

4 g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; STD = standard or emission test cap; FEL=family emission limit; FCL=family certification level; CERT=certification level; CO₂=carbon dioxide; CH₄=methane; N₂O=nitrous oxide; VOCATIONAL=vocational engine; TRACTOR=tractor engine

@ Air Resources Board

BE IT FURTHER RESOLVED: Certification to the FEL(s) / FCL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) / FCL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance), and 13 CCR 2035 et seq. (emission control warranty).

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), 30g rating engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" adopted December 12, 2002, as last amended September 2, 2015, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

BE IT FURTHER RESOLVED: That the manufacturer has elected to include engine models in this engine family which are identified for "emergency vehicle use only". These "emergency vehicle use only" engines are exempt from requirements imposed pursuant to California law and the regulations adopted pursuant thereto for motor vehicle pollution control devices per California Vehicle Code Section 27156.2. The manufacturer must clearly label these engines for "emergency vehicle use only" on the engines' emission control label.

BE IT FURTHER RESOLVED: The listed engine models are conditionally certified in accordance with 13 CCR Section 1971.1(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the heavy-duty on-board diagnostic system of the listed engine models has been determined to have eight deficiencies. The listed engine models are approved subject to the manufacturer paying a fine of \$150 per engine for the third through eighth deficiencies in the listed engine family that is produced and delivered for sale in California. On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of engines produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2017 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all engines covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$5000 per engine pursuant to HSC Section 43154.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-004-0450 dated March 9, 2017.

Executed at El Monte, California on this

_day of June 2017.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

Attachment 1/2

Engine Model Summary Template

A-004-0450-1 5/24/2017

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HF (for diesel only)	5.Fuel Rate: ' (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torq	9.Emission Control ueDevice Per SAE J1930
HNVXH07570SB	A475	A475	475@1700	290	165	1700@1000	313	105 DI	X, ECM, TC(2), 9€ 1,C
	THE ACTION OF THE STATE OF THE	stranovana annovana filosopologo, anno annovana angeles par especial						C	AC(2), EGR, SCR-U
								······································	PTOX, AMOX
HNVXH07570SB	A450H	A450H	450@1700	272	155	1700@1000	313	105	SAME
HNVXH07570SB	A450MT	A450MT	450@1700	272	155	1700/1550	313-286	105-96	SAME
i i					•	@ 1000			
HNVXH07570SB	A430	A430	430@1700	260	148	1550@1000	287	96	SAME
HNVXH07570SB	A430MT	A430MT	430@1700	260	148	1700/1550	313-287	105-96	SAME
						@ 1000			
HNVXH07570SB	A410	A410	410@1700	248	141	1450@1000	266	89	SAME
HNVXH07570SB	A390	A390	390@1700	235	134	1450@1000	266	89	SAME
HNVXH07570SB	A370	. A370	370@1700	223	127	1350@1000	245	82	SAME
HNVXH07570SB	A365	A365	365@1700	219	125	1250@1000	227	76	SAME
EMERGENCY	VEHICLES	\rightarrow							
HNVXH07570SB	F2897	- A475	475@1700	290	165	1700@1000	313	105	SAME
HNVXH07570SB	F2898	A430	430@1700	260	148	1550@1000	287	96	SAME
		V			<u> </u>				
HNVXH07570SB	F2970	// A410	410@1700	248	141	1450@1000	266	89	SAME
HNVXH07570SB	F2969	A390	390@1700	235	134	1450@1000	266	89	SAME
HNVXH07570SB	F2968	- A370	370@1700	223	127	1350@1000	245	. 82	SAME

Attachment 2/2

Engine Model Summary Template

A-004-0450-1 5/24/2017

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque		9.Emission Control Device Per SAE J1930	ricente
HNVXH07570SB	F2967 *	A365	365@1700	219	125	1250@1000	227	76	SAME	

Emergency rehicles Only