Ø Air Resources Board

FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-2026 New On-Road Heavy-Duty Engines Page 1 of 2 Pages

(2012-08-20)

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2: and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST PROCEDURE	INTENDED SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 5				
2017	HFMXH06.7C45	6.7	Diesel	Diesel	CLASS T MHDD	TC, DDI, CAC, EGRC, ECM, PTOX, DOC, SCRC(Urea), NOXS, RDQS	OBD (\$)				
	Y ENGINE'S IDLE			ADDITIONAL IDLE	EMISSIONS CO	NTROL 4					
	30g	·		ra di Miljan da Roja, pangangan	N/A	n da de la composition della c	iga ka .a Tarah				
ENGINE ((L)		ENG	INE MODELS / CODES	(rated power, in	hp):					
6.7		4V F-Series / HBC17E05; HBC17F05 (300 For All Codes) 4V F-Series / HBC17G05; HBC17J05 (330 For All Codes) Emergency Vehicle Rating: 4V F-Series / HBC17B05 (270); HBC17D05 (270); HBC17M05 (300); HBC17N05 (300); HBC17H05 (330); HBC17K05 (330)									
L=liter, hp 1 CNG/LI 2 L/M/H I 3 ECS=el WU (prefix oxygen ser IDI/DDI=ind SPL=smok 4 ESS=el (per 13 CC	n=horsepower; kw=kllowatt MG=compressed/liquefied i HDD=light/medium/heavy h mission control system; 'T. c) =warm-up catalyst; 'DFF nsor); NOXS=nitrogen oxid direct/direct dlessi Injection ke puff limiter; 'ECM/PCM= ngine shutdown system (ps 1956.8(a)(6)(D); Exemp 1956.8(a)(6)(D); Exemp	i; hr=hour; natural gas; LPG= neavy-duty diesel; NC/OC=three-way; =diesel particulate es sensor; TBI=thr ; TC/SC=turbo/ s. engine/powertrain or 13 CCR 1956.8(ot=exempted per 1	liquefied petroleum gas; E UB=urban bus; HDO=heav 'oxidizing catalyst; NAC=N filler; PTOX=periodic trap- ottle body fuel Injection; SF per charger; CAC=charge control module; EM=engin y(6)(A)(1); 30g=30 g/hr N 3 CCR 1956.8(a)(6)(6) or fo	85=85% ethanol fuel; MF=1 wy duty Otto; Ox adsorption catalyst; SC oxidizer; HO2S/O2S=heate -I/MFI=sequential/multi port air cooler; EGR / EGRC=e e modification; 2 (prefix)= Ox (per 13 CCR 1956,8(a)(multi fuel a.k.a. Br RC=selective cata ad/oxygen sensor; fuel injection; DG xhaust gas recircu parallel; (2) (suffix b)(C); APS=interr N/A=not applicable	R 86.abc=Title 40, Code of Federal Regulation =bl fuel; DF=dual fuel; FF=flexible fuel; lytic reduction convertor; RDQS=reductant qual HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a.) -eldirect gasoline injection; GCARB=gaseous clation / cooled EGR; PAIR/AIR=pulsed/second j=in series; all combustion auxiliary power system; ALT=a e (e.g., Otto engines and vehicles);	ality sensor ; , universal or linear earburetor; lary air injectlon;				

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

EMD=engine manufacturer diagnostic system; OBD(F) / (P) / (\$)=full / partial / partial with fine / on-board diagnostic;

in g/bhp-hr	NMHC		NOx		NMHC+NOx		CO"		PM		нсно	
	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
STD	0.14	0.14	0.20	0.20	*	*	15.5	15.5	0.01	0.01	*	*
CERT	0.01	0.01	0.15	0.07	*	* .:	0.6	0.1	0.001	0.000	*	*
NTE	0.21		0.30		*		19.4		0.02			r r

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET= supplemental emissions testing; NTE=Not-to-Exceed emission limit; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; 3.

BE IT FURTHER RESOLVED: The manufacturer has demonstrated compliance with the Greenhouse Gas Emission Standards as specified in Title 13 CCR 1956.8 and the incorporated "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy Duty Diesel-Engines and Vehicles" (HDDE Test Procedures) adopted Dec. 27, 2002, as last amended Sep. 2, 2015 using the 2014 model year National Heavy-Duty Engine and Vehicle Greenhouse Gas Program as specified in Section 1036.108 of the HDDE Test Procedures. For the listed California-only engine family, the manufacturer has submitted the required greenhouse gas information.

	EPA CERTIFICATI	OF CONFORMITY	PRIMARY INTENDED SERVICE CLASS VOCATIONAL			
	HFMXH00	3,7C45-001				
in		O ₂	011			
g/bhp-hr	FTP	. SET	CH₄	N ₂ O		
STD	576	*	0.10	0.10		
FCL	570	*	*	*		
FEL	587	*.	0.10	0.10		
CERT	563	*	0.01	0.04		

STD = standard or emission test cap; FEL=family emission limit; /OCATIONAL=vocational engine; TRACTOR=tractor engine g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; FCL=family certification level; CERT=certification level; CO2=carbon dioxide; CH4=methane; N₂O=nitrous oxide; VOCATIONAL=vocational engine;

@ Air Resources Board

FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-2026 New On-Road Heavy-Duty Engines Page 2 of 2 Pages

BE IT FURTHER RESOLVED: Certification to the FEL(s) / FCL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) / FCL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" adopted Dec. 12, 2002, as last amended Sep. 2, 2015, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

BE IT FURTHER RESOLVED: That the manufacturer has elected to include engine models in this engine family which are identified for "emergency vehicle use only". These "emergency vehicle use only" engines are exempt from requirements imposed pursuant to California law and the regulations adopted pursuant thereto for motor vehicle pollution control devices per California Vehicle Code Section 27156.2. The manufacturer must clearly label these engines for "emergency vehicle use only" on the engines' emission control label.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance), and 13 CCR 2035 et seq. (emission control warranty).

BE IT FURTHER RESOLVED: The listed engine models are conditionally certified in accordance with 13 CCR Section 1971.1(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the heavy-duty on-board diagnostic (HD OBD) system of the listed engine models has been determined to have three deficiencies. The listed engine models are approved subject to the manufacturer paying a fine of \$25 per engine for the third deficiency in the listed engine family that is produced and delivered for sale in California. On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of engines produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2017 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all engines covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$5000 per engine pursuant to HSC Section 43154. Engines certified under this Executive Order must conform to all applicable California emission regulations.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

_ day of December 2016

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division