

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	MODEL ENGINE FAMILY		ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST	SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6			
TEAR			312E3 (L)		PROCEDURE	CLASS 2	DDI, TC, CAC, ECM, EGR, OC,	OBD(\$)			
2018	JCEXH0721	XAG	11.8	Diesel	Diesel	HHDD-UB	PTOX, SCR-U, AMOX	ΟΟΙ Ο Ι (Ψ)			
PRIMARY ENGINE'S IDLE EMISSIONS CONTROL 5				ADDITIONAL IDLE EMISSIONS CONTROL 5							
	30g				N	/A					
ENGINE (L)			ENGINE MODE	LS / CODES (ra	ted power, in	hp)				
11.8	11.8 See attachment for engine models and ratings										
L=liter; hp 1 CNG/LI 2 L/M/H I	* =not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; L=liter; hp=horsepower; kw=kilowatt; hr=hour; CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel; L/M/H HDD=light/medium/heavy-beavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;										
ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; PTOX=periodic trap oxidizer; HO25/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/ super charger; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series;											
(per 13 CC	ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles); EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD(F) / (P) / (\$)=full / partial with a fine / on-board diagnostic;);										

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

NMHC		NOx		NMHC+NOx		co		PM		нсно	
FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
0.14	0.14	0.20	0.20	*	*	15.5	15.5	0.01	0.01	*	*
*	*	*	*	*	*	*	*	*	*	*	*
0.01	0.01	0.17	0.16	*	*	0.4	0.00	0.004	0.003	*	*
0.21		0.	0.30 *		19.4		0.02		*		
	0.14 * 0.01	FTP SET 0.14 0.14 * * 0.01 0.01	FTP SET FTP 0.14 0.14 0.20	FTP SET FTP SET 0.14 0.14 0.20 0.20 * * * * 0.01 0.01 0.17 0.16	FTP SET FTP SET FTP 0.14 0.14 0.20 0.20 * * * * * * 0.01 0.01 0.17 0.16 *	FTP SET FTP SET FTP SET 0.14 0.14 0.20 0.20 * * * * * * * * 0.01 0.01 0.17 0.16 * *	FTP SET FTP SET FTP SET FTP 0.14 0.14 0.20 0.20 * * 15.5 * * * * * * * 0.01 0.01 0.17 0.16 * * 0.4	FTP SET FTP SET FTP SET FTP SET 0.14 0.14 0.20 0.20 * * 15.5 15.5 * * * * * * * * 0.01 0.01 0.17 0.16 * * 0.4 0.00	FTP SET FTP SET FTP SET FTP 0.14 0.14 0.20 0.20 * * 15.5 15.5 0.01 * * * * * * * * 0.01 0.01 0.17 0.16 * * 0.4 0.00 0.004	FTP SET 50.01 0.01 0.01 0.01 0.	FTP SET FTP

4 g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure, SET=Supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: The manufacturer has demonstrated compliance with the Greenhouse Gas Emission Standards as specified in Title 13 CCR 1956.8 and the incorporated "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy Duty Diesel-Engines and Vehicles" (HDDE Test Procedures) adopted Dec. 12, 2002, as last amended Sep. 1, 2017 using the 2014 model year National Heavy-Duty Engine and Vehicle Greenhouse Gas Program as specified in Section 1036.108 of the HDDE Test Procedures. The manufacturer has submitted the required information and therefore has met the criteria necessary to receive a California Executive Order based on the Environmental Protection Agency's Certificate of Conformity for the above listed engine family.

1	EPA CERTIFICAT	E OF CONFORMITY	PRIMARY INTENDED SERVICE CLASS			
	JCEXH07	21XAG-016	TRACTOR / VOCATIONAL			
in g/bhp-hr		O ₂	CII.			
	FTP	SET	CH₄	N₂O		
STD	555	460	0.10	0.10		
FCL	509	465	*	*		
FEL	524	479	0.10	0.11		
CERT	509	465	0.02	0.09		

4 g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; STD = standard or emission test cap; FEL=family emission limit; FCL=family certification level; CERT=certification level; CO₂=carbon dioxide; CH₄=methane; N₂O=nitrous oxide; VOCATIONAL=vocational engine. TRACTOR=tractor engine

BE IT FURTHER RESOLVED: Certification to the FEL(s) / FCL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) / FCL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.





BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" (HDDE Test Procedures) adopted Dec. 12, 2002, as last amended Sep. 1, 2017, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance) and 13 CCR 2035 et seq. (emission control warranty).

BE IT FURTHER RESOLVED: That the manufacturer has elected to include engine models in this engine family which are identified for "emergency vehicle use only". These "emergency vehicle use only" engines are exempt from requirements imposed pursuant to California law and the regulations adopted pursuant thereto for motor vehicle pollution control devices per California Vehicle Code Section 27156.2. The manufacturer must clearly label these engines for "emergency vehicle use only" on the engines' emission control label.

BE IT FURTHER RESOLVED: The listed engine models are conditionally certified in accordance with 13 CCR Section 1971.1(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the heavy-duty on-board diagnostic (HD OBD) system of the listed engine models has been determined to have eleven deficiencies. The listed engine models are approved subject to the manufacturer paying a fine of \$350 per engine for the third through eleventh deficiencies in the listed engine family that is produced and delivered for sale in California. On a quarterly basis, the manufacturer shall submit to California Air Resources Board reports of the number of engines produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2018 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all engines covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$5000 per engine pursuant to HSC Section 43154.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

-1/1

day of January 2018.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

A #achment: Page 10f2 E0#: A-021-0687

1/2/2018

Engine Model Summary Template

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
JCEXH0721XAG	4814;FR20719	X12 350	350@1761	190	113	1350@1000	241	81	SCRC, PTOX, P
JCEXH0721XAG	4814;FR20720	X12 370	270@1761	201	119	1350@1000	241	81	SCRC, PTOX, PC
JCEXH0721XAG	4814;FR20721	X12 380	380@1761	206	122	1450@1000	262	88	SCRC, PTOX, PC
JCEXH0721XAG	4814;FR20749	X12 400ST	400@1761	218	129	1700@1000	308	104	SCRC, PTOX, PC
JCEXH0721XAG	4814;FR20901	X12 400SA	400@1761	218	129	1700@1000	308	104	SCRC, PTOX, PC
JCEXH0721XAG	4814;FR20963	X12 400	400@1761	218	129	1400@1000	253	85	SCRC, PTOX PC
JCEXH0721XAG	4814;FR20722	X12 410	410@1761	223	133	1450@1000	262	88	SCRC, PTOX, PC
JCEXH0721XAG	4814;FR20723	X12 410	410@1761	223	133	1650@1000	300	101	SCRC, PTOX, PC
JCEXH0721XAG	4814;FR20751	X12 410ST	410@1761	223	133	1650@1000	300	101	SCRC, PTOX, PC
JCEXH0721XAG	4814;FR20902	X12 410SA	410@1761	223	133	1650@1000	300	101	SCRC, PTOX, PC
JCEXH0721XAG	4814;FR20724	X12 430	430@1761	235	139	1550@1000	283	95	SCRO, PTOX, PC
JCEXH0721XAG	4814;FR20725	X12 430	430@1761	235	139	1650@1000	300	101	SCRC PTOX, PC
JCEXHÓ721XAG	4814;FR20750	X12 455	455@1761	251	149	1700@1000	308	104	SCRC, PTOX, PC
JCEXH0721XAG	4814;FR20748	X12 455ST	455@1761	251	149	1700@1000	308	104	SCRC, PTOX, PC
JCEXH0721XAG	4814;FR20905	X12 455SA	455@1761	251	149	1700@1000	308	104	SCRC, PTOX, PC
JCEXH0721XAG	4814;FR20854	X12 350	350@1761	190	113	1350@1000	241	81	SCRC, TOX, PC
JCEXH0721XAG	4814;FR20898	X12 365	365@1716	191	111	1250@1000	222	75	SCRC, PTOX, PC
JCEXH0721XAG	4814;FR20855	X12 370	370@1761	201	119	1350@1000	241	81	SCRC PTOX, PC
JCEXH0721XAG	4814;FR20856	X12 380	380@1761	206	122	1450@1000	262	88	SCRO, PTDX, PC
JCEXH0721XAG	4814;FR20857	X12 410	410@1761	223	133	1450@1000	262	88	SCRC, PTOX, PC
JCEXH0721XAG	4814;FR20859	X12 430	430@1761	235	139	1550@1000	283	95	SCRC, PTCX, PC
JCEXH0721XAG	4814;FR20860	X12 430	430@1761	235	139	1650@1000	300	101	SCRC, PTOX, PC
JCEXH0721XAG	4814;FR20861	X12 455	455@1761	251	149	1550@1000	283	95	SCRC, PTOX, PC
JCEXH0721XAG	4814;FR20904	X12 455	455@1761	251	149	1700@1000	308	104	SCRC, PTOX, PC
JCEXH0721XAG	4814;FR20752	X12 475	475@1761	266	158	1700@1000	308	104	SCRC, PTOX PC
JCEXH0721XAG	4814;FR20753	X12 500	500@1761	284	169	1695@1000	306	103	SCRC, PTOX, PC
JCEXH0721XAG	4814;FR20897	X12 350	350@1761	190	113	1350@1000	241	81	SCRC, PTOX, PC
JCEXH0721XAG	4814;FR20899	X12 365	365@1716	191	111	1250@1000	222	75	SCRC, PTOX, PC

DDJ, TC, CAC ECM, EGR, OC, PTOX, SCR-4, AMC A Hachment: Page 20/2 FO#: A-021-0687

1/2/2018

Engine Model Summary Template

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torqu	9.Emission Control	
JCEXH0721XAG	4814;FR20900	X12 380	380@1761	206	122	1450@1000	262	88	ŠÇRC, PTOX, ₽	
	Emergency	Ratings	Below							
JCEXH0721XAG	4814;FR20903	X12 455	455@1761	251	149	1550@1000	283	95	SCRC, PTOX, PO	
JCEXH0721XAG	4814;FR20969	X12 500	500@1761	284	169	1695@1000	306	103	SCRC, PTOX, PO	
	Urban Bus	Ratings	Below							
JCEXH0721XAG	4814;FR21008	X12 410	410@1761	223	133	1450@1000	262	88	SORC, PTOX, R	

ECM, EGK, OC, PTOX, SCR-U, AMOX

a vital