CALIFORNIA AIR RESOURCES BOARD	DETROIT DIESEL CORPORATION	EXECUTIVE ORDER A-290-0164 New On-Road Heavy-Duty Engines
104 II MAIR RESOURCES BOARD		Page 1 of 2 Pages

Pursuant to the authority vested in the California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL ENGINE FAMILY		INE FAMILY ENGINE FUE		STANDARDS & TEST	INTENDED SERVICE	ECS & SPECIAL FEATURES ³	DIAGNOSTIC 6		
TEAR		SIZES (L)		PROCEDURE	CLASS 2	DDI, TC, CAC, ECM, EGR, OC,	OBD(\$)		
2018	JDDXH12.8FED	12.8	Diesel	Diesel	HHDD	PTOX, SCR-U, AMOX			
	RIMARY ENGINE'S IDLE EMISSIONS CONTROL ⁵ 30g N/A								
ENGINE (L) ENGINE MODELS / CODES (rated power, in hp)									
12.8 See attachment for engine models and ratings									
* =not appli L=liter; hp	icable; GVWR=gross veh =horsepower; kw=kilowa	cle weight rating; 13 CC	R xyz=Title 13, California Code c	of Regulations, Sect	ion xyz; 40 CF	R 86.abc=Title 40, Code of Federal Regulation	s, Section 86.abc;		

¹ CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel; ² L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;

ECS=emission control system; TWC/CC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) =warmup catalyst; DPF=diesel particulate filter, PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/ super charger; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke putfi limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series;

ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD(F) / (P) / (\$)=full / partial / partial with a fine / on-board diagnostic;);

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.). ⁴

in g/bhp-hr	NMHC		NOx		NMHC+NOx		CO		PM		НСНО	
	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
STD	0.14	0.14	0.20	0.20	*	*	15.5	15.5	0.01	0.01	*	*
FEL	*	*	*	*	*	*	*	*	*	*	*	*
CERT	0.000	0.002	0.06	0.02	*	*	0.9	0.01	0.000	0.000	*	*
NTE	0.21		0.	.30		*	19	9.4	0.	02		*

⁴ g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: The manufacturer has demonstrated compliance with the Greenhouse Gas Emission Standards as specified in Title 13 CCR 1956.8 and the incorporated "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy Duty Diesel-Engines and Vehicles" (HDDE Test Procedures) adopted Dec. 12, 2002, as last amended Oct. 21, 2014 using the 2014 model year National Heavy-Duty Engine and Vehicle Greenhouse Gas Program as specified in Section 1036.108 of the HDDE Test Procedures. The manufacturer has submitted the required information and therefore has met the criteria necessary to receive a California Executive Order based on the Environmental Protection Agency's Certificate of Conformity for the above listed engine family.

	EPA CERTIFICATI	E OF CONFORMITY	PRIMARY INTENDED SERVICE CLASS TRACTOR/VOCATIONAL			
	JDDXH12	.8FED-002				
ln g/bhp-hr	C	:O ₂				
	FTP	SET	CH4	N ₂ O		
STD	555	460	0.10	0.10		
FCL	508	524	*	*		
FEL	523	540	0.10	0.10		
CERT	508	449	0.02	0.04		

⁴ g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; STD = standard or emission test cap; FEL=family emission limit; FCL=family certification level; CERT=certification level; CO₂=carbon dioxide; CH₄=methane; N₂O=nitrous oxide; VOCATIONAL=vocational engine; TRACTOR=tractor engine **BE IT FURTHER RESOLVED:** Certification to the FEL(s) / FCL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) / FCL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: That the manufacturer has elected to include engine models in this engine family which are identified for "emergency vehicle use only". These "emergency vehicle use only" engines are exempt from requirements imposed pursuant to California law and the regulations adopted pursuant thereto for motor vehicle pollution control devices per California Vehicle Code 27156.2. The manufacturer must clearly label these engines for "emergency vehicle use only" on the engines' emission control label.

BE IT FURTHER RESOLVED: The listed engine models are conditionally certified in accordance with 13 CCR Section 1971.1(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the heavy-duty on-board diagnostic (HD OBD) system of the listed engine models has been determined to have four deficiencies. The listed engine models are approved subject to the manufacturer paying a fine of \$75 per engine for the third through fourth deficiencies in the listed engine family that is produced and delivered for sale in California. On a quarterly basis, the manufacturer shall submit to the California Air Resources Board reports of the number of engines produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2018 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all engines covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per engine pursuant to HSC Section 43154.

BE IT FURTHER RESOLVED: The listed engine models are conditionally certified. These engine models may be sold and or marketed prior to Detroit Diesel Corporation updating the engines with revised HD OBD strategies approved by the California Air Resources Board. Detroit Diesel Corporation shall submit a recall plan pursuant to 13 CCR 1971.5 to the California Air Resources Board by March 31, 2018, to ensure that engine models produced under this conditional Executive Order are reprogrammed in the field to incorporate the California Air Resources Board approved revised HD OBD strategies. The aforementioned reprogramming shall be implemented free of charge based upon a plan approved by the California Air Resources Board approved revised HD OBD strategies. Engine models produced shall incorporate the California Air Resources Board approved revised HD OBD strategies will be deemed uncertified and shall be cause for California Air Resources Board to revoke the conditional Executive Order ab initio. Any engines introduced into commerce under the conditional Executive Order shall be deemed uncertified and subject to a civil penalty of up to \$37,500 per engine pursuant to HSC Section 43154.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of December 2017.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

ATTACHMENT 10F1

Engine Model Summary Template A-290-164

12/15/2017

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (Ibs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J193
JDDXH12.8FED	l (v & t)	DD13 1,2 box	380@1625	218.1	117.8	1450@1075	253.0	90.5	ECM, TC, CAC
JDDXH12.8FED		DD13 1,2 box	4 1 0@1625	235.5	127.2	1450@1075	253.0	90.5	EGR, PTOX
JDDXH12.8FED	II (v & t)	DD13 1,2 box	450@1625	259.4	140.1	1650@1075	289.1	103.4	OC, DDI
JDDXH12.8FED	III (v & t)	DD13 1 box	350@1625	200.7	108.5	1350@1075	235.6	84.3	AMOX, SCR-U
JDDXH12.8FED	IV (v & t)	DD13 1 box	370@1625	212.3	114.7	1250@1075	218.1	78.0	(all ratings)
JDDXH12.8FED	VI (v & t)	DD13 1 box	400@1625	229.7	124.1	1750@1075	307.8	110.0	(v =vocational)
JDDXH12.8FED	VII (v & t)	DD13 1,2 box	450@1625	259.4	140.1	1550@1075	270.8	96.8	(t = tractor)
JDDXH12.8FED		DD13 1,2 box	410@1625	235.5	127.2	1550@1075	270.8	96.8	
JDDXH12.8FED	VIII (v & t)	DD13 1 box	410@1625	235.5	127.2	1650@1075	289.1	103.4	
JDDXH12.8FED		DD13 1 box	410@1625	235.5	127.2	1450@1075	253.0	90.5	
JDDXH12.8FED	IX (v & t)	DD13 1,2 box	435@1625	250.3	135.2	1550@1075	270.8	96.8	
JDDXH12.8FED	XI (v & t)	DD13 1 box	470@1625	271.9	146.9	1650@1075	289.1	103.4	
JDDXH12.8FED	XII (v & t)	DD13 1 box	505@1625	295.8	159.8	1850@1075	327.3	117.0	
JDDXH12.8FED	XIII (v & t)	DD13 EVO Bus	410@1625	235.5	127.2	1450@1075	253.0	90.5	
JDDXH12.8FED	XIV (v & t)	DD13 EVO Bus	450@1625	259.4	140.1	1550@1075	270.8	96.8	
JDDXH12.8FED	XV (v & t)	DD13 FCCC	470@1625	271.9	146.9	1650@1075	. 289.1	103.4	
JDDXH12.8FED	XVII (v)	DD13 FCCC	525@1625	311.1	168.0	1850@1075	327.3	117.0	•
JDDXH12.8FED	XVIII (v & t)	DD13 coach	410@1625	235.5	127.2	1450@1075	253.0	90.5	
JDDXH12.8FED	XIX (v & t)	DD13 coach	450@1625	259.4	140.1	1550@1075	270.8	96.8	
JDDXH12.8FED	XX (v & t)	DD13 coach	450@1625	259.4	140.1	1650@1075	289.1	103.4	
JDDXH12.8FED	Emergency	Vehicle	Models	Below					ECM, TC, CAC
JDDXH12.8FED	XVI (v & t)	DD13 fire truck	505@1625	295.8	159. 8	1750@1075	307.8	110.0	EGR, PTOX
JDDXH12.8FED	XXI (v & t)	DD13 fire truck	470@1625	271.9	146.9	1650@1075	289.1	103.4	OC, DDI
JDDXH12.8FED	XXII (v)	DD13 fire truck	525@1625	311.1	168.0	1850@1075	327.3	117.0	AMOX, SCR-U