CALIFORNIA AIR RESOURCES BOARD	PACCAR INC.	EXECUTIVE ORDER A-384-0056 New On-Road Heavy-Duty Engines Page 1 of 2
-----------------------------------	-------------	---

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

DIAGNOSTIC <sup>6</sup> OBD(\$)	ECS & SPECIAL FEATURES <sup>3</sup>	INTENDED SERVICE	STANDARDS & TEST	FUEL TYPE <sup>1</sup>	ENGINE	MODEL ENGINE FAMILY			
	ECM, PTOX, EGR-C, SCR-U,	CLASS <sup>2</sup>	PROCEDURE	SIZES (L)		S			
	OC, DDI, TC, CAC	HHDD	Diesel	Diesel	12.9	JPCRH12.9M02	2018		
	TROL <sup>5</sup>	IISSIONS COM	TIONAL IDLE EN	ADD		ENGINE'S IDLE NS CONTROL 5			
30g N/A									
	p)	ted power, in	LS / CODES (ra	ENGINE MODE		L)	ENGINE (		
12.9 See attachment for engine models and ratings									
		odels and ra	t for engine m	See attachmer		L)	12.9 =not appli		

CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel; 2 L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;

ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction - urea / - ammonia; WU (prefix) =warm-Lessemission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter, PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/ super charger; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series; 5 ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(b); Exempt=exempted per 13 CCR 1956.8(a)(6) or for CNG/LNG fuel system; N/A=not applicable (e.g., Otto engines and vehicles); 6 EM=engine modification; 2 (CC 1975): DBUE/U/EU/(EMU/CHI/L) (prefix) / parallel; (2) (control / per bardy fictored tion); 7 EXEmption; Parallel; (2) (CC 1977): DBUE/U/EU/(EMU/CHI/L); Parallel; (2) (control / per bardy fictored tion); 8 END=engine modification; 2 (CC 1977): DBUE/U/EU/(EMU/CHI/L); 8 END=engine modification; 2

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD(F) / (P) / (\$)=full / partial / partial with a fine / on-board diagnostic;);

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in	NM	IHC	1	VOX	NMHO	C+NOx	C	0	F F	M	HC	но
g/bhp-hr	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
STD	0.14	0.14	0.20	- 0.20	*	*	15.5	15.5	0.01	0.01	*	*
CERT	0.000	0.000	0.11	0.13	*	*	0.1	0.01	0.001	0.001	*	*
NTE	0.	21	C	.30		*	19	9.4	0.	02		*

<sup>4</sup> g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: The manufacturer has demonstrated compliance with the Greenhouse Gas Emission Standards as specified in Title 13 CCR 1956.8 and the incorporated "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy Duty Diesel-Engines and Vehicles" (HDDE Test Procedures) adopted Dec. 12, 2002, as last amended Sep. 1, 2017 using the 2014 model year National Heavy-Duty Engine and Vehicle Greenhouse Gas Program as specified in Section 1036.108 of the HDDE Test Procedures. The manufacturer has submitted the required information and therefore has met the criteria necessary to receive a California Executive Order based on the Environmental Protection Agency's Certificate of Conformity for the above listed engine family.

	EPA CERTIFICATE	OF CONFORMITY	PRIMARY INTENDE	ED SERVICE CLASS			
	JPCRH12	.9M02-003	TRACTOR / VOCATIONAL				
in g/bhp-hr	С	O <sub>2</sub>	CH4	N2O			
	FTP	SET		N20			
STD	555	460	0.10	0.10			
FCL	495 .	459	*	*			
FEL	510	473	0.08	0.10			
CERT	485	450	0.02	0.04			

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; STD = standard or emission test cap; FEL=family emission lim VOCATIONAL=vocational engine; TRACTOR=tractor engine FCL=family certification level; CERT=certification level; CO2=carbon dioxide; CH4=methane; N2O=nitrous oxide;

BE IT FURTHER RESOLVED: Certification to the FEL(s) / FCL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) / FCL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

CALIFORNIA PACCAR INC. EXECUTIVE ORDER New On-Road Heavy-	
--	--

**BE IT FURTHER RESOLVED:** For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance) and 13 CCR 2035 et seq. (emission control warranty).

**BE IT FURTHER RESOLVED:** Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" (HDDE Test Procedures) adopted Dec. 12, 2002, as last amended Sep. 1, 2017, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

**BE IT FURTHER RESOLVED:** The listed engine models MX-13 380 E and MX-13 380EFE are conditionally certified in accordance with 13 CCR Section 1971.1 (k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the heavy-duty on-board diagnostic (HD OBD) system has been determined to have seven deficiencies, and therefore is approved subject to the manufacturer paying a fine of \$200 per engine for the third through seventh deficiencies in the listed engine family that is produced and delivered for sale in California. The listed engine model MX-13 360 E is conditionally certified in accordance with 13 CCR Section 1971.1 (k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the heavy-duty on-board diagnostic (HD OBD) system has been determined to have eight deficiencies, and therefore is approved subject to the manufacturer paying a fine of \$250 per engine for the third through eighth deficiencies in the listed engine family that is produced and delivered for sale in California. On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of engines produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2018 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all engines covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$5000 per engine pursuant to HSC Section 43154.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_

day of November 2017.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

ATTACHMENT 1 OF1 50 # : A - 384 - 0056DATE: 11 | 06 | 2017

## Engine Model Summary Template

	1-0100	ן וכ		4.Fuel Rate:				8.Fuel Rate	
Engine Family	1.Engine Code	2.Engine Model	3.BHP @RPM (SAE Gross)	(mm^3/stroke) @peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @peak HP (for diesels only)	6.Torque (ft-lb) @RPM (SEA Gross)	(mm <sup>*</sup> 3/stroke) @peak torque	÷ .	9.Emission Control Device Per SAE J1930
JPCRH12.9M02	510 hp	MX-13 380 E	510@1600	298.8	161.1	1850@1000	326.0	150.0	EC+DOC/DPF/SCR/EGR
JPCRH12.9M02	485 hp	MX-13 360 E	485@1600	282.1	152.1	1650@1000	291.9	147.5	EC/DOC/DPF/SCR/EGR
JPCRH12.9M02	510 hp	MX-13 380EFE	510@1600	298.8	161.1	1850@1000	326.0	150.0	EC/DOC/DPF/SCR/EGR
									ECM, EGR-C,
								PTO	x, scr-u, oci

DDi, TZ, CAC