DETROIT DIESEL CORPORATION



Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	ENGINE FAMILY	ENGINE	FUEL TYPE 1	STANDARDS & TEST	SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6			
YEAR		SIZES (L)		PROCEDURE	CLASS 2	DDI, TC, CAC, ECM, EGR, OC,	OBD(\$)			
2018	JDDXH07.7MDE	5.1, 7.7	5.1, 7.7 Diesel		MHDD	PTOX, SCR-U, AMOX	OPD(\$)			
PRIMARY ENGINE'S IDLE EMISSIONS CONTROL 5 ADDITIONAL IDLE EMISSIONS CONTROL 5										
	30g	N/A								
ENGINE (L) ENGINE MODELS / CODES (rated power, in hp)										
5.1	See attachment for engine models and ratings									
7.7	See attachment for engine models and ratings									
= not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc;										

L=liter; hp=horsepower; kw=kilowatt; hr=hour;

CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel;

ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD(F) / (P) / (\$)=full / partial / partial with a fine / on-board diagnostic;);

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO. SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in	NMHC		NOx		NMHC+NOx		CO		PM		нсно	
g/bhp-hr	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
STD	0.14	0.14	0.20	0.20	*	*	15.5	15.5	0.01	0.01	*	*
FEL					*	*					*	*
CERT	0.000	0.000	0.05	0.01	*	*	0.4	0.01	0.000	0.000	*	*
NTE	0.21		0.	30	*		19.4		0.02		*	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; NTE=Not-to-Exceet; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: The manufacturer has demonstrated compliance with the Greenhouse Gas Emission Standards as specified in Title 13 CCR 1956.8 and the incorporated "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy Duty Diesel-Engines and Vehicles" (HDDE Test Procedures) adopted Dec. 12, 2002, as last amended Oct. 21, 2014 using the 2014 model year National Heavy-Duty Engine and Vehicle Greenhouse Gas Program as specified in Section 1036.108 of the HDDE Test Procedures. The manufacturer has submitted the required information and therefore has met the criteria necessary to receive a California Executive Order based on the Environmental Protection Agency's Certificate of Conformity for the above listed engine family.

	EPA CERTIFICATI	OF CONFORMITY	PRIMARY INTENDED SERVICE CLASS TRACTOR/VOCATIONAL			
	JDDXH07	.7MDE-001				
n	C	O ₂	CH ₄	N ₂ O		
g/bhp-hr	FTP	SET	On4	1420		
STD	576	487	0.10	0.10		
FCL	523	479	*	*		
FEL	539	493	0.10	0.10		
CERT	521	466	0.02	0.04		

STD = standard or emission test cap; FEL=family emission lin
TRACTOR=tractor engine FEL=family emission limit: g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; VOCATIONAL=vocational engine; FCL=family certification level; CERT=certification level; CO₂=carbon dioxide; CH₄=methane; N₂O=nitrous oxide

³ ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) = warm-up catalyst; DPF=diesel particulate filter; PTOX=periodic trap oxidizer; HO25/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/ super charger, CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series;

5 ESS=engine shutdown system (per 13 CCR 1958 8/e)/SA/41; 20=20-28 NOV.



BE IT FURTHER RESOLVED: Certification to the FEL(s) / FCL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) / FCL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: The listed engine models are conditionally certified in accordance with 13 CCR Section 1971.1(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the heavy-duty on-board diagnostic (HD OBD) system of the listed engine models has been determined to have seven deficiencies for model DD8 and seventeen deficiencies for model DD5. The listed engine models DD8 and DD5 are approved subject to the manufacturer paying a fine of \$225 per engine model DD8 for the third through seventh deficiencies and \$500 per engine model DD5 for the third through seventhen deficiencies in the listed engine family that is produced and delivered for sale in California. On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of engines produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2018 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all engines covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$5000 per engine pursuant to HSC Section 43154.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

day of December 2017.

ATTACHMENTIOFI

Engine Model Summary Template A-290-0163

JDDXH07.7MDE II DD8 260@2200 119.4 87.4 720@1400 131.2 61.1 EGR, PTOX JDDXH07.7MDE III DD8 280@2200 128.4 94.0 800@1400 143.0 67.2 OC, DDI JDDXH07.7MDE IV DD8 300@2200 139.2 101.9 860@1400 155.1 72.2 AMOX, SCR-U JDDXH07.7MDE V DD8 330@2200 154.4 111.9 1000@1400 184.2 84.9 (all ratings) JDDXH07.7MDE VI DD8 350@2200 166.2 120.4 1050@1400 194.9 89.9 JDDXH07.7MDE VII DD8 375@2200 181.1 131.2 1050@1400 194.9 89.9 JDDXH07.7MDE VIII DD5 210@2200 139.4 68.8 575@1400 156.5 48.1 JDDXH07.7MDE IX DD5 230@2200 152.1 75.1 660@1400 181.8 55.9	Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7,Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torqu	9.Emission Control eDevice Per SAE J1930
JDDXH07.7MDE II DD8 260@2200 119.4 87.4 720@1400 131.2 61.1 EGR, PTOX JDDXH07.7MDE III DD8 280@2200 128.4 94.0 800@1400 143.0 67.2 OC, DDI JDDXH07.7MDE IV DD8 300@2200 139.2 101.9 860@1400 155.1 72.2 AMOX, SCR-U JDDXH07.7MDE V DD8 330@2200 154.4 111.9 1000@1400 184.2 84.9 (all ratings) JDDXH07.7MDE VI DD8 350@2200 166.2 120.4 1050@1400 194.9 89.9 JDDXH07.7MDE VII DD8 375@2200 181.1 131.2 1050@1400 194.9 89.9 JDDXH07.7MDE VIII DD5 210@2200 139.4 68.8 575@1400 156.5 48.1 JDDXH07.7MDE IX DD5 230@2200 152.1 75.1 660@1400 181.8 55.9										
JDDXH07.7MDE III DD8 280@2200 128.4 94.0 800@1400 143.0 67.2 OC, DDI JDDXH07.7MDE IV DD8 300@2200 139.2 101.9 860@1400 155.1 72.2 AMOX, SCR-U JDDXH07.7MDE V DD8 330@2200 154.4 111.9 1000@1400 184.2 84.9 (all ratings) JDDXH07.7MDE VI DD8 350@2200 166.2 120.4 1050@1400 194.9 89.9 JDDXH07.7MDE VIII DD8 375@2200 181.1 131.2 1050@1400 194.9 89.9 JDDXH07.7MDE VIII DD5 210@2200 139.4 68.8 575@1400 156.5 48.1 JDDXH07.7MDE IX DD5 230@2200 152.1 75.1 660@1400 181.8 55.9	JDDXH07.7MDE	1	DD8	260@2200	119.4	87.4	660@1400	120.3	56.0	ECM, TC, CAC
JDDXH07.7MDE IV DD8 300@2200 139.2 101.9 860@1400 155.1 72.2 AMOX, SCR-U JDDXH07.7MDE V DD8 330@2200 154.4 111.9 1000@1400 184.2 84.9 (all ratings) JDDXH07.7MDE VI DD8 350@2200 166.2 120.4 1050@1400 194.9 89.9 JDDXH07.7MDE VIII DD8 375@2200 181.1 131.2 1050@1400 194.9 89.9 JDDXH07.7MDE VIII DD5 210@2200 139.4 68.8 575@1400 156.5 48.1 JDDXH07.7MDE IX DD5 230@2200 152.1 75.1 660@1400 181.8 55.9	JDDXH07.7MDE	Н	DD8	260@2200	119.4	87.4	720@1400	131.2	61.1	EGR, PTOX
JDDXH07.7MDE V DD8 330@2200 154.4 111.9 1000@1400 184.2 84.9 (all ratings) JDDXH07.7MDE VI DD8 350@2200 166.2 120.4 1050@1400 194.9 89.9 JDDXH07.7MDE VII DD8 375@2200 181.1 131.2 1050@1400 194.9 89.9 JDDXH07.7MDE VIII DD5 210@2200 139.4 68.8 575@1400 156.5 48.1 JDDXH07.7MDE IX DD5 230@2200 152.1 75.1 660@1400 181.8 55.9	JDDXH07.7MDE	111	DD8	280@2200	128.4	94.0	800@1400	143.0	67.2	OC, DDI
JDDXH07.7MDE VI DD8 350@2200 166.2 120.4 1050@1400 194.9 89.9 JDDXH07.7MDE VII DD8 375@2200 181.1 131.2 1050@1400 194.9 89.9 JDDXH07.7MDE VIII DD5 210@2200 139.4 68.8 575@1400 156.5 48.1 JDDXH07.7MDE IX DD5 230@2200 152.1 75.1 660@1400 181.8 55.9	JDDXH07.7MDE	IV	DD8	300@2200	139.2	101.9	860@1400	155.1	72.2	AMOX, SCR-U
JDDXH07.7MDE VII DD8 375@2200 181.1 131.2 1050@1400 194.9 89.9 JDDXH07.7MDE VIII DD5 210@2200 139.4 68.8 575@1400 156.5 48.1 JDDXH07.7MDE IX DD5 230@2200 152.1 75.1 660@1400 181.8 55.9	JDDXH07.7MDE	V	DD8	330@2200	154.4	111.9	1000@1400	184.2	84.9	(all ratings)
JDDXH07.7MDE VIII DD5 210@2200 139.4 68.8 575@1400 156.5 48.1 JDDXH07.7MDE IX DD5 230@2200 152.1 75.1 660@1400 181.8 55.9	JDDXH07.7MDE	VI	DD8	350@2200	166.2	120.4	1050@1400	194.9	89.9	
JDDXH07.7MDE IX DD5 230@2200 152.1 75.1 660@1400 181.8 55.9	JDDXH07.7MDE	VII	DD8	375@2200	181.1	131.2	1050@1400	194.9	89.9	
	JDDXH07.7MDE	VIII	DD5	210@2200	139.4	68.8	575@1400	156.5	48.1	
200@2200	JDDXH07.7MDE	IX	DD5	230@2200	152.1	75.1	660@1400	181.8	55.9	
JDDXH07.7MDE X DD8 200@2200 119.4 87.4 660@1400 120.3 56.0	JDDXH07.7MDE	Х	DD8	260@2200	119.4	87.4	660@1400	120.3	56.0	