Pursuant to the authority vested in California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	ENGINE FAMILY	ENGINE FUEL TYP		STANDARDS & TEST		ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6					
		IPG	PROCEDURE SERVICE CLASS		TWC 2WR-HO2S HO2S SEL	OPD(P)						
2019	KKIIL00.0DW2	6.8	LIG	Otto	HDO	100, 200, 1023, 1023, 311	OBD(P)					
PRIMARY	ENGINE'S IDLE EMIS	SIONS CON	NTROL 5		ADDITIONA	AL IDLE EMISSIONS CONTROL						
	N/A					N/A						
ENGINE (L)			ENGINE M	ODELS / CODES (rate	d power, in hp)						
6.8		See Attachment										
* =not appli L=liter; hp 1 CNG/LJ 2 L/M/H H 3 ECS=er up catalyst; WR-HO2S= IDI/DDI=ind SPL=smoke	icable; GVWR=gross vet =horsepower; kw=kilowa KG=compressed/liquefied IDD=light/medium/heavy mission control system; 1 DPF=diesel particulate swide range oxygen sens tirrect/direct diesel injectic e puff limiter; ECM/PCM	hicle weight ra hitt; hr=hour; heavy-duty d rwc/oc=thre filter; PTOX= or; TBI=thrott n; TC/SC=tu =ongine/powe	LPG=liquefied (iesel; UB=urbar e-way/oxidizing periodic trap oxi le body fuel inject rbo/ super charg ertrain control mo	yz=Title 13, California C betroleum gas; E85=85 h bus; HDO=heavy duty catalyst; NAC=NOx ad dizer; HO2S/O2S=heat tion; SFI/MFI=sequent er; CAC=charge air co dule; EM=engine mod	code of Regulations, Section % ethanol fuel; MF=multi fi y Otto; sorption catalyst; SCR-U / vad/oxygen sensor; HAFS// ial/multi port fuel injection; oler; EGR / EGR-C=exhau fication; 2 (prefix)=paralle	n xyz; 40 CFR 86.abc=Title 40, Code of Federal Regula uel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel; SCR-N=selective catalytic reduction – urea / – ammoni AFS=heated/air-fuel-ratio sensor (a.k.a., universal or lin DGI=direct gasoline injection; GCARB=gaseous carbo st gas recirculation / cooled EGR; PAIR/AIR=pulsed/se k; (2) (suffix)=in series;	ations, Section 86.abc, a; WU (prefix) ≕warm- ear oxygen sensor); retor; condary air injection;					

⁵ ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS = internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD(F) / (P) / (\$)=full / partial / partial with a fine / on-board diagnostic;);

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.). ⁴

	NMHC		NOx		NMHC+NOx		CO		PM		НСНО	
	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
STD	0.14	*	0.20	*	*	+	14.4	*	0.01	*	0.01	*
CERT	0.08	*	0.13	*	*	*	3.3	*	0.000	*	0.001	*
NTE	*				÷ .		*		*		*	

⁴ g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: The manufacturer has demonstrated compliance with the Greenhouse Gas Emission Standards as specified in Title 13 CCR 1956.8 and the incorporated "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy Duty Otto Cycle Engines and Vehicles" (HDOE Test Procedures) adopted December 27, 2000, as last amended September 1, 2017 using the 2014 model year National Heavy-Duty Engine and Vehicle Greenhouse Gas Program as specified in Section 1036.108 of the HDOE Test Procedures. The manufacturer has submitted the required information and therefore has met the criteria necessary to receive a California Executive Order based on the Environmental Protection Agency's Certificate of Conformity for the above listed engine family.

	EPA CERTIFICATE C	FCONFORMITY	PRIMARY INTENDED SERVICE CLASS Vocational				
	KRIIE06.8B	WZ-005					
In	CO			№20 0.10			
g/bhp-hr	FTP	SET	CH4				
STD	627	*	0.10				
FCL	627	*	*	*			
FEL	646	*	0.10	0.10			
CERT	618	#	0.04	0.03			

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of December 2018.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

Engine Model Summary Template

ATTACHMENT 1 OF 1

A-344-0098 11/21/18

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
KRIIE06.8BWZ	KKE418NR5	E450 Incomplete	305@4250	NA	NA	420@3250	82.1	85.2	TWC/2WR-HO2S/ HO2S/SFI
KRIIE06.8BWZ	KKE418MR5	Same	Same	Same	Same	Same	Same	Same	Same
KRIIE06.8BWZ	KKE41LNR5	Same	Same	Same	Same	Same	Same	Same	Same
KRIIE06.8BWZ	KKE41LMR5	Same	Same	Same	Same	Same	Same	Same	Same
KRIIE06.8BWZ	KKE418QR5	Same	Same	Same	Same	Same	Same	Same	Same
KRIIE06 8BWZ	KKE418RR5	Same	Same	Same	Same	Same	Same	Same	Same
KRIIE06.8BWZ	KKE41LQR5	Same	Same	Same	Same	Same	Same	Same	Same
KRIIE06.8BWZ	KKE41LRR5	Same	Same	Same	Same	Same	Same	Same	Same