(2012-08-20)

Pursuant to the authority vested in the California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL		ENGINE	FUEL TYPE ¹	STANDARDS	INTENDED	ECS & SPECIAL FEATURES 3 DIAGN			
YEAR	ENGINE FAMILI	SIZES (L)		& TEST PROCEDURE	CLASS ²	DDI, TC, CAC, ECM, EGRC, DOC, PTOX, SCR-U, AMOX, NOXS(2)			
2019	KSZXH05.23FB	5.2	Diesel	Diesel	LHDD		OBD (F)		
PRIMARY	ENGINE'S IDLE			ADDITIONAL IDLE	EMISSIONS CO	NTROL ⁴			
	30g				N/A				
ENGINE (L)		EN	GINE MODELS / CODES	rated power, in	hp)			
5.2		4HK1TC / 523FB-1 (210)							
* =not appli	cable; GVWR=gross vehic	le weight rating; 1:	CCR xyz=Title 13, Cal	forma Code of Regulations, S	ection xyz; 40 CF	R 86.abc=Title 40, Code of Federal Regulation	ns, Section 86.abc;		

L=liter; hp=horsepower; kw=kilowatt; hr=hour; CNG/LNG=compressed/liquefied natural gas: LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel;

2 L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;

ECS=emission control system; TWC/CC=turbee-way/catalyst; NAC=NOx adsorption catalyst; SCRC=selective catalytic reduction convertor; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; PTOX=periodic trap oxidizar; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); NOXS=nitrogen oxide sensor; DBI=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; NOXS=nitrogen oxide sensor; DBI=direct gasoline injection; CC/SC=turbo/ super charger; CAC=charge air cooler; EGR / EGRC=sehaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series;

ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS = internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);

EMD=engine manufacturer diagnostic system ; OBD(F) / (P) / (\$)=full / partial / partial with fine / on-board diagnostic;

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in g/bhp-hr	NN	IHC	N	Ох	NMHO	C+NOx	C	:0	PM		НСНО	
	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
STD	0.14	0.14	0.20	0.20	*	+	15.5	15.5	0.01	0.01	*	*
FEL	*	*	*	*	*	*	*	*	*	*	*	*
CERT	0.001	0.000	0.18	0.01	*	*	0.1	0.04	0.002	0.000	*	*
NTE	0.	21	0.	75		*	19	9.4	0.	02		

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET= supplemental emissions testing; NTE=Not-to-Exceed emission limit; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: The manufacturer has demonstrated compliance with the Greenhouse Gas Emission Standards as specified in Title 13 CCR 1956.8 and the incorporated "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy Duty Diesel-Engines and Vehicles" (HDDE Test Procedures) adopted December 12, 2002, as last amended September 1, 2017, using the 2014 model year National Heavy-Duty Engine and Vehicle Greenhouse Gas Program as specified in Section 1036.108 of the HDDE Test Procedures. For the listed California-only engine family, the manufacturer has submitted the required greenhouse gas information.

	EPA CERTIFICA	TE OF CONFORMITY	PRIMARY INTENDED SERVICE CLASS VOCATIONAL			
	KSZXH	05.23FB-001				
in		CO2	04			
g/bhp-hr	FTP	SET	CH4	N ₂ O		
STD	576	*	0.10	0.10		
CL	576	*	*	*		
EL	593	*	*	*		
CERT	559	. *	0.02	0.06		

FCL=family certification level; CERT=certification level; CO2=carbon dioxide; CH4=methane; N2O=nitrous oxide; VOCATIONAL=vocational engine; TRACTOR=tractor engine



ISUZU MOTORS LTD.

BE IT FURTHER RESOLVED: Certification to the FEL(s) / FCL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) / FCL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance), and 13 CCR 2035 et seq. (emission control warranty).

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), 30g rating engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35. B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" adopted December 12, 2002, as last amended September 1, 2017, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of October 2018.

1enn nnette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

ENGINE MODEL SUMMARY

ENGINE FAMILY	ENGINE CODE	ENGINE MODEL	BHP@RPM (SAE Gross)	FUEL RATE: mm3/stroke @ peak HP	FUEL RATE: lbs/hr @ peak HP	TORQUE@RPM ft-lb	FUEL RATE: mm3/stroke @peak TORQUE	FUEL RATE: lbs/hr @peakTORQUE
KSZXH05.23FB	523FB-1	4HK1TC	210 @ 2500 (157 kW)	138.0	76.6	520 @ 1600 (705 N-m)	, 154.0	55.0

ENGINE	ENGINE	ENGINE	EMISSION CONTROL DEVICE Per SAE J1930
FAMILY	CODE	MODEL	
KSZXH05.23FB	523FB-1	4HK1TC	ECM, DDI, EGRC, CAC, TC, DOC, PTOX, SCR-U, AMOX, NOS(2)