

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	=======================================										
YEAR	ENGINE FAMILY	ENGINE SIZES (L)	FUEL TYPE 1		& TEST PROCEDURE	INTENDED SERVICE CLASS ²	ECS & SPECIAL FEATURES 3 DIAGNO				
2020	0 LGMXE06.6001 6.6 Ga		Gasoline		Otto	HDO	2TWC, 2HO2S(2), DGI	OBD(F)			
PRIMARY	NALIDLE EMISSIONS CONTROL 5										
ENCINE	N/A N/A										
	ENGINE (L) ENGINE MODELS / CODES (rated power, in hp)										
6.6 L8T / 70 (350)											
CNG/LN 2 L/M/H H 3 ECS=en catalyst; DI WR-HO2S= IDI/DDI=ind SPL=smoke ESS=en (per 13 CCF	= not applicable; GWWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; L=litter; hp=horsepower; kw=kilowatt; hr=hour; CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel; L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto; ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U/SCR-N=selective catalytic reduction = urea / ammonia; WU (prefix)=warm-up WR-HOZS=wide range exygen sensor; TBI=throttle body fuel injection; SFI/MF1=sequential/multi port fuel injection; DG=direct gasoline injection; GCARB=gaseous carburetor; BPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series; ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/fn NOx (per 13 CCR 1956.8(a)(6)(C); APS=internal combustion auxiliary power system; ALT=alternative method EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD(F) / (P) / (\$)=full / partial / partial with a fine / on-board diagnostic;);										

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.). 4

	NMHC		NOx		NMHC+NOx		CO		PM		нсно	
	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
TD	0.14	*	0.20	*	*	*	14.4	*	0.01	*	0.01	*
EL	*	*	0.12	*	*	*	*	*	*	*	*	*
CERT	0.06	*	0.05	*	*	*	1.7	*	0.002	*	0.000	*
NTE	*		*		*		*		*		*	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde:

BE IT FURTHER RESOLVED: The manufacturer has demonstrated compliance with the Greenhouse Gas Emission Standards as specified in Title 13 CCR 1956.8 and the incorporated "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy Duty Otto Cycle Engines and Vehicles" (HDOE Test Procedures) adopted December 27, 2000, as last amended December 19, 2018 using the 2014 model year National Heavy-Duty Engine and Vehicle Greenhouse Gas Program as specified in Section 1036.108 of the HDOE Test Procedures. The manufacturer has submitted the required information and therefore has met the criteria necessary to receive a California Executive Order based on the Environmental Protection Agency's Certificate of Conformity for the above listed engine family.

	EPA CERTIFICAT	E OF CONFORMITY	PRIMARY INTENDED SERVICE CLASS			
	LGMXE0	6.6001-002	Vocational			
In	C	O ₂				
g/bhp-hr	FTP	SET	CH4	N₂O		
STD	627	*	0.10	0.10		
FCL	627	*	*	*		
FEL	646	*	*	*		
CERT	606	*	0.04	0.003		

4 g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; STD = standard or emission test cap; FEL=family emission limit; FCL=family certification level; CERT=certification level; CO₂=carbon dioxide; CH₄=methane; N₂O=nitrous oxide; VOCATIONAL=vocational engine; TRACTOR=tractor engine

GENERAL MOTORS LLC



BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-006-2249 dated June 10, 2020.

Executed on this _____day of June 2020.

Allen Lyons, Chief

Emissions Certification and Compliance Division