VOLVO GROUP TRUCKS TECHNOLOGY



Pursuant to the authority vested in California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAM	y ENGINE		FUEL TYPE 1	STANDARDS & TEST	INTENDED SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC ⁶ OBD(P)			
	ENGINE I AIME		SIZES (L)		PROCEDURE	CLASS 2	TC, CAC, EGR, DDI, ECM, DOC,				
2020	LVPTH12.80	303	12.8	Diesel	Diesel	HHDD	PTÓX, SCR-U, AMOX	OBD(P)			
	ENGINE'S IDLE NS CONTROL 5			A	DDITIONAL IDLE EN	IISSIONS COI	NTROL 5				
30g		N/A									
ENGINE (L	-)	ENGINE MODELS / CODES (rated power, in hp)									
12.8		See attachments for engine models and ratings									

=not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; hp=horsepower; kw=kilowatt; hr=hour

CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E86=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel;

ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalystic reduction – urea / – ammonia; WU (prefix)=warm-up catalyst; DPF=diesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/super charger; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter, ECM/PCM=engine/powertrain control module, EM=engine module, EM=engine module, EM=engine shuldown system (net 13 CCR 1966 Palv/VAV4) - 28=285

ESS=engine shuldown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/nr NOx (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD(F) / (P) / (\$)=full / partial / partial with a fine / on-board diagnostic;);

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diésel" CO, SET and NTE certification compliancé may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in g/bhp-hr	NMHC		NOx		NMHC+NOx		CO		PM		нсно		
	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	
STD	0.14	0.14	0.20	0.20	*		15.5	15.5	0.01	0.01	- (*)	*	
CERT	0.002	0.001	0.08	0.04	*	*	1.2	0.00	0.000	0.000	*	*	
NTE	0.21		0.	0.30		*		19.4		0.02			

q/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit, CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde,

BE IT FURTHER RESOLVED: The manufacturer has demonstrated compliance with the Greenhouse Gas Emission Standards as specified in Title 13 CCR 1956.8 and the incorporated "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy Duty Diesel-Engines and Vehicles" (HDDE Test Procedures) adopted December 12, 2002, as last amended April 18, 2019 using the 2014 model year National Heavy-Duty Engine and Vehicle Greenhouse Gas Program as specified in Section 1036.108 of the HDDE Test Procedures. The manufacturer has submitted the required information and therefore has met the criteria necessary to receive a California Executive Order based on the Environmental Protection Agency's Certificate of Conformity for the above listed engine family.

	EPA CERTIFICAT	OF CONFORMITY	PRIMARY INTENDED SERVICE CLASS				
	LVPTH12	.8G03-003	TRACTOR/VOCATIONAL				
ln .		O ₂	aut.	0.21			
g/bhp-hr	FTP	SET	CH₄	N ₂ O			
STD	506	442	0.10	0.10			
FCL	515	445		*			
FEL	530	458	0.10	0.10			
CERT	512	442	0.02	0.07			

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; STD = standard or emission test cap; FEL=family emission limit; FCL=family certification level; CERT=certification level; CO2=carbon dioxide; TRACTOR=tractor engine CH4=methane; N2O=nitrous oxide; VOCATIONAL=vocational engine;



VOLVO GROUP TRUCKS TECHNOLOGY

EXECUTIVE ORDER A-242-0138 New On-Road Heavy-Duty Engines Page 2 of 2

BE IT FURTHER RESOLVED: Certification to the FEL(s) / FCL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) / FCL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance) and 13 CCR 2035 et seq. (emission control warranty).

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" (HDDE Test Procedures) adopted December 12, 2002, as last amended April 18, 2019, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

_ day of January 2020.

Allen Lyons, Chief

Emissions Certification and Compliance Division

Engine Model Summary Template = 0 16. A - 242 - 0138

Allachment: 1/1

12/30/2019

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM 1r (SAE Gross)	4,Fuel Rate: n/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HF (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
LVPTH12.8G03	SWrev-00	D13N - 455	455 @ 1700	226.0	152.0	1850 @ 1150	276.0	137.0	TC, CAC, EGR, DDI, ECM, DOC, PTOX, SCR, AMOX
LVPTH12,8G03	SWrev-00	D13N - 425	425 @ 1700	221.0	149.0	1750 @ 1050	262.0	130.0	TC, CAC, EGR, DDI, ECM, DOC, PTOX, SCR, AMOX
LVPTH12.8G03	SWrev-00	MP8 - 445E	455 @ 1700	226.0	152.0	1850 @ 1150	276.0	137.0	TC, CAC, EGR, DDI, ECM, DOC, PTOX, SCR, AMOX
LVPTH12.8G03	SWrev-00	MP8 - 415E	425 @ 1700	221.0	149.0	1750 @ 1050	262.0	130.0	TC, CAC, EGR, DDI, ECM, DOC, PTOX, SCR, AMOX