

ENGINE FAMILY

ENGINE

MODEL

FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-2383-1 New On-Road Heavy-Duty Engines Page 1 of 2

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

STANDARDS

INTENDED

SERVICE

YEAR	ENGINE FAI	SIZES (L)		FUEL TYPE	PROCEDURE	CLASS 2	ECS & SPECIAL FEATURES	DIAGNOSTIC					
2022	NEMVEO7 3	NFMXE07.3BX4		Flexible Fuel: Ethanol (E85) / Gasoline	Otto	HDO	TWC, SFI, HO2S, WR-HO2S	OBD(P)					
2022	2022 NFIVIXEU7.3BX4		7.3	Ethanol (E65) / Gasonile	Ollo	טטח	1 WC, 3FI, HO23, WK-HO23	ODD(P)					
	Y ENGINE'S IDLE ONS CONTROL 5		ADDITIONAL IDLE EMISSIONS CONTROL 5										
	N/A		N/A										
ENGINE (GINE (L) ENGINE MODELS / CODES (rated power, in hp)												
7.3		See attachment for engine models and ratings											
	* =not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; L=liter; hp=horsepower; kw=kilowatt; hr=hour;												
1 CNG/LI	NG=compressed/liqu	efied natur	al gas; LPG=liquefi	ed petroleum gas; E85 =85% etha	nol fuel; MF=multi	fuel a.k.a. BF=	bi fuel; DF =dual fuel; FF =flexible fuel;						
² L/M/H F	HDD=light/medium/h	eavy heavy	/-duty diesel; UB=ui	rban bus; HDO =heavy duty Otto;									
catalyst; D TBI =throttle	PF=diesel particulate body fuel injection;	filter; PT	OX=periodic trap oxi sequential/multi port	idizer; HO2S/O2S=heated/oxygen fuel injection; DGI=direct gasoline	sensor; HAFS/AF injection; GCARB	S=heated/air-fu =gaseous carb	ive catalytic reduction – urea / ammonia; WU iel-ratio sensor (a.k.a., universal or linear oxyge uretor; IDI/IDDI=indirect/direct diesel injection; in SPI space put limiter: ECMPCM-paging	n sensor); FC/SC =turbo/super					

charger; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; AMOX=Ammonia Oxidation Catalyst; NOXS=NOx sensor; 2 (prefix)=parallel; (2) (suffix)=in series;

ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS=internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD(**F**) / (**P**) / (**\$**)=full / partial with a fine / on-board diagnostic;);

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in	NMHC		NO	NOx NMHC		+NOx	CO		PM		нсно	
g/bhp-hr	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
STD	0.14 [0.14]	*	0.20 [0.20]	*	*	*	14.4 [14.4]	*	0.01 [0.01]	*	0.01 [0.01]	*
CERT	0.11 [0.09]	*	0.07 [0.06]	*	*	*	2.4 [5.5]	*	0.004 [0.01]	*	0.002 [0.001]	*
NTE	*		*		*		*		*		*	

4 g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: The manufacturer has demonstrated compliance with the Greenhouse Gas Emission Standards as specified in Title 13 CCR 1956.8 and the incorporated "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy Duty Otto Cycle Engines and Vehicles" (HDOE Test Procedures) adopted December 27, 2000, as last amended December 19, 2018.

	PRIMARY INTENDED SERVICE CLASS: Vocational										
In	CC	2	CH₄	N₂O							
g/bhp-hr	FTP	SET	On ₄	N ₂ O							
STD	627 [627]	*	0.10 [0.10]	0.10 [0.10]							
FCL	627 [627]	*	*	*							
FEL	646 [646]	*	0.10 [0.10]	0.10 [0.10]							
CERT	605 [618]	*	0.06 [0.04]	0.02 [0.02]							

4 g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; STD = standard or emission test cap; FEL=family emission limit; FCL=family certification level; CERT=certification level; CO₂=carbon dioxide; CH₄=methane; N₂O=nitrous oxide; VOCATIONAL=vocational engine; TRACTOR=tractor engine



FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-2383-1 New On-Road Heavy-Duty Engines Page 2 of 2

BE IT FURTHER RESOLVED: Certification to the FEL(s) / FCL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) / FCL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-010-2383 dated December 14, 2021.

Executed on this <u>day</u> of May 2022.

Allen Lyons, Chief

Johns Sahi for

Emissions Certification and Compliance Division

Attachment: Engine Models EO #: A-010-2383-1 Family: NFMXE07.3BX4 Attachment Last Revised: 3/25/2021

Model	Code	Trim	Config	Displacement	Displacement - Units	Peak Power	Peak Power - Units	Peak Power - Speed (rpm)	Peak Power - Fueling	Peak Power - Fuel Units	Peak Torque	Peak Torque - Units	Peak Torque - Speed (rpm)	Peak Torque - Fuel	Peak Torque - Fuel Units	OBD	GHG	Special	Notes
E-Series	NTE4JONJ	N/A	V8	7.3	Liters	325	horsepower	3750	105.0	mm3/stroke	450	lb-ft	3750	98	mm3/stroke	Partial	Vocational	N/A	SFI, HO2S, TWC, WR- HO2S
E-Series	NTE4JONK	N/A	V8	7.3	Liters	325	horsepower	3750	105.0	mm3/stroke	450	lb-ft	3750	98	mm3/stroke	Partial	Vocational	N/A	SFI, HO2S, TWC, WR- HO2S