

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

CTANDADDO INTENDED

MODEL YEAR	ENGINE FAM	ENGINE FAMILY		FUEL TYPE ¹	STANDARDS & TEST PROCEDURE	SERVICE CLASS 2	ECS & SPECIAL FEATURES ³	DIAGNOSTIC ⁶						
2022	NCEXH0540LDC 8.9			CNG/LNG	Diesel	HHDD	TBI, TC, CAC, ECM, EGR-C, TWC, HO2S(2)	OBD(F)						
PRIMARY ENGINE'S IDLE EMISSIONS CONTROL 5		ADDITIONAL IDLE EMISSIONS CONTROL 5												
E	Exempt	N/A												
ENGINE (L) ENGINE MODELS / CODES (rated power, in hp)														
8.9				See attachmen	t for engine mo	odels and ra	atings							
L=liter; hp 1 CNG/LI 2 L/M/H F 3 ECS=er catalyst; D TBI=throttle charger; C module; El 5 ESS=er	=horsepower; kw=ki NG=compressed/liqu HDD=light/medium/he mission control syste PF=cliesel particulate be body fuel injection; AC=charge air coole M=engine modification igne shutdown syste	lowatt; hr efied nature eavy heavy m; TWC/0 e filter; PT SFI/MFI= r; EGR / E on; AMOX em (per 13	=hour; ral gas; LPG=liquefir y-duty diesel; UB=ur OC=three-way/oxidizi OX=periodic trap oxi sequential/multi port EGR-C=exhaust gas =Ammonia Oxidatior CCR 1956.8(a)(6)(A)	ad petroleum gas; E85=85% etha ban bus; HDO=heavy duty Otto; ng catalyst; NAC=NOx adsorptio dizer; HO2S/O2S=heated/oxygen fuel injection; DGI=direct gasoline recirculation / cooled EGR; PAIR, I Catalyst; NOXS=NOx sensor; 2	nol fuel; MF=multin n catalyst; SCR-U / sensor; HAFS/AF einjection; GCARB AIR=pulsed/secont (prefix)=parallel; (; CR 1956.8(a)(6)(C);	fuel a.k.a. BF=I SCR-N=selecti S=heated/air-fu =gaseous carbi dary air injectior 2) (suffix)=in se APS =internal	combustion auxiliary power system; ALT=alter	(prefix)=warm-up n sensor); rC/SC=turbo/super powertrain control						

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD(F) / (P) / (\$)=full / partial / partial with a fine / on-board diagnostic;);

in	NM	НС	N	Ох	NMHC	*NOx	С	0	P	М	нсно	
g/bhp-hr	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
STD	0.14	0.14	0.02	0.02	*	*	15.5	15.5	0.01	0.01	*	*
CERT	0.01	0.000	0.01	0.004	*	*	1.5	0.3	0.002	0.000	*	*
NTE	0.21		0.30		*		19.4		0.02		*	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: The manufacturer has demonstrated compliance with the Greenhouse Gas Emission Standards as specified in Title 13 CCR 1956.8 and the incorporated "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy Duty Diesel-Engines and Vehicles" (HDDE Test Procedures) adopted December 12, 2002, as last amended April 18, 2019.

ln g/bhp-hr	C	CO ₂	011		
	FTP	SET	CH₄	N₂O	
STD	513	447	0.10	0.10	
FCL	485	427	*	*	
FEL	500	440	0.65	0.10	
CERT	465	414	0.56	0.01	

BE IT FURTHER RESOLVED: Certification to the FEL(s) / FCL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) / FCL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

CUMMINS INC.

EXECUTIVE ORDER A-021-0743
New On-Road Heavy-Duty Engines

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance) and 13 CCR 2035 et seq. (emission control warranty).

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" (HDDE Test Procedures) adopted December 12, 2002, as last amended April 18, 2019, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 7th day of September 2021.

Allen Lyons, Chief

Emissions Certification and Compliance Division

Attachment: Engine Models EO #: A-021-0743 Family: NCEXH0540LDC Attachment Last Revised: 8/10/2021

					Displacement -		Peak Power -	Peak Power -	Peak Power -	Peak Power - Fuel Peak Tor			Peak Torque -	Peak Torque - Fuel					
Model	Code	Trim	Config	Displacement	Units	Peak Power	Units	Speed (rpm)	Fueling	Units	Peak Torque	Units	Speed (rpm)	Peak Torque - Fuel	Units	OBD	GHG	Special	Notes
L9N 320	LH1	N/A	16	8.9	Liters	320	horsepower	2000	52.6	kg/hr	1000	lb-ft	1300	37.2	kg/hr	Full	Vocational	N/A	N/A
L9N 300	LH2	N/A	16	8.9	Liters	300	horsepower	2100	50.8	kg/hr	860	lb-ft	1300	33.9	kg/hr	Full	Vocational	N/A	N/A
L9N 280	LH3	N/A	16	8.9	Liters	280	horsepower	2200	48.1	kg/hr	900	lb-ft	1300	35.5	kg/hr	Full	Vocational	N/A	N/A
L9N 260	LH4	N/A	16	8.9	Liters	260	horsepower	2200	46.1	kg/hr	660	lb-ft	1300	25.4	kg/hr	Full	Vocational	N/A	N/A
L9N 250	LH5	N/A	16	8.9	Liters	250	horsepower	2000	44.3	kg/hr	730	lb-ft	1300	27.8	kg/hr	Full	Vocational	N/A	N/A
L9N 320	LH1	N/A	16	8.9	Liters	320	horsepower	2000	52.6	kg/hr	1000	lb-ft	1300	37.2	kg/hr	Full	Tractor	N/A	N/A
L9N 300	LH2	N/A	16	8.9	Liters	300	horsepower	2100	50.8	kg/hr	860	lb-ft	1300	33.9	kg/hr	Full	Tractor	N/A	N/A
L9N 280	LH3	N/A	16	8.9	Liters	280	horsepower	2200	48.1	kg/hr	900	lb-ft	1300	35.5	kg/hr	Full	Tractor	N/A	N/A
L9N 260	LH4	N/A	16	8.9	Liters	260	horsepower	2200	46.1	kg/hr	660	lb-ft	1300	25.4	kg/hr	Full	Tractor	N/A	N/A
L9N 250	LH5	N/A	16	8.9	Liters	250	horsepower	2000	44.3	kg/hr	730	lb-ft	1300	27.8	kg/hr	Full	Tractor	N/A	N/A