DETROIT DIESEL CORPORATION



Pursuant to the authority vested in California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAM	ENGINE FAMILY		FUEL TYPE ¹	STANDARDS INTENDED SERVICE PROCEDURE CLASS 2		ECS & SPECIAL FEATURES 3	DIAGNOSTIC ⁶					
2022	NDDX07.7N	NDDX07.7MDC		Diesel	Diesel MHDD		TC, CAC, EGR, DDI, ECM, OC, PTOX, SCR-U, AMOX	OBD(\$)					
	Y ENGINE'S IDLE ONS CONTROL 5	ADDITIONAL IDLE EMISSIONS CONTROL 5											
30g		N/A											
ENGINE (L)			ENGINE MODE	LS / CODES (ra	ted power, in	hp)						
5.1				See attachmen	t for engine m	odels and ra	atings						
7.7				See attachmen	t for engine m	odels and ra	atings						
* =not appli	icable: GVWP=gross	vehicle w	eight rating: 13 CCE	vvz=Title 13 California Code of	Regulations Section	n vvz: 40 CFR	86 abc=Title 40. Code of Federal Regulations	Section 86 abc:					

^{*=}not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; L=liter; hp=horsepower; kw=kilowatt; hr=hour;

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in	NM	IHC	NOx		NMHC+NOx		СО		PM		нсно	
g/bhp-hr	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
STD	0.14	0.14	0.20	0.20	*	*	15.5	15.5	0.01	0.01	*	*
FEL	*	* 0.20 0.20 * *		*	*	*	*	*	*			
CERT	0.03	0.003	0.08	0.02	*	*	0.5	0.01	0.001	0.000	*	*
NTE	0.21		0.30		*		19.4		0.02		*	

⁴ g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: The manufacturer has demonstrated compliance with the Greenhouse Gas Emission Standards as specified in Title 13 CCR 1956.8 and the incorporated "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy Duty Diesel-Engines and Vehicles" (HDDE Test Procedures) adopted December 12, 2002, as last amended April 18, 2019.

	PRIMARY INTENDED SERVICE CLASS: Tractor/Vocational											
In		CO ₂	CII	N.O.								
g/bhp-hr	FTP	SET	CH₄	N₂O								
STD	545	473	0.10	.010								
FCL	531	468	*	*								
FEL	546	482	0.10	0.10								
CERT	522	459	0.02	0.04								

⁴ g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; STD = standard or emission test cap; FEL=family emission limit; FCL=family certification level; CERT=certification level; CO₂=carbon dioxide; CH₄=methane; N₂O=nitrous oxide; VOCATIONAL=vocational engine; TRACTOR=tractor engine

BE IT FURTHER RESOLVED: Certification to the FEL(s) / FCL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) / FCL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

¹ CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel;

L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;

ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix)=warm-up catalyst; DPF=diesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFSi/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; TG/SC=turbo/super charger; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; AMOX=Ammonia Oxidation Catalyst, NOXS=NOx sensor; 2 (prefix)=parallel; (2) (suffix)=in series;

⁵ ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD(F) / (P) / (\$)=full / partial / partial with a fine / on-board diagnostic;);



DETROIT DIESEL CORPORATION

EXECUTIVE ORDER A-290-0184-1 New On-Road Heavy-Duty Engines

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance) and 13 CCR 2035 et seq. (emission control warranty).

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" (HDDE Test Procedures) adopted December 12, 2002, as last amended April 18, 2019, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

BE IT FURTHER RESOLVED: The listed engine models DD5 BUS XX, DD5 BUS XXI, DD5 BUS XXII, DD5 XXIII, DD5 XXIV, and DD5 XXV are conditionally certified in accordance with 13 CCR Section 1971.1 (k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the heavy-duty on-board diagnostic (HD OBD) system has been determined to have three deficiencies, and therefore is approved subject to the manufacturer paying a fine of \$25 per engine for the third in the listed engine family that is produced and delivered for sale in California. On a quarterly basis, the manufacturer shall submit to California Air Resources Board reports of the number of engines produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2022 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all engines covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$40,725 per engine pursuant to HSC Section 43154.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-290-0184 dated January 7, 2022.

Executed on this _____ day of July 2022.

Robin U. Lang, Chief

John Shi for

Emissions Certification and Compliance Division

Attachment: Engine Models EO #: A-290-0184-1 Family: NDDXH07.7MDC Attachment Last Revised: 7/12/2022

					Displacement -		Peak Power -	Peak Power -	Peak Power -	Peak Power -		Peak Torque -	Peak Torque -	Peak Torque -	Peak Torque -				
Model	Code	Trim	Config	Displacement	Units	Peak Power	Units	Speed (rpm)	Fueling	Fuel Units	Peak Torque	Units	Speed (rpm)	Fuel	Fuel Units	OBD	GHG	Special	Notes
DD8-DS-R	I		L6	7.7	Liters	330	horsepower	2200	111.9	lb/hr	1000	lb-ft	1400	84.9	lb/hr	Partial			
DD8-DS-R	II		L6	7.7	Liters	350	horsepower	2200	120.4	lb/hr	1050	lb-ft	1400	89.9	lb/hr	Partial			
DD8-DS-R	Ш		L6	7.7	Liters	375	horsepower	2200	131.2	lb/hr	1050	lb-ft	1400	89.9	lb/hr	Partial			
DD8-DS-F	IV		L6	7.7	Liters	330	horsepower	2200	111.9	lb/hr	1000	lb-ft	1400	84.9	lb/hr	Partial			
DD8-DS-F	V		L6	7.7	Liters	350	horsepower	2200	120.4	lb/hr	1050	lb-ft	1400	89.9	lb/hr	Partial			
DD8-DS-F	VI		L6	7.7	Liters	375	horsepower	2200	131.2	lb/hr	1050	lb-ft	1400	89.9	lb/hr	Partial			
DD8-DS-F	VII		L6	7.7	Liters	350	horsepower	2200	120.4	lb/hr	1050	lb-ft	1400	89.9	lb/hr	Partial			
DD8-SS-F	VIII		L6	7.7	Liters	260	horsepower	2200	87.4	lb/hr	720	lb-ft	1400	61.1	lb/hr	Partial			
DD8-SS-F	IX		L6	7.7	Liters	280	horsepower	2200	94.0	lb/hr	800	lb-ft	1400	67.2	lb/hr	Partial			
DD8-SS-F	X		L6	7.7	Liters	300	horsepower	2200	101.9	lb/hr	860	lb-ft	1400	72.2	lb/hr	Partial			
DD8-SS-F	XI		L6	7.7	Liters	260	horsepower	2200	87.4	lb/hr	660	lb-ft	1400	56	lb/hr	Partial			
DD8-SS-R	XIII		L6	7.7	Liters	260	horsepower	2200	87.4	lb/hr	720	lb-ft	1400	61.1	lb/hr	Partial			
DD8-SS-R	XIV		L6	7.7	Liters	280	horsepower	2200	94.0	lb/hr	800	lb-ft	1400	67.2	lb/hr	Partial			
DD8-SS-R	XV		L6	7.7	Liters	300	horsepower	2200	101.9	lb/hr	860	lb-ft	1400	72.2	lb/hr	Partial			
DD8-SS-R	XVI		L6	7.7	Liters	260	horsepower	2200	87.4	lb/hr	660	lb-ft	1400	56	lb/hr	Partial			
DD5	XVII		L4	5.1	Liters	200	horsepower	2200	64.9	lb/hr	560	lb-ft	1400	46.2	lb/hr	Partial			
DD5	XVIII		L4	5.1	Liters	220	horsepower	2200	72.4	lb/hr	560	lb-ft	1400	46.2	lb/hr	Partial			
DD5	XIX		L4	5.1	Liters	240	horsepower	2200	79.0	lb/hr	660	lb-ft	1400	55.4	lb/hr	Partial			
DD5 BUS	XX		L4	5.1	Liters	200	horsepower	2200	64.9	lb/hr	560	lb-ft	1400	46.2	lb/hr	Partial with Fines	5		
DD5 BUS	XXI		L4	5.1	Liters	220	horsepower	2200	72.4	lb/hr	560	lb-ft	1400	46.2	lb/hr	Partial with Fines	5		
DD5 BUS	XXII		L4	5.1	Liters	240	horsepower	2200	79.0	lb/hr	660	lb-ft	1400	55.4	lb/hr	Partial with Fines	5		
DD5	XXIII		L4	5.1	Liters	200	horsepower	2200	74.9	lb/hr	620	lb-ft	1400	52	lb/hr	Partial with Fines	5		
DD5	XXIV		L4	5.1	Liters	220	horsepower	2200	72.4	lb/hr	660	lb-ft	1400	55.4	lb/hr	Partial with Fines	5		
DD5	XXV		L4	5.1	Liters	240	horsepower	2200	79.0	lb/hr	660	lb-ft	1400	55.4	lb/hr	Partial with Fines	5		
DD5	XXVI		L4	5.1	Liters	200	horsepower	2200	74.9	lb/hr	620	lb-ft	1400	52	lb/hr	Partial			
DD5	XXVII		L4	5.1	Liters	220	horsepower	2200	72.4	lb/hr	660	lb-ft	1400	55.4	lb/hr	Partial			
DD5	XXVIII		L4	5.1	Liters	240	horsepower	2200	79.0	lb/hr	660	lb-ft	1400	55.4	lb/hr	Partial			