## **ROUSH INDUSTRIES INC.**



Pursuant to the authority vested in California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR ENGINE FAMILY		IILY	ENGINE SIZES (L)	FUEL TYPE <sup>1</sup>	STANDARDS & TEST PROCEDURE	INTENDED SERVICE CLASS <sup>2</sup>	ECS & SPECIAL FEATURES <sup>3</sup>	DIAGNOSTIC <sup>6</sup>						
2023 PRIIE07.3BL		3L3	7.3	LPG	Otto	HDO	TWC, HO2S, SFI, 2WR-HO2S	OBD(P)						
	PRIMARY ENGINE'S IDLE EMISSIONS CONTROL 5		ADDITIONAL IDLE EMISSIONS CONTROL 5											
	N/A		N/A											
ENGINE (L)			ENGINE MODELS / CODES (rated power, in hp)											
7.3	See Attachment													
* =not applicable: GVWP=gross vehicle weight rating: 13 CCP vvz=Title 13 California Code of Regulations, Section vvz: 40 CEP 86 abc=Title 40 Code of Federal Regulations, Section														

<sup>\*=</sup>not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; L=liter; hp=horsepower; kw=kilowatt; hr=hour;

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in	NMHC		N	Ox	NMHC+NOx		С	0	P	М	нсно	
g/bhp-hr	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
STD	0.14	*	0.02	*	*	*	14.4	*	0.01	*	0.01	*
CERT	0.05	*	0.01	*	*	*	4.5	*	0.000	*	0.004	*
NTE	*		*		*		*		1	ŧ	*	

<sup>4</sup> g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

**BE IT FURTHER RESOLVED:** That the listed engine family is certified to the Optional Low NOx Emission Standards as specified in 13 CCR 1956.8(c)(1)(B) and section 10.B.1 of the incorporated "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Otto-Cycle Engines and Vehicles" adopted December 27, 2000, as last amended September 9, 2021.

**BE IT FURTHER RESOLVED:** The manufacturer has demonstrated compliance with the Greenhouse Gas Emission Standards as specified in Title 13 CCR 1956.8 and the incorporated "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy Duty Otto Cycle Engines and Vehicles" (HDOE Test Procedures) adopted December 27, 2000, as last amended September 9, 2021.

	PRIMARY INTENDED SERVICE CLASS: Vocational											
In		CO <sub>2</sub>	OU.	11.0								
g/bhp-hr	FTP	SET	CH₄	N₂O								
STD	627	*	0.10	0.10								
FCL	627	*	*	*								
FEL	646	*	*	*								
CERT	556	*	0.03	0.02								

dybhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; STD = standard or emission test cap; FEL=family emission limit; FCL=family certification level; CERT=certification level; CO₂=carbon dioxide; CH₄=methane; N₂O=nitrous oxide; VOCATIONAL=vocational engine; TRACTOR=tractor engine

**BE IT FURTHER RESOLVED:** Certification to the FEL(s) / FCL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) / FCL(s) is the emission level declared by the manufacturer and serves in

<sup>1</sup> CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel;

L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;

ECS=emission control system; TWC/IOC-three-way/oxidizing catalyst; NCS=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix)=warm-up catalyst; DPF=diesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/super charger; CAC=charge air cooler; EGR / EGR,C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; AMOX=Ammonia Oxidation Catalyst; NOXS=NOx sensor; 2 (prefix)=parallel; (2) (suffix)=in series;

<sup>5</sup> ESS-engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/n NOx (per 13 CCR 1956.8(a)(6)(C); APS = internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD(F) / (P) / (\$)=full / partial / partial with a fine / on-board diagnostic;);



## **ROUSH INDUSTRIES INC.**

EXECUTIVE ORDER A-344-0158 New On-Road Heavy-Duty Engines Page 2 of 2

lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

**BE IT FURTHER RESOLVED:** For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 10th day of May 2023.

Robin U. Lang Robin U. Lang, Chief

**Emissions Certification and Compliance Division** 

Attachment: Engine Models EO #: A-344-0158 Family: PRIIE07.3BL3 Attachment Last Revised: 4/27/2023

					Displacement -		Peak Power -	Peak Power -	Peak Power -	Peak Power - Fue	I	Peak Torque -	Peak Torque -		Peak Torque - Fue	el			
Model	Code	Trim	Config	Displacement	Units	Peak Power	Units	Speed (rpm)	Fueling	Units	Peak Torque	Units	Speed (rpm)	Peak Torque - Fuel	l Units	OBD	GHG	Special	Notes
E-Series	PPE41FS R5	N/A	V8	7.3	Liters	335	horsepower	3750	N/A	N/A	468	lb-ft	3750	91.5	mm3/stroke		Vocatio nal	N/A	TWC, HO2S, SFI, 2WR- HO2S
E-Series	PPE41FV R5	N/A	V8	7.3	Liters	335	horsepower	3750	N/A	N/A	468	lb-ft	3750	91.5	mm3/stroke		Vocatio nal	N/A	TWC, HO2S, SFI, 2WR- HO2S
E-Series	PPE41FD R5	N/A	V8	7.3	Liters	335	horsepower	3750	N/A	N/A	468	lb-ft	3750	91.5	mm3/stroke		Vocatio nal	N/A	TWC, HO2S, SFI, 2WR- HO2S
Medium Duty	PPFC1FS R5	N/A	V8	7.3	Liters	335	horsepower	3750	N/A	N/A	468	lb-ft	3750	91.5	mm3/stroke		Vocatio nal	N/A	TWC, HO2S, SFI, 2WR- HO2S
Medium Duty	PPFC1FD R5	N/A	V8	7.3	Liters	335	horsepower	3750	N/A	N/A	468	lb-ft	3750	91.5	mm3/stroke		Vocatio nal	N/A	TWC, HO2S, SFI 2WR- HO2S
Medium Duty	PPFC1FV R5	N/A	V8	7.3	Liters	335	horsepower	3750	N/A	N/A	468	lb-ft	3750	91.5	mm3/stroke		Vocatio nal	N/A	TWC, HO2S, SFI 2WR- HO2S
Commerci	PPF41FS R5	N/A	V8	7.3	Liters	335	horsepower	3750	N/A	N/A	468	lb-ft	3750	91.5	mm3/stroke		Vocatio nal	N/A	TWC, HO2S, SFI 2WR- HO2S
Motorho me	PPF51FD R5	N/A	V8	7.3	Liters	335	horsepower	3750	N/A	N/A	468	lb-ft	3750	91.5	mm3/stroke		Vocatio nal	N/A	TWC, HO2S, SFI, 2WR- HO2S