## **DETROIT DIESEL CORPORATION**



Pursuant to the authority vested in California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAN	ENGINE FAMILY		FUEL TYPE <sup>1</sup>	STANDARDS & TEST PROCEDURE	INTENDED SERVICE CLASS <sup>2</sup>	ECS & SPECIAL FEATURES <sup>3</sup>	DIAGNOSTIC <sup>6</sup>					
2023	PDDXH15.6	GEC	15.6	Diesel	iesel Diesel		TC, CAC, EGR, DDI, ECM, OC, PTOX, SCR-U, AMOX	OBD(P)					
PRIMARY ENGINE'S IDLE EMISSIONS CONTROL 5			ADDITIONAL IDLE EMISSIONS CONTROL 5										
	30g	N/A											
ENGINE (	(L)			ENGINE MODELS / CODES (rated power, in hp)									
15.6				See attachmen	t for engine m	odels and ra	atings						
L=liter; hp  1 CNG/LI  2 L/M/H H  3 ECS=elecatalyst; D TBl=throttlecharger; C module; E  5 ESS=election	=horsepower; kw=k NG=compressed/liqu HDD=light/medium/h mission control syste IPF=diesel particulate body fuel injection; AC=charge air coole M=engine modification ingine shutdown syste	efied natur eavy heavy m; TWC/C e filter; PT SFI/MFI=: r; EGR / E on; AMOX em (per 13	=hour; ral gas; LPG=liquefic r-duty diesel; UB=ur OC=three-way/oxidizi OX=periodic trap oxi sequential/multi port GGR-C=exhaust gas =Ammonia Oxidatior CCR 1956.8(a)(6)(A	ad petroleum gas; E85=85% ethan bus; HDO=heavy duty Otto; ng catalyst; NAC=NOx adsorptior dizer; HO25/O25=heated/oxygen fuel injection; DGI=direct gasoline recirculation / cooled EGR; PAIR; Catalyst; NOXS=NOx sensor; 2	nol fuel; MF=multi n catalyst; SCR-U sensor; HAFS/AF injection; GCARE AIR=pulsed/secon (prefix)=parallel; (RR 1956.8(a)(6)(C);	fuel a.k.a. BF=  / SCR-N=select /S=heated/air-fuel / Sagaseous carb dary air injectior // Suffix)=in se / APS =internal	combustion auxiliary power system; ALT=alter	(prefix)=warm-up sensor); rC/SC=turbo/super powertrain control					

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diésel" CO, SET and NTE certification compliancé may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD(F) / (P) / (\$)=full / partial / partial with a fine / on-board diagnostic;);

in	NMHC		NOx		NMHC+NOx		СО		PM		нсно	
g/bhp-hr	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
STD	0.14	0.14	0.20	0.20	*	*	15.5	15.5	0.01	0.01	*	*
FEL	*	*	0.20	0.20	*	*	*	*	*	*	*	*
CERT	0.003	0.003	0.07	0.04	*	*	0.1	0.04	0.001	0.000	*	*
NTE	0.21		0.30		*		19.4		0.02		*	
4												

<sup>4</sup> g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: The manufacturer has demonstrated compliance with the Greenhouse Gas Emission Standards as specified in Title 13 CCR 1956.8 and the incorporated "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy Duty Diesel-Engines and Vehicles" (HDDE Test Procedures) adopted December 12, 2002, as last amended September 9, 2021.

	PRIMARY INTENDED SERVICE CLASS: Tractor and Vocational											
In	C	CO <sub>2</sub>										
g/bhp-hr	FTP	SET	CH₄	N <sub>2</sub> O								
STD	513	447	0.10	0.10								
FCL	517	449	*	*								
FEL	532	463	0.10	0.10								
CERT	505	444	0.02	0.07								

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; STD = standard or emission test included in the standard or emission test in STD = standard or emission test cap; FEL=family emission limit; VOCATIONAL=vocational engine; TRACTOR=tractor engine

BE IT FURTHER RESOLVED: Certification to the FEL(s) / FCL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) / FCL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.



## **DETROIT DIESEL CORPORATION**

EXECUTIVE ORDER A-290-0188
New On-Road Heavy-Duty Engines
Page 2 of 2

**BE IT FURTHER RESOLVED:** For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance) and 13 CCR 2035 et seq. (emission control warranty).

**BE IT FURTHER RESOLVED:** Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" (HDDE Test Procedures) adopted December 12, 2002, as last amended September 9, 2021, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>22nd</u> day of December 2022.

Robin U. Lang, Chief

Emissions Certification and Compliance Division

Attachment: Engine Models EO #: A-290-0188 Family: PDDXH15.6GEC Attachment Last Revised: 12/15/2022

								Displacement -		Peak Power -	Peak Power -	Peak Power -	Peak Power - Fue	el .	Peak Torque -	Peak Torque -	Peak Torque - Fuel					
Model	Code	Trim	Config	Displacement	Units	Peak Power	Units	Speed (rpm)	Fueling	Units	Peak Torque	Units	Speed (rpm)	Peak Torque - Fue	Units	OBD	GHG	Special	Notes			
DD16	1		L6	15.6	Liters	500	horsepower	1800	160.7	lb/hr	1850	lb-ft	1120	99	lb/hr	Partial						
DD16	II		L6	15.6	Liters	530	horsepower	1800	170.4	lb/hr	1850	lb-ft	1120	99	lb/hr	Partial						
DD16	III		L6	15.6	Liters	560	horsepower	1800	180.9	lb/hr	1850	lb-ft	1120	99	lb/hr	Partial						
DD16	IV		L6	15.6	Liters	600	horsepower	1800	194.9	lb/hr	1850	lb-ft	1120	99	lb/hr	Partial						
DD16	V		L6	15.6	Liters	560	horsepower	1800	180.9	lb/hr	2050	lb-ft	1120	134.2	lb/hr	Partial						
DD16	VI		L6	15.6	Liters	600	horsepower	1800	194.9	lb/hr	2050	lb-ft	1120	134.2	lb/hr	Partial						