

ENGINE

MODEL

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

STANDARDS

INTENDED

YEAR	ENGINE FAN	ENGINE FAMILY		FUEL TYPE 1	& TEST PROCEDURE	CLASS 2	ECS & SPECIAL FEATURES 3	DIAGNOSTIC ⁶						
2023	PCEXH0540	LDA	8.9	CNG/LNG	Diesel	MHDD	TBI, TC, CAC, ECM, EGR-C, TWC, HO2S(2)	OBD(F)						
	Y ENGINE'S IDLE ONS CONTROL 5		ADDITIONAL IDLE EMISSIONS CONTROL 5											
	Exempt				N/A									
ENGINE (GINE (L) ENGINE MODELS / CODES (rated power, in hp)													
8.9		See attachment for engine models and ratings												
L=liter; hp 1 CNG/LI 2 L/M/H I 3 ECS=electalyst; D TBI=throttle	=horsepower; kw=kl NG=compressed/liqu HDD=light/medium/he mission control syste PF=diesel particulate body fuel injection;	lowatt; hr efied nature eavy heavy m; TWC/0 e filter; PT SFI/MFI=:	=hour; ral gas; LPG=liquefi; r-duty diesel; UB=ur DC=three-way/oxidiz OX=periodic trap oxisequential/multi port	ed petroleum gas; E85=85% etha ban bus; HDO=heavy duty Otto; ing catalyst; NAC=NOx adsorptio dizer; HO2S/O2S=heated/oxyger fuel injection; DGI=direct gasoline	nol fuel; MF=multi n catalyst; SCR-U n sensor; HAFS/AF e injection; GCARE	fuel a.k.a. BF= SCR-N=select S=heated/air-fu =gaseous carb	86.abc=Title 40, Code of Federal Regulations, bi fuel; DF=dual fuel; FF=flexible fuel; ive catalytic reduction – urea / – ammonia; WU lel-ratio sensor (a.k.a., universal or linear oxyge uretor; IDI/DDI=indirect/direct diesel injection;	(prefix)=warm-up n sensor); TC/SC=turbo/super						
module; E	M=engine modification	n; AMOX	=Ammonia Oxidătior	n Catalyst; NOXS=NOx sensor; 2	(prefix)=parallel; (2) (suffix)=in se	n; SPL=smoke puff limiter; ECM/PCM=engine/ eries;	•						

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET, LLC, and 3B-MAW limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO and SET certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

5 ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD(F) / (P) / (\$)=full / partial / partial with a fine / on-board diagnostic;);

in	NMHC			NOx		NMHC+NOx			со			PM			нсно			
g/bhp-hr	FTP	SET	LLC	FTP	SET	LLC	FTP	SET	LLC	FTP	SET	LLC	FTP	SET	LLC	FTP	SET	LLC
STD	0.14	0.14	*	0.20	0.20	*	*	*	*	15.5	15.5	*	0.01	0.01	*	*	*	*
FEL	0.14	0.14	0.14	0.050	0.050	0.200	*	*	*	15.5	15.5	15.5	0.005	0.005	0.005	*	*	*
CERT	0.01	0.000	0.01	0.01	0.004	0.001	*	*	*	1.5	0.3	2.0	0.002	0.000	0.000	*	*	*
3B-MAW CF	2.0		2.0 *			2.0			2.0			*						

⁴ g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; LLC=low-load cycle; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; 3B-MAW CF= Three Binned Moving Average Window Conformity Factor; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: The listed engine models have been optionally certified to model year 2024-2026 requirements in title 13, CCR, sections 1956.8, 1968.2, 1971.1, 2035, 2036, 2112 and 2139 as specified in section I.15.B.4 of "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy Duty Diesel-Engines and Vehicles" (HDDE Test Procedures) adopted December 12, 2002, as last amended September 9, 2021.

BE IT FURTHER RESOLVED: The manufacturer has demonstrated compliance with the Greenhouse Gas Emission Standards as specified in Title 13 CCR 1956.8 and the incorporated "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy Duty Diesel-Engines and Vehicles" (HDDE Test Procedures) adopted December 12, 2002, as last amended September 9, 2021.

	PRIMARY INTENDED SERVICE CLASS: Tractor/Vocational												
In	C	CO ₂	CII	н о									
g/bhp-hr	FTP	SET	CH₄	N₂O									
STD	545	473	0.10	0.10									
FCL	485	427	*	*									
FEL	500	440	0.65	0.10									
CERT	465	414	0.56	0.01									

⁴ g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; STD = standard or emission test cap; FEL=family emission limit; FCL=family certification level; CERT=certification level; CO₂=carbon dioxide; CH₄=methane; N₂O=nitrous oxide; VOCATIONAL=vocational engine; TRACTOR=tractor engine

CUMMINS INC.



BE IT FURTHER RESOLVED: Certification to the FEL(s) / FCL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) / FCL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance) and 13 CCR 2035 et seq. (emission control warranty).

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [10 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" (HDDE Test Procedures) adopted December 12, 2002, as last amended September 9, 2021, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 27th day of December 2022.

Robin U. Lang, Chief

Emissions Certification and Compliance Division

Attachment: Engine Models EO #: A-021-0771 Family: PCEXH0540LDA Attachment Last Revised: 12/7/2022

					Displacement -		Peak Power -	Peak Power -	Peak Power -	Peak Power - Fuel Peak Torq			Peak Torque -	Peak Torque - Fuel					
Model	Code	Trim	Config	Displacement	Units	Peak Power	Units	Speed (rpm)	Fueling	Units	Peak Torque	Units	Speed (rpm)	Peak Torque - Fuel Units		OBD	GHG	Special	Notes
L9N 320	LM1	N/A	16	8.9	Liters	320	horsepower	2000	52.6	kg/hr	1000	lb-ft	1300	37.2	kg/hr	Full	Vocational	N/A	N/A
L9N 300	LM2	N/A	16	8.9	Liters	300	horsepower	2100	50.8	kg/hr	860	lb-ft	1300	33.9	kg/hr	Full	Vocational	N/A	N/A
L9N 280	LM3	N/A	16	8.9	Liters	280	horsepower	2200	48.1	kg/hr	900	lb-ft	1300	35.5	kg/hr	Full	Vocational	N/A	N/A
L9N 260	LM4	N/A	16	8.9	Liters	260	horsepower	2200	46.1	kg/hr	660	lb-ft	1300	25.4	kg/hr	Full	Vocational	N/A	N/A
L9N 250	LM5	N/A	16	8.9	Liters	250	horsepower	2000	44.3	kg/hr	730	lb-ft	1300	27.8	kg/hr	Full	Vocational	N/A	N/A
L9N 320	LM1	N/A	16	8.9	Liters	320	horsepower	2000	52.6	kg/hr	1000	lb-ft	1300	37.2	kg/hr	Full	Tractor	N/A	N/A
L9N 300	LM2	N/A	16	8.9	Liters	300	horsepower	2100	50.8	kg/hr	860	lb-ft	1300	33.9	kg/hr	Full	Tractor	N/A	N/A
L9N 280	LM3	N/A	16	8.9	Liters	280	horsepower	2200	48.1	kg/hr	900	lb-ft	1300	35.5	kg/hr	Full	Tractor	N/A	N/A
L9N 260	LM4	N/A	16	8.9	Liters	260	horsepower	2200	46.1	kg/hr	660	lb-ft	1300	25.4	kg/hr	Full	Tractor	N/A	N/A
L9N 250	LM5	N/A	16	8.9	Liters	250	horsepower	2000	44.3	kg/hr	730	lb-ft	1300	27.8	kg/hr	Full	Tractor	N/A	N/A