

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

**IT IS ORDERED AND RESOLVED:** The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	ENGINE SIZES (L)	FUEL TYPE <sup>1</sup>	STANDARDS & TEST PROCEDURE	INTENDED SERVICE CLASS <sup>2</sup>	ECS & SPECIAL FEATURES <sup>3</sup>	DIAGNOSTIC <sup>6</sup>
2023	PDDXH07.7MDC	5.1, 7.7	Diesel	Diesel	MHDD	TC, CAC, EGR, DDI, ECM, OC, PTOX, SCR-U, AMOX	OBD(P)
<b>PRIMARY ENGINE'S IDLE EMISSIONS CONTROL <sup>5</sup></b>		<b>ADDITIONAL IDLE EMISSIONS CONTROL <sup>5</sup></b>					
30g		N/A					
<b>ENGINE (L)</b>	<b>ENGINE MODELS / CODES (rated power, in hp)</b>						
5.1	See attachment for engine models and ratings						
7.7	See attachment for engine models and ratings						

<sup>\*</sup> =not applicable; **GVWR**=gross vehicle weight rating; **13 CCR xyz**=Title 13, California Code of Regulations, Section xyz; **40 CFR 86.abc**=Title 40, Code of Federal Regulations, Section 86.abc; L=liter; **hp**=horsepower; **kw**=kilowatt; **hr**=hour;  
<sup>1</sup> **CNG/LNG**=compressed/liquefied natural gas; **LPG**=liquefied petroleum gas; **E85**=85% ethanol fuel; **MF**=multi fuel a.k.a. **BF**=bi fuel; **DF**=dual fuel; **FF**=flexible fuel;  
<sup>2</sup> **L/M/H HDD**=light/medium/heavy heavy-duty diesel; **UB**=urban bus; **HDO**=heavy duty Otto;  
<sup>3</sup> **ECS**=emission control system; **TWC/OC**=three-way/oxidizing catalyst; **NAC**=NOx adsorption catalyst; **SCR-U / SCR-N**=selective catalytic reduction – urea / -- ammonia; **WU (prefix)**=warm-up catalyst; **DPF**=diesel particulate filter; **PTOX**=periodic trap oxidizer; **HO2S/O2S**=heated/oxygen sensor; **HAFS/AFS**=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); **TBI**=throttle body fuel injection; **SFI/MFI**=sequential/multi port fuel injection; **DGI**=direct gasoline injection; **GCARB**=gaseous carburetor; **IDI/DDI**=indirect/direct diesel injection; **TC/SC**=turbo/super charger; **CAC**=charge air cooler; **EGR / EGR-C**=exhaust gas recirculation / cooled EGR; **PAIR/AIR**=pulsed/secondary air injection; **SPL**=smoke puff limiter; **ECM/PCM**=engine/powertrain control module; **EM**=engine modification; **AMOX**=Ammonia Oxidation Catalyst; **NOXS**=NOx sensor; **2 (prefix)**=parallel; **(2) (suffix)**=in series;  
<sup>5</sup> **ESS**=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1)); **30g**=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C)); **APS**=internal combustion auxiliary power system; **ALT**=alternative method (per 13 CCR 1956.8(a)(6)(D)); **Exempt**=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; **N/A**=not applicable (e.g., Otto engines and vehicles);  
<sup>6</sup> **EMD**=engine manufacturer diagnostic system (13 CCR 1971); **OBD(F) / (P) / (S)**=full / partial / partial with a fine / on-board diagnostic;

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [ ] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.). <sup>4</sup>

in g/bhp-hr	NMHC		NOx		NMHC+NOx		CO		PM		HCHO	
	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
<b>STD</b>	0.14	0.14	0.20	0.20	*	*	15.5	15.5	0.01	0.01	*	*
<b>FEL</b>	*	*	0.20	0.20	*	*	*	*	*	*	*	*
<b>CERT</b>	0.03	0.003	0.08	0.02	*	*	0.5	0.01	0.001	0.000	*	*
<b>NTE</b>	0.21		0.30		*		19.4		0.02		*	

<sup>4</sup> **g/bhp-hr**=grams per brake horsepower-hour; **FTP**=Federal Test Procedure; **SET**=Supplemental emissions testing; **NTE**=Not-to-Exceed; **STD**=standard or emission test cap; **FEL**=family emission limit; **CERT**=certification level; **NMHC/HC**=non-methane/hydrocarbon; **NOx**=oxides of nitrogen; **CO**=carbon monoxide; **PM**=particulate matter; **HCHO**=formaldehyde;

**BE IT FURTHER RESOLVED:** The manufacturer has demonstrated compliance with the Greenhouse Gas Emission Standards as specified in Title 13 CCR 1956.8 and the incorporated "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy Duty Diesel-Engines and Vehicles" (HDDE Test Procedures) adopted December 12, 2002, as last amended September 9, 2021.

PRIMARY INTENDED SERVICE CLASS: Tractor and Vocational				
In g/bhp-hr	CO <sub>2</sub>		CH <sub>4</sub>	N <sub>2</sub> O
	FTP	SET		
<b>STD</b>	545	473	0.10	0.10
<b>FCL</b>	531	468	*	*
<b>FEL</b>	546	482	0.10	0.10
<b>CERT</b>	522	459	0.02	0.04

<sup>4</sup> **g/bhp-hr**=grams per brake horsepower-hour; **FTP**=Federal Test Procedure; **SET**=Supplemental emissions testing; **STD**=standard or emission test cap; **FEL**=family emission limit; **FCL**=family certification level; **CERT**=certification level; **CO<sub>2</sub>**=carbon dioxide; **CH<sub>4</sub>**=methane; **N<sub>2</sub>O**=nitrous oxide; **VOCATIONAL**=vocational engine; **TRACTOR**=tractor engine

**BE IT FURTHER RESOLVED:** Certification to the FEL(s) / FCL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) / FCL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

**BE IT FURTHER RESOLVED:** For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance) and 13 CCR 2035 et seq. (emission control warranty).

**BE IT FURTHER RESOLVED:** Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NO<sub>x</sub>] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" (HDDE Test Procedures) adopted December 12, 2002, as last amended September 9, 2021, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 22nd day of December 2022.



Robin U. Lang, Chief  
Emissions Certification and Compliance Division

**Attachment: Engine Models**

**EO #:** A-290-0185

**Family:** PDDXH07.7MDC

**Attachment Last Revised:** 12/13/2022

Model	Code	Trim	Config	Displacement	Displacement - Units	Peak Power	Peak Power - Units	Peak Power - Speed (rpm)	Peak Power - Fueling	Peak Power - Fuel Units	Peak Torque	Peak Torque - Units	Peak Torque - Speed (rpm)	Peak Torque - Fuel	Peak Torque - Fuel Units	OBD	GHG	Special	Notes
DD8-DS-R	I		L6	7.7	Liters	330	horsepower	2200	111.9	lb/hr	1000	lb-ft	1400	84.9	lb/hr	Partial			
DD8-DS-R	II		L6	7.7	Liters	350	horsepower	2200	120.4	lb/hr	1050	lb-ft	1400	89.9	lb/hr	Partial			
DD8-DS-R	III		L6	7.7	Liters	375	horsepower	2200	131.2	lb/hr	1050	lb-ft	1400	89.9	lb/hr	Partial			
DD8-DS-F	IV		L6	7.7	Liters	330	horsepower	2200	111.9	lb/hr	1000	lb-ft	1400	84.9	lb/hr	Partial			
DD8-DS-F	V		L6	7.7	Liters	350	horsepower	2200	120.4	lb/hr	1050	lb-ft	1400	89.9	lb/hr	Partial			
DD8-DS-F	VI		L6	7.7	Liters	375	horsepower	2200	131.2	lb/hr	1050	lb-ft	1400	89.9	lb/hr	Partial			
DD8-DS-F	VII		L6	7.7	Liters	350	horsepower	2200	120.4	lb/hr	1050	lb-ft	1400	89.9	lb/hr	Partial			
DD8-SS-F	VIII		L6	7.7	Liters	260	horsepower	2200	87.4	lb/hr	720	lb-ft	1400	61.1	lb/hr	Partial			
DD8-SS-F	IX		L6	7.7	Liters	280	horsepower	2200	94.0	lb/hr	800	lb-ft	1400	67.2	lb/hr	Partial			
DD8-SS-F	X		L6	7.7	Liters	300	horsepower	2200	101.9	lb/hr	860	lb-ft	1400	72.2	lb/hr	Partial			
DD8-SS-F	XI		L6	7.7	Liters	260	horsepower	2200	87.4	lb/hr	660	lb-ft	1400	56	lb/hr	Partial			
DD8-SS-R	XIII		L6	7.7	Liters	260	horsepower	2200	87.4	lb/hr	720	lb-ft	1400	61.1	lb/hr	Partial			
DD8-SS-R	XIV		L6	7.7	Liters	280	horsepower	2200	94.0	lb/hr	800	lb-ft	1400	67.2	lb/hr	Partial			
DD8-SS-R	XV		L6	7.7	Liters	300	horsepower	2200	101.9	lb/hr	860	lb-ft	1400	72.2	lb/hr	Partial			
DD8-SS-R	XVI		L6	7.7	Liters	260	horsepower	2200	87.4	lb/hr	660	lb-ft	1400	56	lb/hr	Partial			
DD5	XXVII		L4	5.1	Liters	200	horsepower	2200	64.9	lb/hr	560	lb-ft	1400	46.2	lb/hr	Partial			
DD5	XXVIII		L4	5.1	Liters	220	horsepower	2200	72.4	lb/hr	560	lb-ft	1400	46.2	lb/hr	Partial			
DD5	XIX		L4	5.1	Liters	240	horsepower	2200	79.0	lb/hr	660	lb-ft	1400	55.4	lb/hr	Partial			
DD5 BUS	XX		L4	5.1	Liters	200	horsepower	2200	64.9	lb/hr	560	lb-ft	1400	46.2	lb/hr	Partial			
DD5 BUS	XXI		L4	5.1	Liters	220	horsepower	2200	72.4	lb/hr	560	lb-ft	1400	46.2	lb/hr	Partial			
DD5 BUS	XXII		L4	5.1	Liters	240	horsepower	2200	79.0	lb/hr	660	lb-ft	1400	55.4	lb/hr	Partial			
DD5	XXIII		L4	5.1	Liters	200	horsepower	2200	74.9	lb/hr	620	lb-ft	1400	52	lb/hr	Partial			
DD5	XXIV		L4	5.1	Liters	220	horsepower	2200	72.4	lb/hr	660	lb-ft	1400	55.4	lb/hr	Partial			
DD5	XXV		L4	5.1	Liters	240	horsepower	2200	79.0	lb/hr	660	lb-ft	1400	55.4	lb/hr	Partial			
DD5	XXVI		L4	5.1	Liters	200	horsepower	2200	74.9	lb/hr	620	lb-ft	1400	52	lb/hr	Partial			
DD5	XXVII		L4	5.1	Liters	220	horsepower	2200	72.4	lb/hr	660	lb-ft	1400	55.4	lb/hr	Partial			
DD5	XXVIII		L4	5.1	Liters	240	horsepower	2200	79.0	lb/hr	660	lb-ft	1400	55.4	lb/hr	Partial			