## **California Environmental Protection Agency** FAIR RESOURCES BOARD

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The following on-road motor vehicles with a manufacturer's GVWR over 14000 pounds are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						•	ENGINE I	DESCRIPTION						
MANUFACTURER				MOE YEA		NE FAMILY	ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST PROCEDURE		INTENDED SERVICE CLASS <sup>2</sup>	ECS & SPECIAL FEATURES		
ISE CORPORATI			A-359-0006 200		9 9ISEH06.8GH		6.8	Gasoline	Otto		UB-Hybrid	EC, TWC, SFI, HO2S, Hyb Powertrain		
Gasoline, LPG	or Alci	ohol	Vehicles Or	ıly		•		VEHICLE D	ESCR	IPTION				
EVAPORATI FAMILY	EVAPORATIVE FUEL TANK CAPACITY FAMILY UL (K) (gallons)		Y	VEHICLE MODEL YEAR	VEHICLE MAKE & MODELS				ENGINE (L)	ENGINE MODELS / CODES {rated power, in hp}				
9ISEF0462AAA	150	5	110		2009	2009 New Flyer (GE40LF), NABI 42 (BRT-01)				6.8	F53-04 / 4F718Q0505 (310hp)			
A	ŵ		*			1		Ŵ		*		*		
* * *		*		*			*				*			
ak.	# % *		*			•		. *		*				
* *		A #			*	*		*				*		

-not applicable, GVWK=gross vehicle weight rating L=liter; K=100D miles; hp=horsepower; kw=kilowatt; t rating; 13 CCR xyz=Title 13, ( CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel; a. BF=bi fuel; DF=dual fuel; FF=fiexible fuel;

LIM/H BDD=ight/medium/heavy heavy-duty diesel; UB=urbanb us; HDD=heavy duty Otto;
LEM/H BDD=ight/medium/heavy heavy-duty diesel; UB=urbanb us; HDD=heavy duty Otto;
ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; WU (prefix) =warm-up catalyst; DPF=diasel particulate filter; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/airfuel-ratio sensor (a.k.a., universal or linection; CGARB=gaseous carbumator; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/super charge; CAC=charge air cooler; EGR=exhaust gas recirculation; PAIR/AIR=pulsed/secondary air injection; SPL=smoke put limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=paraile; (2) (suffix)=in series; (2004may25)

Following are: 1) the FTP exhaust emission standards or family emission limit(s) as applicable under 13 CCR 1956.1 (urban bus) or 13 CCR 1956.8 (other than urban bus); 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, in g/bhp-hr, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.1 or 13 CCR 1956.8 are in parentheses.)

	NMHC		NOx		NMHC+NOx		со		PM		нсно	
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	*		*	*		15.5	*	0.01	+	*	•
FEL	*	•	1.16		1.3			*	•	*	*	*
CERT	0.12		0.47	•	0.59		1.6		*	*	*	•
NTE				ŧ		*		*		*		*

of bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle; NTE=Not-to-Exceed emission limit; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

**BE IT FURTHER RESOLVED:** Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: The listed engine models have been certified to split engine family standards under 13 CCR 1956.8(b) [diesel engines] or 13 CCR 1956.8(d) [Otto engines] and the incorporated 40 CFR 86.007-15(m)(9).

BE IT FURTHER RESOLVED: The listed engine models have been certified to operate in the primary intended service class for urban buses with the emission compliance useful-life of 435,000 miles, 10 years, or 22,000 hours, whichever occurs first. The listed engine models were designed and certified for an emissions compliance period of 110,000 miles. To demonstrate the useful life emissions compliance of the intended service class of an urban bus, the engine manufacturer shall provide a required service to the engine at, or about, 110,000, 220,000, and 330,000 miles of the urban bus. The required service shall include a replacement engine, related parts and labor.

BE IT FURTHER RESOLVED: Each replacement engine may be: 1) a newly California certified urban bus engine of the model year in which the service interval occurs, 2) a new replacement engine in all material respects the same as the engines listed in this Executive Order, or 3) a newly remanufactured engine conforming to all specifications of the engines listed in this Executive Order or conforming to all specifications of newer model-year engines certified to the urban bus primary intended service class.

ISE Corporation	EXECUTIVE ORDER A-359-0007-1 New On-Road Heavy-Duty Motor Vehicles Page 2 of 2 pages

**BE IT FURTHER RESOLVED:** For the listed vehicle models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1976(b)(1)(F) {evaporative emission standards}, 13 CCR 2035 et seq. (emission control warranty), and 13 CCR 2235 [fill pipes and openings of motor vehicle fuel tanks].

Vehicles certified under this Executive Order must conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-359-0007 dated February 17, 2009.

Executed at El Monte, California on this \_\_\_\_\_\_\_ day of June 2009.

Annette Hebert, Chief Mobile Source Operations Division