Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following diesel or incomplete medium-duty vehicles (MDV) with a manufacturer's GVWR from 8501 to 14000 pounds are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGIN	IE FAMIL		ENGINE	EMISSION STD	FUEL TYPE 1	STANDARDS & TEST PROCEDURE		ENGINE	ECS & SPECIAL FEATURES 3	EF OBD
	HFMX	H06.7P4	B MAN	UFACTURER					(L)	ECS & SPECIAL FEATURES	
	EXECUTIVE ORDER			OTOD COMPAND	CATEGORY 2	Diesel	PROCEDURE		6.7	TC, DDI, CAC, ECM, EGRC,	O P P (#)
2017	A-0	A-010-2028		OTOR COMPANY	ULEV			Diesel		DOC, PTOX, SCRC(Urea), NOXS, RDQS	OBD(\$)
Gasolinë	, LPG or	Alcohol \	/ehicles Only	MACONSTITUTE Y	高级军务 经金额人	的。 1905年(1905年)	EHICLE	DESCRIP	TION	<b>"在这个人,但是是是一个人的人</b>	<b>经</b>
EVAPORATI FAMILY		/E UL (K)	FUEL TANK CAPACITY (gallons)	VEHICLE MODEL YEAR	VEHICLE MAKE & MODELS					ENGINE MODELS / CODES (rated power, In hp)	ENG. OBD
*		*	*	2017	Ford: F38	50 Incomplete	OBD(\$)		6.7	4V F-Series / HFE17N05 (330) Emergency Vehicle Rating: 4V F-Series / HFE17Q05 (330)	OBD(\$)

\*=not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; L=liter; hp=horsepower; kw=kilowatt, EF=engine family; (2006dec22) CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a BF=bi fuel; DF=dual fuel; FF=flexible fuel;

SULEV / ULEV / LEV=super ultra / ultra / low emission vehicle;

SULEY / ULEY - LEY = Super full of a view emission ventice;

SULEY / ULEY = Super full of a view emission ventice;

ECS = emission control system; TWC/IOC = three-way/oxidizing catalyst; SCRC=selective catalytic reduction convertor; RDQS=reductant quality sensor; WU (prefix) = warm-up catalyst;

DPF=diesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); NOXS=nitrogen oxides sensor; TBI=throttle body fuel injection; PMF=sequential/multi port fuel injection; DGI=direot gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indireot/direct diesel injection; TC/SC=turbo/super charger; CAC=charge air cooler; EGR / EGRC=exhaust gas recirculation / cooled EGR; PAIR/AIR=putsed/secondary air injection; PL=smoke puff limiter; OBD(F) / (P) / (S)=full / partial with a fine / on-board diagnostic; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series;

Following are: 1) the FTP exhaust emission standards or family emission limit(s) as applicable under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, in g/bhp-hr, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For dual- and flexible-fuel, the CERT values in brackets [] are those when tested on conventional test fuel.)

	NIV	NMHC		NOx		NMHC+NOx		co		PM		нсно	
	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	
STD	0.14	0.14	0.20	0.20	*	*	15.5	15.5	0.01	0.01	0.050	0.050	
CERT	0.02	0.000	0.14	0.15	*	*	0.5	0.04	0.01	0.003	0.002	0.007	
NTE	0.	0.21		0.30		*		19.4		0.02		0.075	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle; NTE=Not-to-Exceed emission limit; STD=standard or emission test cap, FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: The listed engine models have been certified to the optional emission standards and test procedures in 13 CCR 1956.8 applicable to diesel or incomplete MDV with a 8501-14000 pound GVWR and shall be subject to 13 CCR 2139(c) (in-use testing of engines certified for use in diesel or incomplete MDV with a 8501-14000 pound GVWR).

BE IT FURTHER RESOLVED: That the manufacturer has elected to include engine models in this engine family which are identified for "emergency vehicle use only". These "emergency vehicle use only" engines are exempt from requirements imposed pursuant to California law and the regulations adopted pursuant thereto for motor vehicle pollution control devices per California Vehicle Code Section 27156.2. The manufacturer must clearly label these engines for "emergency vehicle use only" on the engines' emission control label.

BE IT FURTHER RESOLVED: For the listed vehicle models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1968.2 (on-board diagnostic, full or partial compliance), 13 CCR 1976(b)(1)(B)-(C) or 13 CCR 1976(b)(1)(F) (evaporative emission standards), 13 CCR 2035 et seq. (emission control warranty), and 13 CCR 2235 [fill pipes and openings of motor vehicle fuel tanks]. (The braces {} are for gasoline, LPG or alcohol fueled vehicles only. The brackets [] are for gasoline or alcohol fueled vehicles only.)

## FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-2029 New Diesel or Incomplete Medium-Duty Vehicles Using Certified Engines Page 2 of 2

BE IT FURTHER RESOLVED: The listed engine models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the listed engine models has been determined to have three deficiencies. The listed engine models are approved subject to the manufacturer paying a fine of \$25 per engine for the third deficiency in the listed test group that is produced and delivered for sale in California. On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of engines produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2017 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all engines covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$5000 per engine pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

\_ day of December 2016

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division