A	CALIFORNIA AIR RESOURCES BOARD	
ACTIV	AIR RESOURCES BOARD	

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following on-road motor vehicles with a manufacturer's GVWR over 14000 pounds are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MANUFACTURER ROUSH INDUSTRIES, INC.				MOL YE/		NE FAMILY	ENGINE SIZES (L)	FUEL TYPE ¹	STANDARDS & TEST PROCEDURE Otto		INTENDED SERVICE CLASS ²	ECS & SPECIAL FEATURES TWC, HO2S, SFI, 2WR-HO2S ECM	
				201	18 JRIII	E06.8BWL	6.8	LPG			HDO		
Gasoline, LPG	or Alco	ohol	Vehicles Only	y				VEHICLE	DESCR	IPTION	1 1 1		
EVAPORATIVE			FUEL TANK		VEHICLE MODEL			MAKE & MODELS		ENGINE	ENGINE MODELS / CODES		
FAMILY	UL (P	()	(gallons)		YEAR					(L)	(rated power, in hp)		
JRIIF0265LPG			67.5, 93, 47	7			Blue Bird Vis	ion School Bus	Ŧ	Blue Bird Vision Bus / JJF618BR5; JJF618FR5 (320 hp for all codes)			
			45, 67.5			Roush Step Van				1.	Step Van / JJF410TR5; JJF417TR5; JJF41ATR5; JJF416TR5; JJF4178R5; JJF4168R5 (320 hp for all codes)		
	150	150 . 45	45, 67.5	5 2018			Roush N	lotor Home	6.8	Motor Home / JJF510TR5; JJF517TR JJF51ATR5; JJF516TR5; JJF5178R(JJF5168R5 (320 hp for all codes)			
		49, 53, 73, 67.5, 30, 50 35, 67.5			Roush F-650/750 Chassis Cab				F-650/750 Chassis Cab / JJFC10KR5; JJFC10RR5; JJFC178R5; JJFC10PR5 (320 hp for all codes)				
						Roush F-450/	h F-450/550 Chassis Cab			F-450/550 Chassis Cab / JJFA10CR5; JJFA17CR5; JJFA178R5 (320 for all codes)			

* =not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; L=ilter; K=1000 miles; hp=horsepower; kw=kilowatit; 1 CNO/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel;

L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban-bus; HDO=heavy duty Otto;

³ ECS-emission control system; TWC/OC=three-way/oxidizing catalyst; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/airfuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throtitle body fuel injection; SFI/MFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/super charger; CAC=charge air cooler; EGR=exhaust gas recirculation; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series; (2004may26)

Following are: 1) the FTP exhaust emission standards or family emission limit(s) as applicable under 13 CCR 1956.1 (urban bus) or 13 CCR 1956.8 (other than urban bus); 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, in g/bhp-hr, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.1 or 13 CCR 1956.8 are in parentheses.) ⁴

	NMHC		NOx		NMHC+NOx		со		PM		нсно	
	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
STD	0.14	*	0.05	*	*	*	14.4	*	0.01	*	0.01	*
ERT	0.06	*	0.01	*	*	*	5.0	*	0.002	*	0.001	*
NTE	*		* .		*		*		*		*	

* g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=supplemental emissions testing Steady-State Cycle; NTE=Not-to-Exceed emission limit; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: For the listed vehicle models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1976(b)(1)(F) {evaporative emission standards}, 13 CCR 2035 et seq. (emission control warranty), and 13 CCR 2235 [fill pipes and openings of motor vehicle fuel tanks].

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

CALIFORNIA AIR RESOURCES BOARD KI

ROUSH INDUSTRIES, INC.

This Executive Order hereby supersedes Executive Order A-344-0083 dated March 7, 2018.

FM day of September 2018. Executed at El Monte, California on this

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division