

## MITSUBISHI FUSO TRUCK AND BUS CORPORATION

EXECUTIVE ORDER A-361-0027
New On-Road Heavy-Duty Motor Vehicles

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following on-road motor vehicles with a manufacturer's GVWR over 14000 pounds are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						ENGINE D	ESCRIPTION					
MANUFACTURER				EL FN	GINE FAMILY	ENGINE SIZES -	FUEL TYPE 1	STANDARDS & TEST		INTENDED	ECS & SPECIAL FEATURES 3	
		ORDER		AR EN		(L)		PROCEDURE		CLASS 2	EGG & GI EGIAE I EATOREG	
POWER SOLUTIONS INTERNATIONAL INC.		A-415-0017 20		19 KPSIE06.0GAS		6.0	Gasotine	Otto		HDO	ECM, TWC, 2H02S(2), SFI	
Gasoline, LPG	or Alcoho	ol Vehicles O	nly				VEHICLE	DESCRIPTIO	N	THE STATE OF		
EVAPORATIVE FUEL TAN			VEHICLE		VE.110 - 111 / 1 110 - 1			ENGINE EN		GINE MODELS / CODES		
FAMILY	UL (K)	CAPACI (gallons		MODEL YEAR		VEHICLE MAKE & MODELS			(L)		(rated power, in hp)	
KMFTF0178EES						FUSO FE140 Gasoline						
	150	40		2019		FUSO FE160 Gasoline				50/ L96 (311), 55 / LC8 (311)		
						FUSO FE180 Gasoline						

<sup>\* =</sup>not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc, L=liter; K=1000 miles; hp=horsepower; kw=kilowatt;

Following are: 1) the FTP exhaust emission standards or family emission limit(s) as applicable under 13 CCR 1956.1 (urban bus) or 13 CCR 1956.8 (other than urban bus); 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, in g/bhp-hr, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.) 4

	NW.	NMHC		NOx		NMHC+NOx		СО		PM		нсно	
	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	
STD	0.14	*	0.20			*	14.4	*	0.01	•	0.01	*	
CERT	0.05		0.12				6.6	*	0.002	*	0.000		
NTE						*		•		*		•	

<sup>4</sup> g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=supplemental emissions testing Steady-State Cycle; NTE=Not-to-Exceed emission limit; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde.

BE IT FURTHER RESOLVED: For the listed vehicle models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1976(b)(1)(F) {evaporative emission standards}, 13 CCR 2035 et seq. (emission control warranty), and 13 CCR 2235 [fill pipes and openings of motor vehicle fuel tanks]. (The braces {} are for gasoline, LPG or alcohol fueled vehicles only.)

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_\_ day of January 2019.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel;

L/MH HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;

ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; WU (prefix) =warm-up cetalyst; DPF=diesel particulate filter; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC-turbo/super charger; CAC=charge rooler; EGR=exhaust gas recirculation; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series;