

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The following on-road motor vehicles with a manufacturer's GVWR over 14000 pounds are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						ENGINE DI	ESCRIPTION					
MANUFACTURE	. [EXECUTIVE		EL FN	INE FAMILY	ENGINE SIZES	FUEL TYPE 1	STANDARDS & TEST	INTENDED	ECS & SPECIAL FEATURES		
MANUFACTURER		ORDER		AR ENG	INE PAMILT	(L)		PROCEDURE	CLASS 2	ECS & SPECIAL PEATURES		
ROUSH INDUSTRIE INC.		A-344-0096		19 KR	IE06.8BW2	6.8	LPG	Otto	HDO	TWC, HO2S, SFI, 2WR-HO2S		
Gasoline, LPG o	r Alcoh	ol Vehicles O	nly		V ST	No. of San	VEHICLE	DESCRIPTION				
		FUEL TA		VEHICLI		VELHOLE M	WE & MODELS	ENGINE	EN	ENGINE MODELS / CODES		
FAMILY	UL (K)	(gallons		MODEL				(L)	(rated power, in hp)			
LRIIF0265LPG	150	47, 67.5, 93		2020	Blue Bird Vision School Bus			6.8	Blue Bird Vision Bus / KKFB18BR5; KKFB18FR5 (320 hp for all codes)			
*	* *			*			*	*		•		

*=not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; L=liter; K=1000 miles; hp=horsepower; kw=kilowatt;

Following are: 1) the FTP exhaust emission standards or family emission limit(s) as applicable under 13 CCR 1956.1 (urban bus) or 13 CCR 1956.8 (other than urban bus); 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, in g/bhp-hr, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.1 or 13 CCR 1956.8 are in parentheses.) 4

	NMHC		NOx		NMHC+NOx		CO		PM		нсно	
	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
STD	0.14	*	0.02	*	*	*	14.4	*	0.01	*	0.01	*
CERT	0.04	*	0.01	*	*	*	5.0	*	0.002	*	0.000	*
NTE	*				•		th the		*		*	

g/bhp-hr=grams per brake horsepower-hour. FTP=Federal Test Procedure; SET=supplemental emissions testing Steady-State Cycle; NTE=Not-to-Exceed emission limit; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter;

BE IT FURTHER RESOLVED: That the listed engine family is certified to the Optional Low NOx Emission Standards as specified in 13 CCR 1956.8(c)(1)(B) and section 10. B. 1 of the incorporated "California Exhaust Emission Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Otto-Cycle Engines and Vehicles" adopted December 27, 2000, as last amended December 19, 2018.

BE IT FURTHER RESOLVED: For the listed vehicle models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1976(b)(1)(F) {evaporative emission standards), 13 CCR 2035 et seq. (emission control warranty), and 13 CCR 2235 [fill pipes and openings of motor vehicle

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 29774

day of July 2019.

Emissions Certification and Compliance Division

L=liter; K=1000 miles; hp=horsepower; kw=kilowatt;

CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel;

LIM/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDD=heavy duty Otto;

ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) =warm-up catalyst; DP=diesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); WR-HO2S=wide range oxygen sensor; TBI=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; GCARB=gaseous carburator; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/ super charger; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series;