Tule

(Page 1 of 2)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER U-R-2-3

Relating to Certification of New Heavy-Duty Off-Road Equipment Engines

CUMMINS ENGINE COMPANY, INC.

Pursuant to the authority vested in the Air Resources Board by Sections 43000.5, 43013 and 43018 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following Cummins Engine Company, Inc. 1996 model-year engine, with rated power between 175 and 750 horsepower, and exhaust emission control systems are certified as described below for use in heavy-duty off-road equipment:

Typical Equipment Usage:

Agricultural Tractors, Construction/Mining Trucks, Snow Groomers, Logging Equipment

Fuel Type: Diesel

Engine Family	<u>Liters (C</u>	ubic Inches)	Exhaust Emission Control Systems and Special Features
TCE505R6DTRC (B413)	8.3	(505)	Turbocharger Charge Air Cooler

Engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The total hydrocarbons (THC), carbon monoxide (CO), nitrogen oxides (NOx), and particulate matters (PM) certification exhaust emission standards, in grams per brake horsepower-hour (g/bhp-hr), and the opacity of smoke emission standards, in percent (%), during acceleration (Accel), lugging (Lug), and peak (Peak) modes, for this engine family are (Title 13, California Code of Regulations, Section 2423):

Exhaust Emissions (g/bhp-hr)			Smoke Opacity (%)			
<u>THC</u>	<u>co</u>	<u>NOx</u>	<u>PM</u>	<u>Accel</u>	<u>Luq</u>	<u>Peak</u>
1.0	8.5	6.9	0.4	20	15	50

The THC, CO, NOx and PM exhaust emission certification values, in g/bhp-hr, and the opacity of smoke emission certification values, in percent (%), for this engine family are:

	<u>ıst Emission (g/bhp-hr)</u>			Smoke Opacity (%)			
Engine Family	THC	<u>co</u>	<u>NOx</u>	<u>PM</u> _	<u>Accel</u>	<u>Lug</u>	<u>Peak</u>
TCE505R6DTRC (B413)	0.3	0.5	5.4	0.2	7	2	16

BE IT FURTHER RESOLVED: That the listed engine models comply with the "Exhaust Emission Standards and Test Procedures--Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2423) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed engine models also comply with the "Emission Control Labels--1996 and Later Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2425 et seq.).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this

R. B. Summerfield

Assistant Division Chief Mobile Source Division

day of November 1995.

E.O. #	<u>u-R-2-3</u>		
Page	1 of 1		

1996 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET HEAVY-DUTY OFF-ROAD DIESEL ENGINES

Displacement: 505 / 8.3 Liters/Cubic Inches Eng Config: 2.6 All Codes in Eng Fam: CA 495 508 Cert Test Procedures: ARB EPA All Codes in Eng Fam: CA 495 508 Cert Test Procedures: ARB EPA All Codes in Eng Fam: CA 495 508 Cert Test Procedures: ARB EPA Avives/Ports per Cylinder 2 Strokes per Combustion Cycle 4 Maximum Rated Power: 240 HP (179 KW) @ 2200 RPM Ignition: Compression Compression Compression with Glow Plug Spark Fuel Type(s): Dedicated Flex-Fuel Dual Fuel Diesel M100 M85 Fuel Type(s): Dedicated Flex-Fuel Dual Fuel Diesel M100 M85 Fuel Type(s): Dedicated M200 M85 Fuel Type(s): Dedicated M300 M300 M300 M300	Manufacturer Cu	ummins Engine	Company, Inc.	Engine Famil	y (B413) TC	E505R6DTRC	
Strokes per Combustion Cycle 4 179 KW 2200 RPM							- 6
Maximum Rated Power: 240	All Codes in E	ng Fam: CA 🔲	49S 🔲 50S	☐ Cert Tes	t Procedures:	ARB 🛛 EPA	⊴
Maximum Rated Power: 240	Valves/Ports pe	er Cylinder	2	Strokes	per Combustion	Cycle 4	
Fuel Type(s): Dedicated M Flex-Fuel Disal Fuel Dissel M100 M85 CNG NG N	Maximum Rated	Power: 2	40 HP	(179	KW) @	2200	RPM_
CNG LNG LPG Other (specify)	Ignition: Comp	pression 🛮	Compressi	ion with Glow Plug]	Spar	k 🔲
Diesel Cert Fuel: 40 CFR 89.330-96 Other (specify) Primary Service Equipment: Aq Ttactors, Construction/Mining Trucks, Snow Groomers, and Logging Exhaust ECS (e.g., MFI, TC, CAC): TC,CAC (use abbreviations per SAE J1930 JUN93) Fingine Model (Eng Code) Rated HP (Eng Code) Rated HP (Rated HP (Rated HP (abs/hr))) 2062 240 & 2200 124(91.0) FP 392685 N/A	Fuel Type(s):	Dedicated 🛮	Flex-Fuel	Dual Fue	l 🔲 Diese	1 🛛 M100 🗀] м85 🗌
Primary Service Equipment: Aq Ttactors, Construction/Mining Trucks, Snow Groomers, and Logging Equipment		CNG 🔲 I	LNG LPG	☐ Other (specify)			
Equipment Exhaust ECS (e.g., MFI, TC, CAC): TC,CAC (use abbreviations per SAE J1930 JUN93) Fuel Rate (Bright Model) (Eng Code) (RMM) (R	Diesel Cert Fu	el: 40 CFR 89	9.330-96 🖾	Other (specify))	_	
Engine Model (Eng Code) Rated HP (RM Clbs/hr) Rate No. Rated HP (RM Clbs/hr) Rate No. Rate No. Rated HP (RM Clbs/hr) Rate No. Rate No. Rated HP (RM Clbs/hr) Rate No. Rate No		e Equipment:	Ag Ttactors, C	onstruction/Mining	Trucks, Snow G	roomers, and	Logging
Engine Model (Eng Code) Rated HF (Eng Code) Rated HF (Ring Code) 2062 3.3-C 240 @ 2200 124(91.0) FP 3926885 IN 3928229 N/A IN 3928229 N/A N/A N/A N/A N/A N/A N/A N/A N/A N/	Exhaust ECS (e	.g., MFI, TC,	CAC):	TC,CAC			
Engine Model (Eng Code) Rated HP (RPM Code) Rated				(use abbreviati	ions per SAE J	1930 JUN93)	1
2055 C8.3-C 215 @ 1900 122(76.7) FP 3930113 IN 3928229 2007 C8.3-C 215 @ 2200 110(80.6) FP 3926882 IN 3928229 N/A N/A N/A N/A N/A N/A N/A N/A N/A N/		ł	@ Rated HP mm³ / stroke	& Injector	· '	Valve	Catalytic Converter
2056 C8.3-C 2056 C8.3-C 215 @ 1900 122(76.7) FP 3930113 IN 3928229 2007 C8.3-C 215 @ 2200 110(80.6) FP 3926882 IN 3928229 N/A N/A N/A N/A N/A N/A N/A N/		240 @ 2200	124(91.0)		N/A	N/A	N/A
2007 C8.3-C 215 @ 2200	<u>∠055</u> C8.3-C	230 @ 2000	127(84.4)		N/A	N/A	N/A
2057 C8.3-C 230 @ 2200		215 @ 1900	122(76.7)		N/A	N/A	N/A
C8.3-C 230 @ 2200 120 (87.3) FP 3929837 N/A		215 @ 2200	110(80.6)	i	N/A	N/A	
evisions:		230 @ 2200	120 (87.3)		N/A	N/A	N/A
evisions:				-			
evisions:							
	te Issued:		1	1	ı	Ł	1
t tip tipe to the control of the con	evisions:						