(page 1 of 2)

## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER U-R-4-13

Relating to Certification of New Heavy-Duty Off-Road Equipment Engines

## DEERE POWER SYSTEM GROUP OF DEERE & COMPANY

Pursuant to the authority vested in the Air Resources Board by Sections 43000.5, 43013 and 43018 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following Deere Power System Group of Deere & Company 1996 model-year engine, with rated power between 175 and 750 horsepower, and exhaust emission control systems are certified as described below for use in heavy- duty off-road equipment:

Typical Equipment Usage: Agricultural Tractor

<u>Fuel Type</u>: Diesel

<u>Engine Family</u>	<u>Liters (Cubic Inches)</u>	Exhaust Emission Control Systems and Special Features
TJD10.RJDBRA	10.5 (644)	Turbocharger Charge Air Cooler Engine Control Module

Engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The total hydrocarbons (THC), carbon monoxide (CO), nitrogen oxides (NOx), and particulate matters (PM) certification exhaust emission standards, in grams per brake horsepower-hour (g/bhp-hr), and the opacity of smoke emission standards, in percent (%), during acceleration (Accel), lugging (Lug), and peak (Peak) modes, for this engine family are (Title 13, California Code of Regulations, Section 2423):

Exhaust Emissions (g/bhp-hr)				Smoke Opacity ( % )			
THC	<u>CO</u>	NOx	PM	<u>Accel</u>	Lug	<u>Peak</u>	
1.0	8.5	6.9	0.4	20	15	50	

DEERE POWER SYSTEMS GROUP OF DEERE & COMPANY EXECUTIVE ORDER U-R-4-13 (Page 2 of 2)

The THC, CO, NOx and PM exhaust emission certification values, in g/bhp-hr, and the opacity of smoke emission certification values, in percent (%), for this engine family are:

]	Exhaust 1	Emissio	n (g/bh	<u>o-hr)</u>	Smoke C	pacity	( % )
Engine Family	<u>THC</u>	<u>C0</u>	NOx	<u>PM</u>	<u>Accel</u>	Lug	<u>Peak</u>
TJD10.RJDBRA	0.2	0.9	5.3	0.1	17	4	35

BE IT FURTHER RESOLVED: That the listed engine models comply with the "Exhaust Emission Standards and Test Procedures--Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2423) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed engine models also comply with the "Emission Control Labels--1996 and Later Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2425 et seq.).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this 5 day of August 1996.

R. B. Summerfield Assistant Division Chief Mobile Source Division

16.03.03 - 550HA

Page 1 of 1

## 1996 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET **HEAVY-DUTY OFF-ROAD DIESEL ENGINES**

Mfgr: Deere Power Systems Group of Deere & Company Engine Family: TJD10.RJDBRA Displacement: 10.5 liters Eng Config: I-6 All Codes in Eng Fam: CA \_\_ 49S \_\_ 50S X Cert Test Procedures: ARB \_\_\_\_ EPA X Valves/Ports per Cylinder 4 Strokes per Combustion Cycle 4 Maximum Rated Power: <u>389</u> HP (<u>290</u> kW) @ <u>2100</u> RPM Compression with Glow Plug Ignition: Compression X Spark \_\_\_\_ Dedicated X Flex-Fuel Dual Fuel Diesel X M100 M85 Fuel Type(s): CNG LNG LPG Other (specify) Diesel Cert Fuel: 40 CFR 89.330-96(b)(2) Table 5 X Primary Service Equipment: Agricultural Tractor Exhaust ECS (e.g., MFI, TC, CAC): EX, EC, TC, CAC

(Use abbreviations per SAE J1930 JUN93)

Engine Model (Eng Code)	Rated HP @ RPM	Fuel Rate @ Rated	Fuel Pump & Injector Part No.	ECM/ PCM	EGR Valve	PTOX / Catalytic
ENQ: DE moll (SSOHA)		HP mm <sup>3</sup> / stroke (lbs/hr)		Part No.	Part No.	Converter Part No.
6105HF001A	389 @ 2100	193 (134)	RE63054 RE64866	SW377		
6105HRW01	316 @ 2100	154 (109)	RE63054 RE64866	SW279		
6105HF001B	322 @ 2100	159 (111)	RE63054 RE64866	SW378		
6105HF001C	350 @ 2100	174 (121)	RE63054 RE64866	SW379		
6105HF001D	375 @ 2100	187 (130)	RE63054 RE64866	SW380		
Date Issued:						
Revisions:	ŀ			1		