(page 1 of 2)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER U-R-4-15

Relating to Certification of New Heavy-Duty Off-Road Equipment Engines

DEERE POWER SYSTEM GROUP OF DEERE & COMPANY

Pursuant to the authority vested in the Air Resources Board by Sections 43000.5, 43013 and 43018 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following Deere Power System Group of Deere & Company 1997 model-year engine, with rated power between 175 and 750 horsepower, and exhaust emission control systems are certified as described below for use in heavy- duty off-road equipment:

Typical Equipment Usage: Agricultural Tractor, Loader, Generator Set

Fuel Type: Diesel

Engine Family	Displacement in Liters	Exhaust Emission Control <u>Systems and Special Features</u>		
VJD8.1R6DBRA (450HA)	8.1	Turbocharger Charge Air Cooler		

Engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The total hydrocarbons (THC), carbon monoxide (CO), nitrogen oxides (NOx), and particulate matters (PM) certification exhaust emission standards, in grams per brake horsepower-hour (g/bhp-hr), and the opacity of smoke emission standards, in percent (%), during acceleration (Accel), lugging (Lug), and peak (Peak) modes, for this engine family are (Title 13, California Code of Regulations, Section 2423):

Exhaust Emissions (g/bhp-)			Smoke Opacity (%)			
THC	<u>CO</u>	NOx		Accel	Lug	Peak
1.0	8.5	6.9	0.4	20	15	50

the state of the s

DEERE POWER SYSTEMS GROUP OF DEERE & COMPANY EXECUTIVE ORDER U-R-4-15 (Page 2 of 2)

The THC, CO, NOx and PM exhaust emission certification values, in g/bhp-hr, and the opacity of smoke emission certification values, in percent (%), for this engine family are:

	<u>Exhaust Emission (g/bhp-hr)</u>				<u>Smoke (</u>	Smoke Opacity (%)		
<u>Engine_Family</u>	THC	<u>C0</u>	NOx	PM	<u>Accel</u>	<u>Luq</u>	<u>Peak</u>	
VJD8.1R6DBRA (450HA)	0.4	1.0	6.0	0.2	12	4	18	

BE IT FURTHER RESOLVED: That the listed engine models comply with the "Exhaust Emission Standards and Test Procedures--Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2423) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed engine models also comply with the "Emission Control Labels--1996 and Later Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2425 et seq.).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this 23^{4} day of December 1996.

R. B. Summerfield, Chief Mobile Source Operations Division

_ . . .

LARGE ENGINE MODEL SUMMARY

Disce La history

Manufacturer. Deere Power Systems Group of Deere & Company

EPA Engine Female MJD8.1R6DBRA

	DO, HOUBHA	Manufacturer Fami	ly Name:	450HA			
E pre lode Er pre	BHP O RPM Mindre (SAE Gross)	Fuel Rate; mm/stroke @ peak HP (for diesel only)	Fuel Rate: (Ibs/hr) & peak HP (for diesets only)	Torque @ RPM (SEA Gross)	Fuel Rate; mm/stroke@peak torque	Fuel Rate; (Ibs/hr) Øpeak lorqu	Emission Control Device Per SAE J1930
<u>E 106 ode Ergne</u> A. 50 State-Codes . 6081HF0017 . 6081HF0016 . 6081HF0018 . 6081HF0018 . 6081HF007 . 6081HRW07 . 6081HRW08 . 6081HRW08 . 6081HRW08 . 6081HRW09 . 6081HRW03 . 6081HDW04 . 6081HDW04	Mode SAE Gross) 300@2200 300@2200 322@1800 268@2200 193@2200 217@2200 241@2200 200@2200 223@2200 247@2200 247@2200 275@2200 300@2100 182@2200 169@2000 219@2000 266@2100 303@2200	139@2200 139@2200 139@2200 175@1800 122@2200 92@2200 106@2200 106@2200 109@2200 109@2200 118@2200 125@2200 145@2100 94@2200 92@2000 119@2000 130@2100 143@2200	(bosh) 6 peak HP (for dissels only) 103@2200 106@1800 90@2200 67@2200 67@2200 84@2200 69@2200 69@2200 93@2200 101@2100 69@2200 61@2000 78@2000 90@2100 104@2200	Torque © RPM (SEA Gross) 1024 @ 1200 959@ 1400 N/A 871@ 1200 619@ 1400 712@ 1400 785@ 1200 641@ 1400 730@ 1400 805@ 1200 960@ 1500 841@ 1000 705@ 1000 781@ 1000 900@ 1200 962@ 1600	191@1200 172@1400 N/A 170@1200 120@1400 135@1400 135@1400 135@1400 124@1400 138@1400 161@1200 161@1200 175@1200 180@1500 164@1000 137@1000 150@1000 181@1200 176@1600	(lbs/hr) @peak lorqu 77@1200 81@1400 N/A 69@1200 55@1400 62@1400 62@1400 62@1200 57@1400 64@1200 71@1200 89@1500 55@1000 45@1000 55@1000 72@1200 93@1600	^a Emission Control Device Per SAE J1930 TC, CAC, EM TC, CAC, EM
6081HH004 6081HH006 6081HH002 6081HH003 6081HH01(6081HH011	267@2200 303@2200 276@2200 239@2200 276@2200 283@2200	126@2200 143@2200 131@2200 114@2200 131@2200 131@2200	92@2200 104@2200 95@2200 83@2200 95@2200 98@2200	847@1600 962@1600 877@1600 758@1600 877@1600 898@1600	155@1600 176@1600 160@1600 139@1600 160@1600 164@1600	93@1600 82@1600 93@1600 85@1600 73@1600 85@1600	TC, CAC, EM TC, CAC, EM TC, CAC, EM TC, CAC, EM TC, CAC, EM TC, CAC, EM TC, CAC, EM