

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER U-R-2-24

Relating to Certification of New Heavy-Duty Off-Road Equipment Engines

CUMMINS ENGINE COMPANY, INC.

Pursuant to the authority vested in the Air Resources Board by Sections 43000.5, 43013 and 43018 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following Cummins Engine Company Inc. 1998 model-year engine, with rated power between 175 and 750 horsepower, and exhaust emission control systems are certified as described below for use in heavy-duty off-road equipment:

Typical Equipment Usage: Crane, Tractor, Dozer, Pump, and Generator Set

Fuel Type: Diesel

<u>Engine Family</u>	<u>Liters (Cubic Inches)</u>	<u>Exhaust Emission Control Systems and Special Features</u>
WCEXL0505AAA (A412)	8.3 (505)	Turbocharger Charge Air Cooler

Engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The total hydrocarbons (THC), carbon monoxide (CO), nitrogen oxides (NOx), and particulate matters (PM) certification exhaust emission standards, in grams per brake horsepower-hour (g/bhp-hr), and the opacity of smoke emission standards, in percent (%), during acceleration (Accel), lugging (Lug), and peak (Peak) modes, for this engine family are (Title 13, California Code of Regulations, Section 2423):

<u>Exhaust Emissions (g/bhp-hr)</u>				<u>Smoke Opacity (%)</u>		
<u>THC</u>	<u>CO</u>	<u>NOx</u>	<u>PM</u>	<u>Accel</u>	<u>Lug</u>	<u>Peak</u>
1.0	8.5	6.9	0.4	20	15	50

The THC, CO, NOx and PM exhaust emission certification values, in g/bhp-hr, and the opacity of smoke emission certification values, in percent (%), for this engine family are:

<u>Engine Family</u>	<u>Exhaust Emission (g/bhp-hr)</u>				<u>Smoke Opacity (%)</u>		
	<u>THC</u>	<u>CO</u>	<u>NOX</u>	<u>PM</u>	<u>Accel</u>	<u>Lug</u>	<u>Peak</u>
WCEXL0505AAA (A412)	0.3	0.6	5.6	0.2	5	2	11


BE IT FURTHER RESOLVED: That the listed engine models comply with the "Exhaust Emission Standards and Test Procedures--Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2423) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed engine models also comply with the "Emission Control Labels--1996 and Later Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2425 et seq.).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this 11th day of February 1998.


R. B. Summerfield, Chief
Mobile Source Operations Division

LARGE ENGINE MODEL SUMMARY

Process Code: **New Submission**

Manufacturer: **Cummins Engine Company**

Manufacturer Family Name: **A412**

EPA Engine Family: **WCXLO505AAA**

8. Fuel Rate:
(lbs/hr)/peak torque Device Per SAE J1930

7. Fuel Rate:
mm/stroke/peak torque

5. Fuel Rate:
(lbs/hr) @ peak HP
(for diesels only)

4. Fuel Rate:
mm/stroke @ peak HP
(for diesel only)

3. BHP@RPM
(SAE Gross)

1. Engine Code 2. Engine Model

1. Engine Code	2. Engine Model	3. BHP@RPM (SAE Gross)	4. Fuel Rate: mm/stroke @ peak HP (for diesel only)	5. Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6. Torque @ RPM (SEA Gross)	7. Fuel Rate: mm/stroke/peak torque	8. Fuel Rate: (lbs/hr)/peak torque Device Per SAE J1930	9. Emission Control
1943								TC, CAC
FR 9874	C8.3-C	215@2200	111	82.3	642@1500	127	64.0	TC, CAC
FR 90181	C8.3-C	215@2200	111	82.3	642@1500	127	64.0	TC, CAC
FR 90239	C8.3-C	215@2200	111	82.3	642@1500	127	64.0	TC, CAC
FR 9873	C8.3-C	205@2200	106	78.9	636@1500	125	63.4	TC, CAC
FR 90178	C8.3-C	205@2200	106	78.9	636@1500	125	63.4	TC, CAC
FR 90118	C8.3-C	205@2200	106	78.9	636@1500	125	63.4	TC, CAC
FR 9871	C8.3-C	190@2200	98	73.0	590@1500	116	58.5	TC, CAC
FR 90042	C8.3-C	185@2200	96	71.0	575@1500	110	55.8	TC, CAC
FR 9870	C8.3-C	185@2200	96	71.0	575@1500	110	55.8	TC, CAC
FR 90330	C8.3-C	185@2200	96	71.0	575@1500	110	55.8	TC, CAC
FR 9869	C8.3-C	170@2200	92	68.0	560@1500	111	56.0	TC, CAC
FR 90225	C8.3-C	170@2200	92	68.0	520@1500	105	52.9	TC, CAC
CPL 2060								TC, CAC
FR 90043	C8.3-C	205@2000	115	77.6	636@1500	126	63.9	TC, CAC
FR 90113	C8.3-C	195@1900	112	71.8	563@1600	115	62.2	TC, CAC
FR 90044	C8.3-C	180@2000	98	66.2	575@1500	126	63.9	TC, CAC
FR 90168	C8.3-C	178@2000	100	67.5	626@1500	124	62.7	TC, CAC
FR 90114	C8.3-C	177@2100	95	67.4	575@1500	113	57.0	TC, CAC
FR 90117	C8.3-C	150@2200	80	59.1	475@1500	85	43.2	TC, CAC
CPL 2061								TC, CAC
FR 90177	C8.3-C	201@2500	99	83.7	574@1500	110	55.8	TC, CAC
FR 90041	C8.3-C	177@2500	87	73.7	507@1500	98	49.5	TC, CAC
CPL 2185								TC, CAC
FR 90040	C8.3-C	215@2500	106	89.1	610@1500	119	60.0	TC, CAC
CPL 2120								TC, CAC
FR 90119	C8.3-C	173@2380	87	68.9	496@1600	98	51.8	TC, CAC
FR 90353	C8.3-C	173@2300	89	69.0	496@1500	99	50.0	TC, CAC
CPL 2216								TC, CAC
FR 90240	C8.3-G	207@1800	125	75.9	181@1500	131	66.2	TC, CAC