## State of California AIR RESOURCES BOARD

EXECUTIVE ORDER U-R-5-31
Relating to Certification of New Heavy-Duty Off-Road Equipment Engines

## KOMATSU LTD.

Pursuant to the authority vested in the Air Resources Board by Sections 43000.5, 43013 and 43018 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following Komatsu Ltd. 1998 model-year engines with rated power between 175 and 750 horsepower and exhaust emission control systems are certified as described below for use in heavy-duty off-road equipment:

Typical Equipment Usage:

Excavator, Off-road Dump Truck

Fuel Type:

Diesel

| Engine Family              |      | lacement<br><u>Cubic Inches</u> | Exhaust Emission Control Systems and Special Features |
|----------------------------|------|---------------------------------|---|
| WKLXL15.2ED1<br>(SAA6D140) | 15.2 | 928                             | Turbocharger<br>Charge Air Cooler                     |

Engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The total hydrocarbons (THC), carbon monoxide (CO), nitrogen oxides (NOx), and particulate matter (PM) certification exhaust emission standards in grams per brake horsepower-hour (g/hp-h), and the opacity-of-smoke standards in percent (%) during acceleration (Accel), lugging (Lug), and peak (Peak) modes for this engine family are as follows (Title 13, California Code of Regulations, Section 2423):

| <u>Exhaus</u> | <u>st Emiss</u> | ions (g/l  | <u>np-h)</u> | _Smoke       | Opacity    | y (%)       |
|---------------|-----------------|------------|--------------|--------------|------------|-------------|
| THC           | <u>co</u>       | <u>NOx</u> | <u>PM</u>    | <u>Accel</u> | <u>Luq</u> | <u>Peak</u> |
| 1.0           | 8.5             | 6.9        | 0.4          | 20           | 15         | 50          |

The THC, CO, NOx, and PM exhaust emissions certification values in grams per brake horsepower-hour and the opacity-of-smoke certification values in percent for this engine family are:

| <u>Exhau</u> | st Emis   | sions (    | g/hp-h)   | Smoke        | <u>Opacity</u> | (%)         |
|--------------|-----------|------------|-----------|--------------|----------------|-------------|
| THC          | <u>co</u> | <u>NOx</u> | <u>PM</u> | <u>Accel</u> | <u>Lug</u>     | <u>Peak</u> |
| 0.2          | 0.6       | 6.1        | 0.2       | 16           | 6              | 24          |

BE IT FURTHER RESOLVED: That the listed engine models comply with the "Exhaust Emission Standards and Test Procedures--Heavy-Duty Off-Road Diesel-Cycle Engines" (Title 13, California Code of Regulations Section 2423) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed engine models also comply with the "Emission Control Labels--1996 and Later Heavy-Duty Off-Road Diesel-Cycle Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Sections 2425 et seq.).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this 44 day of July 1999.

R. B. Summerfield, Chief

Mobile Source Operations Division

## This page may contain Confidential Business Information

## LARGE ENGINE MODEL SUMMARY

Manufacturer: KOMATSU LTD.

EPA Engine Family: WKLXL15.2ED1

| 1.Engine Code | .Engine Code 2.Engine Model | 3. Rated<br>BHP@RPM<br>(SAE Gross) | <b>.</b>          | 5. Fuel Rate:<br>(lbs/hr) @ peak<br>HP | 6. Torque @ RPM<br>(SEA Gross) | 7. Fuel Rate:<br>mnvstroke@peak<br>torque | 8. Fuel Rate:<br>(lbs/hr)@peak<br>torque | 9. Emission Control<br>Device Per SAE J1930 |
|---------------|-----------------------------|------------------------------------|-------------------|--|--------------------------------|---|--|---|
|               |                             |                                    | (nor aleser only) | (in diesers only)                      |                                |   |  |   |
| K6            | SAA6D140E-2                 | 525 @ 2100                         | 257               | 177                                    | 1641 @ 1500                    | 300                                       | 148                                      | EM TC CAC                                   |
| Κ7            | SAA6D140E-2                 | 473 @ 1800                         | 269               | 159                                    | 1590 @ 1350                    | 294                                       | 131                                      | EM TC CAR                                   |
| <b>8</b> 8    | SAA6D140E-2                 | 508 @ 2000                         | 259               | 171                                    | 1598 @ 1400                    | 297                                       | 137                                      | EM TC CAC                                   |