

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER U-R-12-19-1

Relating to Certification of New Heavy-Duty Off-Road Equipment Engines

NAVISTAR INTERNATIONAL TRANSPORTATION CORP.

Pursuant to the authority vested in the Air Resources Board by Sections 43000.5, 43013 and 43018 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following Navistar International Transportation Corp., 1998 model-year engine, with rated power between 175 and 750 horsepower, and exhaust emission control systems are certified as described below for use in heavy-duty off-road equipment:

Typical Equipment Usage: Loaders, Tractors, Pumps and Compressors

Fuel Type: Diesel

<u>Engine Family</u>	<u>Liters (Cubic Inches)</u>	<u>Exhaust Emission Control Systems and Special Features</u>
WNVXLO466BNA (DT-466)	7.8 (466)	Turbocharger Smoke Puff Limiter

Engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The total hydrocarbons (THC), carbon monoxide (CO), nitrogen oxides (NOx), and particulate matters (PM) certification exhaust emission standards, in grams per brake horsepower-hour (g/bhp-hr), and the opacity of smoke emission standards, in percent (%), during acceleration (Accel), lugging (Lug), and peak (Peak) modes, for this engine family are (Title 13, California Code of Regulations, Section 2423):

<u>Exhaust Emissions (g/bhp-hr)</u>				<u>Smoke Opacity (%)</u>		
<u>THC</u>	<u>CO</u>	<u>NOx</u>	<u>PM</u>	<u>Accel</u>	<u>Lug</u>	<u>Peak</u>
1.0	8.5	6.9	0.4	20	15	50

The THC, CO, NOx and PM exhaust emission certification values, in g/bhp-hr, and the opacity of smoke emission certification values, in percent (%), for this engine family are:

<u>Engine Family</u>	<u>Exhaust Emission (g/bhp-hr)</u>				<u>Smoke Opacity (%)</u>		
	<u>THC</u>	<u>CO</u>	<u>NOx</u>	<u>PM</u>	<u>Accel</u>	<u>Lug</u>	<u>Peak</u>
WNVXLO466BNA (DT-466)	0.1	1.2	6.6	0.1	18	8	32

BE IT FURTHER RESOLVED: That the listed engine models comply with the "Exhaust Emission Standards and Test Procedures--Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2423) for the aforementioned model year.


BE IT FURTHER RESOLVED: That the listed engine models also comply with the "Emission Control Labels--1996 and Later Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2425 et seq.).

Executive Order U-R-12-19, dated January 7, 1998, is hereby superseded by Executive Order U-R-12-19-1.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this 14th day of January 1998.


R. B. Summerfield, Chief
Mobile Source Operations Division

LARGE ENGINE MODEL SUMMARY

Manufacturer: **Navistar** E.O. # **U-R-12-19-1** Process Code: **New Submission**

EPA Engine Family: **WNVXL0466BNA** Manufacturer Family Name: **DT-466**

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque Device Per SAE J1930	9.Emission Control
IA160	IA160	160@2200	87.5	64.5	475@1600	107.0	57.3	DI, TC, SPL
IA170	IA170	170@2500	73.1	61.2	455@1700	91.3	52.0	DI, TC, SPL
IA180	IA180	180@2200	94.3	69.5	531@1600	110.0	59.0	DI, TC, SPL
IA190	IA190	190@2500	83.3	69.8	525@1700	119.4	68.0	DI, TC, SPL
IA195	IA195	195@2400	92.7	74.6	550@1600	123.1	66.0	DI, TC, SPL
IAL210	IAL210	210@2400	103.9	83.6	625@1600	137.1	73.5	DI, TC, SPL
IA210	IA210	210@2500	102.3	85.7	625@1600	137.1	73.5	DI, TC, SPL