(Page 1 of 2)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER U-R-16-10

Relating to Certification of New Heavy-Duty Off-Road Equipment Engines

MERCEDES-BENZ AG

Pursuant to the authority vested in the Air Resources Board by Sections 43000.5, 43013 and 43018 of the Health and Safety Code; and,

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following Mercedes-Benz AG 1998 model-year engine, with rated power between 175 and 750 horsepower, and exhaust emission control systems are certified as described below for use in heavy-duty off-road equipment:

<u>Typical Equipment Usage</u>: Crane, Road Grader, Harvester, Compressor

Fuel Type: Diesel

<u>Engine Family</u>	Liters	Exhaust Emission Control <u>Systems and Special Features</u>
WMBXL5.96R6B	6.0 and 4.0	Turbocharger Smoke Puff Limiter

Engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The total hydrocarbons (THC), carbon monoxide (CO), nitrogen oxides (NOx), and particulate matter (PM) certification exhaust emission standards, in grams per brake horsepower-hour (g/bhp-hr), and the opacity of smoke emission standards, in percent (%), during acceleration (Accel), lugging (Lug), and peak (Peak) modes, for this engine family are (Title 13, California Code of Regulations, Section 2423):

<u>Exhaust</u>	<u>Emissi</u>	ons (q/	<u>bhp-hr)</u>	Smoke	<u>Opacity</u>	(%)
<u>thc</u>	<u>00</u>	<u>NOx</u>	<u>PM</u>	Accel	Lug	<u>Peak</u>
1.0	8.5	6.9	0.4	20	15	50

The THC, CO, NOx and PM exhaust emission certification values, in g/bhp-hr, and the opacity of smoke emission certification values, in percent (%), for this engine family are:

<u>Exhaust</u>	<u>t Emissi</u>	<u>ons (g/</u>	<u>bhp-hr)</u>	<u> Smoke</u>	Opacity	(%)
<u>THC</u>	<u>C0</u>	<u>NOx</u>	<u>PM</u>	<u>Accel</u>	Lug	<u>Peak</u>
0.6	0.9	6.2	0.2	2	2	3

BE IT FURTHER RESOLVED: That the listed engine models comply with the "Exhaust Emission Standards and Test Procedures--Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2423) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed engine models also comply with the "Emission Control Labels--1996 and Later Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2425 et seq.).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this $\frac{7}{2}$ day of April 1998.

R. B. Summerfield, Chief Mobile Source Operations Division

$\mathbf{\Sigma}$
\sim
5
S
$\overline{\mathbf{O}}$
~1
ןניי
ا ت
ล
늬
ΣI
ш
Z
<u> </u>
Z
ш
ш
Ы
N
5
4
[

EO: U-R-16-10

1/14/98

. •

MERCF0FC- AENQ- 8G/ Manufacturer:

Process Code: New Submission

EPA Engine Far	EPA Engine Family: WMBXL5.96R6B	96R6B		Manufacturer Family Name:	⁻ amily Name:	NA		
1.Engine Code	1.Engine Code 2.Engine Model	3.BHP@RPM (SAE Gross)	4.ruel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuei Rate: (lbs/hr)@peak torque	8.Fuet Rate: 9.Emission Control (Ibs/hr)@peak torque Device Per SAE J1930
366 A. E I/1	OM 366 A	162 @ 2600	72	62.2	398 @ *	82	35.1	EM SPI TC
366 A. E 1/2	OM 366 A	160 @ 2500	73	60.0	398 @ •	82	35.1	
366 A. E I/3	OM 366 A	158 @ 2400	74	58.4	398 @ *	82	35.1	
366 A. E I/4	OM 366 A	150 @ 2400	72	56.8	376 @ *	80	34.2	
366 A. E I/5	OM 366 A	135 @ 1800	82	48.4	398 @ •	82	35.1	
366 A. E I/6	OM 366 A	123 @ 2400	60	47,3	313 @ *	65	27.9	
364 A. E I/1	OM 364 A	106 @ 2600	71	40.4	265 @ **	68	2.2.2	
364 A. E I/2	OM 364 A	103 @ 2400	75	39.5	265 @ **	5	22.3	
364 A. E I/3	OM 364 A	101 @ 2400	71	37.3	258 @ **	81 81	23.1	
* 1300 - 1700)		- - -		5		
** 1300 - 1500								

-

ł

Ş.

4