## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER U-R-1-80

Relating to Certification of New Heavy-Duty Off-Road Equipment Engines

CATERPILLAR, INC.

Pursuant to the authority vested in the Air Resources Board by Sections 43000.5, 43013 and 43018 of the Health and Safety Code; and,

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following Caterpillar, Inc. 1999 model-year engine, with rated power between 175 and 750 horsepower, and exhaust emission control systems are certified as described below for use in heavy-duty off-road equipment:

Typical Equipment Usage: Loader, Agriculture Tractor

<u>Fuel Type</u>: Diesel

Engine Family	Liters	(Cubic Inches)	Exhaust Emission Control Systems and Special Features
XCPXL07.2MRB	7.2	(442)	Turbocharger Charge Air Cooler Smoke Puff Limiter

Engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The total hydrocarbons (THC), carbon monoxide (CO), nitrogen oxides (NOx), and particulate matter (PM) certification exhaust emission standards, in grams per brake horsepower-hour (g/bhp-hr), and the opacity of smoke emission standards, in percent (%), during acceleration (Accel), lugging (Lug), and peak (Peak) modes, for this engine family are (Title 13, California Code of Regulations, Section 2423):

Exhaust Emissions (g/bhp-hr)			Smoke	Smoke Opacity (%)		
<u>THC</u>	<u>CO</u>	<u>NOx</u>	<u>PM</u>	<u>Accel</u>	<u>Luq</u>	<u>Peak</u>
1.0	8.5	6.9	0.4	20	15	50

The THC, CO, NOx and PM exhaust emission certification values, in g/bhp-hr, and the opacity of smoke emission certification values, in percent (%), for this engine family are:

Exhaust Emissions (g/bhp-hr)			Smoke Opacity (%)			
<u>THC</u>	<u>co</u>	<u>NOx</u>	<u>PM</u>	<u>Accel</u>	Luq	<u>Peak</u>
0.1	0.8	6.5	0.2	14	3	35

BE IT FURTHER RESOLVED: That the listed engine models comply with the "Exhaust Emission Standards and Test Procedures--Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2423) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed engine models also comply with the "Emission Control Labels--1996 and Later Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2425 et seq.).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this \_\_\_\_\_\_day of December 1998.

R.) B. Summerfield, Chief

Mobile Source Operations Division

## LARGE ENGINE MODEL SUMMARY

E0:U-R-1-80

Manufacturer: CATERPILLAR INC.\_\_\_\_ Process Code: New Submission \_\_\_\_ EPA Engine Family: \_XCPX1\_07.2MRB\_ Manufacturer Family Name: 4. Fuel Rate: 5.Fuel Rate: 3.8HP@RPM mm/stroke @ prak HP 7.Fuel Rate: 1.Engine Code 2.Engine Model (fbs/fil) @ peak HP 6.Torque @ RPM (SAE Gross) (for diesel only) ninystroke@peak 8.Fuel Rate: 9.Emission Control (for cliesels only) (SEA Gross) (lbs/hr)@peak torque Device Per SAE J1930 torque Note: Peak Hp and Peak Torque fuel rates are nominal values. Du∈ to production engine avgs 1 - Cert Engine these fuel rates 3126 255 @ 2200 may change. 134 09.3 742 @ 1450 2 3126 150 230 @ 2600 73.0 EM, DI, TC, SPL, 103 89.9 3 575 @ 1950 114 3126 250 @ 2500 75.0 EM, DI, TC, SPL, 119 100.3 683 @ 1650 3126 132 73.1 260 @ 2400 EM, DI, TC, SPL, 128 103.4 740 @ 1450 5 3126 148 72.2 255 @ 2400 EM, DI, TC, SPL, 125 100.9 6 725 @ 1450 3126 145 70.5 240 @ 2400 116 EM, DI, TC, SPL. 93.9 683 @ 1450 135 3126 65.7 230 @ 2400 EM, DI, TC, SPL, 111 90.0 8 654 @ 1450 3126 129 220 @ 2400 62.7 EM, DI, TC, SPL, 106 85.7 626 @ 1400 3126 123 260 @ 2600 57.7 EM, DI, TC, SPL. 122 :08.5 10 363 @ 1650 3128 139 250 @ 2200 77.3 EM, DI, TC, SPL, 131 97.1 729 @ 1450 11 3126 146 71.4 240 @ 2200 EM, DI, TC, SPI 125 92.7 700@1450 12 3126 139 230 @ 2200 68.0 EM, DI, TC, SPL 119 88.1 13 070 @ 1450 3126 133 EM, DI, TC, SPL, CAC 215 @ 2200 64.8 111 31.9 14 625 @ 1400 3126 123 57.8 195 @ 2100 EM, DI, TC, SPL, 103 73.1 15 576 @ 1450 3126 114 230 @ 2200 55.7 EM, DI, TC, SPL, 119 88.1 670 @ 1450 16 3126 133 225 @ 2200 64.8 EM, DI, TC, SPL, 113 83.7 17 724 @ 1400 150 3126 221 @ 2200 70.5 EM, DI, TC, SPL, 110 81.7 18 710 @ 1400 3126 135 221 @ 2200 63.8 EM, DI, TC, SPL, 110 81.7 19 710 @ 1400 3126 135 225 @ 2200 63.8 EM, DI, TC, SPL, 113 83.7 20 724 @ 1400 150 3126 70.5 221 @ 2200 EM, DI, TC, SPL, 110 81.7 710 @ 1400 21 3126 135 221 @ 2200 63.8 EM, DI, TC, SPL, 110 81.7 22 710 @ 1400 3126 135 63.8 217 @ 2200 EM, DI, TC, SPL, 109 80.7 23 696 @ 1400 3126 144 EM, DI, TC, SPL, 204 @ 2200 67.9 104 77.0 721 @ 1400 24 3126 149 204 @ 2200 70.1 EM, DI, TC, SPL, 102 75.3 25 653 @ 1400 3126 126 59.1 201 @ 2200 EM, DI, TC, SPL, 101 74.6 26 643 @ 1400 123 3126 201 @ 2200 58.1 EM, DI, TC, SPL. 101 74.6 27 643 @ 1400 123 3126 196 @ 2200 58.1 100 EM, DI, TC. SPL. 74.1 692 @ 1400 143 67.5 EM, DI, TC, SPL,