Tree

(Page 1 of 2)

#### State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER U-R-7-31

## Relating to Certification of New Heavy-Duty Off-Road Equipment Engines

## DETROIT DIESEL CORPORATION

Pursuant to the authority vested in the Air Resources Board by Sections 43000.5, 43013 and 43018 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

Pursuant to the December 15, 1998 Settlement Agreement between the Air Resources Board and Detroit Diesel Corporation and any modifications to the Settlement Agreement;

IT IS ORDERED AND RESOLVED: That the following Detroit Diesel Corporation 1999 model-year engines with rated power between 175 and 750 horsepower and exhaust emission control systems are certified as described below in heavy-duty off-road equipment:

Typical Equipment Usage:

Crane, Dozer, Pump, Compressor,

and Generator Set

<u>Fuel Type:</u>

Diesel

Engine Family		acement Cubic Inches	Exhaust Emission Control Systems and Special Featur			
XDDXL08.5TJD (Series 50)	8.5	519	Charge Air Cooler Turbocharger Electronic Control Module			

Engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The total hydrocarbons (THC), carbon monoxide (CO), oxides of nitrogen (NOx), and particulate matter (PM) certification exhaust emission standards in grams per brake horsepower-hour (g/bhp-hr), and the opacity-of-smoke emission standards in percent (%) during acceleration (Accel), lugging (Lug), and peak (Peak) modes for this engine family are as follows (Title 13, California Code of Regulations, Section 2423):

Exhaust Emissions (g/bhp-hr)			<u>bhp-hr)</u>	<u>Smoke Opacity (%)</u>			
<u>THC</u>	<u>co</u>	<u>N0x</u>	<u>PM</u>	<u>Accel</u>	<u>Luq</u>	<u>Peak</u>	
1.0	8.5	6.9	0.4	20	15	50	

The THC, CO, NOx, and PM exhaust emissions certification values in grams per brake horsepower-hour, and the opacity-of-smoke emissions certification values in percent for this engine family are:

Exhaust Emissions (g/bhp-hr)			bhp-hr)	Smoke Opacity (%)			
<u>THC</u>	<u>co</u>	<u>N0x</u>	<u>PM</u>	<u>Accel</u>	<u>Lug</u>	<u>Peak</u>	
0.1	0.5	6.4	0.04	5	1	10	

BE IT FURTHER RESOLVED: That the listed engine models comply with the "Exhaust Emission Standards and Test Procedures--Heavy-Duty Off-Road Diesel-Cycle Engines" (Title 13, California Code of Regulations Section 2423) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed engine models also comply with the "Emission Control Labels--1996 and Later Heavy-Duty Off-Road Diesel-Cycle Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Sections 2425 et seq.).

BE IT FURTHER RESOLVED: That the aforementioned engine family has been conditionally certified subject to the following conditions:

- 1. The Settlement Agreement is in effect.
- 2. The Settlement Agreement has not become null and void under Settlement Agreement Paragraph 165.
- 3. Detroit Diesel Corp. is in compliance with all applicable certification requirements of the Settlement Agreement.

Engines certified under this Executive Order must conform to all applicable California emission regulations and to all applicable terms and conditions of the Settlement Agreement.

Executed at El Monte, California this  $\frac{1}{2}$  day of January 1999.

R. B. Summerfield, Chief Mobile Source Operations Division

# LARGE ENGINE MODEL SU. MARY

Manufacturer: Detroit Diesel Corporation

Process Code: New Submission

N

EPA Engine Family: XDDXL08.5TJD

Manufacturer Family Name: SERIES 50

Engine Code	Engine Model	BHP@RPM (SAE Gross)	Fuel Rate: mm/stroke @ peak HP	Fuel Rate: (lbs/hr) @ peak HP	Torque @ RPM (SEA Gross)	Fuel Rate: mm/stroke@peak torque	Fuel Rate: (lbs/hr)@peak torque	Emission Control Device Per SAE J1930
1A21	SERIES 50	315 @ 2100	(for diesel only) 235.6	(for diesels only) 109.7	1050 @ 1000		y	
1A18		315 @ 1800			1050 @ 1200	290.6	77.3	ECM, TC, CAC
1/10		313 @ 1800	251.1	100.2	1050 @ 1200	290.6	77.3	ECM TC, CAC
1B21	SERIES 50	300 @ 2100	215.2	100.2	1000 @ 1200	0700		
1B18		300 @ 1800		!	1000 @ 1200	270.0	71.8	ECH, TC, CAC
1570		300 @ 1800	236.8	94.5	1000 @ 1200	270.0	71.8	ECH TO,CAC
1C21	SERIES 50	275 @ 2100	197.9	92.2	900 @ 1200			•
1C18		275 @ 1800				241.9	64.4	ECM TC, CAC
1010		273 @ 1800	215.8	86.1	900 @ 1200	241.9	64.4	ECM, TC, CAC
1D21	SERIES 50	250 @ 2100	190.7	88.8	800 @ 1200	240.0		
1D18		250 @ 1800	195.5			218.8	58.2	ECM, TC. CAC
		200 @ 1000	130.0	78.0	800 @ 1200	218.8	58.2	ECM, TC, CAC ECM, TC, CAC
GS1	SERIES 50	315 @ 1800	251.6	100.4	NA			
GS2	SERIES 50	250 @ 1800	196.0	1		NA	NA	ECM, TC, CAC
-22	52,20 00	200 @ 1000	190.0	78.2	NA	NA	NA	ECM, TC, CAC