## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER U-R-9-9

Relating to Certification of New Heavy-Duty Off-Road Equipment Engines

## MITSUBISHI MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by Sections 43000.5, 43013 and 43018 of the Health and Safety Code; and,

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following Mitsubishi Motors Corporation 1999 model-year engine, with rated power between 175 and 750 horsepower, and exhaust emission control systems are certified as described below for use in heavy-duty off-road equipment:

Typical Equipment Usage: Loader, Generator

Fuel Type: Diesel

Engine Family Liters (Cubic Inches)

Exhaust Emission Control Systems and Special Features

XMTXL07.5D6C 7.5 (460)

Turbocharger

Engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The total hydrocarbons (THC), carbon monoxide (CO), nitrogen oxides (NOx), and particulate matter (PM) certification exhaust emission standards, in grams per brake horsepower-hour (g/bhp-hr), and the opacity of smoke emission standards, in percent (%), during acceleration (Accel), lugging (Lug), and peak (Peak) modes, for this engine family are (Title 13, California Code of Regulations, Section 2423):

| <u>Exhaust</u> | t Emissi  | ons (g/l   | bhp-hp)   | Smoke        | Smoke Opacity (%) |             |  |
|----------------|-----------|------------|-----------|--------------|-------------------|-------------|--|
| <u>THC</u>     | <u>co</u> | <u>NOx</u> | <u>PM</u> | <u>Accel</u> | <u>Lug</u>        | <u>Peak</u> |  |
| 1.0            | 8.5       | 6.9        | 0.4       | 20           | 15                | 50          |  |

The THC, CO, NOx and PM exhaust emission certification values, in g/bhp-hr, and the opacity of smoke emission certification values, in percent (%), for this engine family are:

| <u>Exhaust</u> | <u>t Emissi</u> | ons (g/l   | ohp-hr)   | <u>Smoke</u> | Smoke Opacity (%) |             |  |  |
|----------------|-----------------|------------|-----------|--------------|-------------------|-------------|--|--|
| <u>THC</u>     | <u>CO</u>       | <u>NOx</u> | <u>PM</u> | <u>Accel</u> | Lug               | <u>Peak</u> |  |  |
| 0.3            | 0.6             | 6.7        | 0.2       | 17           | 4                 | 34          |  |  |

BE IT FURTHER RESOLVED: That the listed engine models comply with the "Exhaust Emission Standards and Test Procedures--Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2423) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed engine models also comply with the "Emission Control Labels--1996 and Later Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2425 et seq.).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this \_\_\_\_\_\_ day of February 1998.

R. B. Summerfield, Chief

Mobile Source Operations Division

12/16/97

## LARGE ENGINE MODEL SUMMARY

EO: U-R-9-9

Process Code: New Submission Manufacturer: Mitsubishi Motors Corporation N/A Manufacturer Family Name: EPA Engine Family: XMTXL07.5D6C 4.Fuel Rate: 5.Fuel Rate: 7.Fuel Rate: 8.Fuel Rate: 6.Torque @ RPM 9.Emission Control (lbs/hr) @ peak HP mm/stroke @ peak HP 3.BHP@RPM mm/stroke@peak (lbs/hr)@peak torque Device Per SAE J1930 2.Engine Model (SEA Gross) 1.Engine Code (for diesel only) (for diesels only) (SAE Gross) torque EM,TC 51.2 485 @ 1600 96 178 @ 2200 64.8 6D16TEB-US99 6D16-TEB 89 EM,TC 119 58.9 65.0 582 @ 1500 109 6D16TEA-US99 6D16-TEA 184 @ 1800 EM,TC 106 56.1 94 87.3 514 @ 1600 212 @ 2800 6D16TEC-US99 6D16-TEC