## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER U-R-1-121 Relating to Certification of New Heavy-Duty Off-Road Equipment Engines

## CATERPILLAR, INC.

Pursuant to the authority vested in the Air Resources Board at Sections 43000.5, 43013, and 43018 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned at Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9; and

IT IS ORDERED AND RESOLVED: That the following diesel engines and the exhaust emission control systems produced by the manufacturer are certified as described below for use in heavy-duty off-road equipment:

Model Year: 2000

Typical Equipment Usage: Industrial equipment

Engine Power Ratings Range: 175 - 750 horsepower, inclusive

Fuel Type: Diesel

	Displac	cement	Exhaust Emission Control
Engine Family	<u>Liters</u>	Cubic Inches	Systems and Special Features
YCPXL27.0MRJ	27.0	1658	Smoke Puff Limiter Turbocharger Charge Air Cooler

The engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The exhaust emission certification standards and certification values in grams per brake horsepower-hour (g/hp-h) for total hydrocarbons (THC), carbon monoxide (CO), nitrogen oxides (NOx), and particulate matter (PM), and the opacity-of-smoke certification standards and certification values in percent (%) during acceleration (Accel), lugging (Lug), and the peak-values from either mode (Peak) for this engine family are as follows (Title 13, California Code of Regulations, Section 2423):

<u>Ex</u>	<u>haust Em</u>	nissions	( <u>g/hp-h)</u>		<u>Smo</u>	<u>ke Opacity</u>	<u>/ (%)</u>
Standard	<u>THC</u>	<u>CO</u> 8.5	<u>NOx</u> 6.9	<u>PM</u> 0.4	Accel 20	<u>Lug</u> 15	<u>Peak</u> 50
Certification	0.1	1.6	6.7	0.3	17	6	29

BE IT FURTHER RESOLVED: That the listed engine models comply with "Exhaust Emission Standards and Test Procedures—Heavy-Duty Off-Road Diesel-Cycle Engines" (Title 13, California Code of Regulations, Section 2423) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed engine models also comply with "Emission Control Labels—1996 and Later Heavy-Duty Off-Road Diesel-Cycle Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Sections 2425 *et seg.*).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this  $\mathcal{F}$  day of December 1999.

1

R. B. Summerfield, Chief

Mobile Source Operations Division

EO: U-R-1-121

Process Code: New Submission

Manufacturer: CATERPILLAR INC.

## LARGE ENGINE MODEL SUMMARY

EPA Engine Fa	EPA Engine Family: YCPXL27.0MRJ	OMRJ		Manufacturer	Manufacturer Family Name:	A A		
1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAE J1930
Note: Peak Hp	and Peak Torque	fuel rates are	nominal values.	Due to product-	ion engine avgs.	these fuel rates	may change.	
1 - Cert Engine	3412	700 @ 2100	214	303.0	2562 @ 1400	260	244.6	EM, DI, TC, SPL,
2	3412	700 @ 2100	200	282.0	1612 @ 1400	237	223.4	EM, DÇÆC, SPL,
က	3412	650 @ 2100	182	257.7	2115 @ 1400	212	200.0	DCAC.
4	3412	700 @ 2100	200	282.0	1612 @ 1400	237	223.4	EM, DÇAC, SPL,
5	3412	650 @ 2100	182	257.7	2115 @ 1400	212	200.0	DÇÆC,
9	3412	600 @ 2100	167	235.9	1932 @ 1400	194	182.9	DÇAC,
7	3412	575 @ 2100	159	225.1	1841 @ 1400	185	174.3	DCAC.
ဆ	3412	650 @ 1800	199	240.6	2216 @ 1350	227	206.0	DCAC,
6	3412	625 @ 1800	191	231.2	2098 @ 1350	215	195.0	EM, DÇÆC, SPL,
10	3412	600 @ 1800	183	222.0	1994 @ 1350	204	185.5	DÇAC,
#	3412	575 @ 1800	174	210.9	1892 @ 1350	194	175.9	EM, DÇAC, SPL,
12	3412	600 @ 2000	175	235.9	1995 @ 1400	204	192.3	EM, DÇÆC, SPL,
13	3412	560 @ 1800	170	205.3	1830 @ 1350	187	170.1	EM, DÇÆC, SPL,
14	3412	515 @ 1800	156	188.8	1658 @ 1350	170	154.1	EM, DÇÆC, SPL,
								ફ <b>(</b>