(Page 1 of 2)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER U-R-2-55 Relating to Certification of New Heavy-Duty Off-Road Equipment Engines

CUMMINS ENGINE COMPANY, INC.

Pursuant to the authority vested in the Air Resources Board at Sections 43000.5, 43013, and 43018 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned at Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9; and

IT IS ORDERED AND RESOLVED: That the following diesel engines and exhaust emission control systems produced by the manufacturer are certified as described below for use in heavy-duty off-road equipment:

Model Year: 2000

Typical Equipment Usage: Crane, Loader, Tractor, Dozer, Pump, and Compressor

Engine Power Ratings Range: 175 - 750 horsepower, inclusive

Fuel Type: Diesel

	Disp	olacement	Exhaust Emission Control
Engine Family	<u>Liters</u>	Cubic Inches	Systems and Special Features
YCEXL0505AAA	8.3	505	Turbocharger
(A412)			Charge Air Cooler

The engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The exhaust emission certification standards and certification values in grams per brake horsepower-hour (g/bhp-hr) for total hydrocarbons (THC), carbon monoxide (CO), nitrogen oxides (NOx), and particulate matter (PM), and the opacity-of-smoke certification standards and certification values in percent (%) during acceleration (Accel), lugging (Lug), and the peak-values from either mode (Peak) for this engine family are as follows (Title 13, California Code of Regulations, Section 2423):

<u>Exh</u>	<u>aust Emi</u>	ssions (g		<u>Smo</u>	<u>ke Opacit</u>	<u>/ (%)</u>	
Standard Certification	<u>THC</u> 1.0 0.3	<u>CO</u> 8.5 0.6	<u>NOx</u> 6.9 5.7	<u>PM</u> 0.4 0.2	<u>Accel</u> 20 5	<u>Lug</u> 15 2	<u>Peak</u> 50 11

BE IT FURTHER RESOLVED: That the engine models listed on the attachments with engine power ratings less than 175 horsepower are not covered by this Executive Order.

BE IT FURTHER RESOLVED: That the listed engine models comply with "Exhaust Emission Standards and Test Procedures—Heavy-Duty Off-Road Diesel-Cycle Engines" (Title 13, California Code of Regulations, Section 2423) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed engine models also comply with "Emission Control Labels—1996 and Later Heavy-Duty Off-Road Diesel-Cycle Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Sections 2425 et seq.).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this 3074 day of December 1999.

R. B. Summerfield, Chief Mobile Source Operations Division

Replace Sumowity

Engine Model Smany Form

Manufacturer: Cummins Engine Company

Engine category: Nonroad Over 50 Hp

EPA Engine Family: YCEXL0505AAA

Mfr Family Name: A412

Process Code: New Submission

9.Emission Control Device Per SAE J1930	1	2	21) (<u> </u>	2 4	ی د	သ	ည (ည ငှ	2 Ç	2 6) - -) - -	۲ ۾) - F	<u>ر</u>	۲ -)) (<u>ک</u> ۲	ر ۱ –	2	<u>ن</u>) - H	<u> </u>	2 4)
8.Fuel Rate: (lbs/hr)@peak torque	64.0	64.0		0.10	4.00	63.4	63.4	58.5	55.8	52.8 	55.8	55.8	56.0	52.9	63.9	62.2	63.9	62.7	51,6	43.2	55.8	49.5	0.09	51.8	20.0	The second secon	
7.Fuel Rate: mm/stroke@peak torque	127	197	12	171	471	125	125	116	110	110	110	110		105	126	115	126	124	109	85	110	86	119	86	66		
6.Torque @ RPM (SEA Gross)	642@1500	642@1500	045(0)	642@1500	636@1500	636@1500	636@1500	590@1500	575@1500	575@1500	575@1500	575@1500	560@1500	520@1500	636@1500	563@1600	575@1500	626@1500	550@1400	475@1500	574@1500	507@1500	610@1500	496@1600	496@1500		
5.Fuel Rate: (Ibs/hr) @ peak HP (for diesels only)	82.3) i	82.3	82.3	78.9	78.9	78.9	73.0	71.0	71.0	71.0	71.0	68.0	0.89	77.6	71.8	66.2	8.7.9	66.1	59.1	83.7	73.7	89.1	68.9	0.69	75.9	66.2
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	+ + +				106	106	106	86	96	96	96	96	92	92	115	112	86	101	89	08	66	87	106	87	89	125	131 C.
3.BHP@RPM	(375 3133)	715(@2200	215@2200	215@2200	205@2200	205@2200	205@2200	190@2200	185@2200	185@2200	185@2200	185@2200	170@2200	170@2200	205@2000	195@1900	180@2000	181@2000	165@2100	150@2200	201@2500	177@2500	215@2500	173@2380	173@2300	207@1800	181@1500
c Engine Model	Z.E.I.gille Model	C8.3-C	C8.3-C	C8.3-C	C8.3-C	C8.3-C	C8.3-C	C8.3-C	C8.3-C	C8.3-C	C8.3-C	C8.3-C	C8.3-C	C8.3-C	C8.3-C	C8.3-C	C8.3-C	C8.3-C	C8.3-C	C8.3-C	C8.3-C	C8.3-C	C8.3-C	C8.3-C	C8.3-C	6CT8.3-G2	6СТ8.3-G2
F () () () () () () () () () (1943;FR9874	1943;FR90181	1943;FR90416	1943;FR9873	1943:FR90178	1943 FR90118	1943.FR9871	1943:FR90042	1943.FR9870	1943:FR90330	1943:FR90417	1943:FR9869	1943:FR90225	2060 FR90043	2060;FR90113	2060;FR90044	2060:FR90168	2060;FR90350	2060;FR90117	2061:FR90177	2061:FR90041	2185:FR90040	2120:FR90119	2120;FR90353	2216:FR90240	2216;FR90241