

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER U-R-2-66
Relating to Certification of New Heavy-Duty Off-Road Equipment Engines

CUMMINS ENGINE COMPANY, INC.

Pursuant to the authority vested in the Air Resources Board at Sections 43000.5, 43013, and 43018 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned at Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9; and

IT IS ORDERED AND RESOLVED: That the following diesel engines and exhaust emission control systems produced by the manufacturer are certified as described below for use in heavy-duty off-road equipment:

Model Year: 2000

Typical Equipment Usage: Generator Set

Engine Power Ratings Range: 175 horsepower and greater

Fuel Type: Diesel

<u>Engine Family</u>	<u>Displacement</u>		<u>Exhaust Emission Control Systems and Special Features</u>
	<u>Liters</u>	<u>Cubic Inches</u>	
YCEXL015.ABA (B103)	15.0	921	Engine Control Module Turbocharger Charge Air Cooler

The engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The exhaust emission certification standards and certification values in grams per brake horsepower-hour (g/hp-h) for engines with power ratings between 175 and 750 horsepower, inclusive, for total hydrocarbons (THC), carbon monoxide (CO), nitrogen oxides (NOx), and particulate matter (PM), and the opacity-of-smoke certification standards and certification values in percent (%) during acceleration (Accel), lugging (Lug), and the peak-values from either mode (Peak) for this engine family are as follows (Title 13, California Code of Regulations, Section 2423):

	<u>Exhaust Emissions (g/bhp-h)</u>				<u>Smoke Opacity (%)</u>		
	<u>THC</u>	<u>CO</u>	<u>NOx</u>	<u>PM</u>	<u>Accel</u>	<u>Lug</u>	<u>Peak</u>
Standard	1.0	8.5	6.9	0.4	20	15	50
Certification	0.1	0.8	6.4	0.1	--	--	--

The exhaust emission certification standards and certification values in grams per brake horsepower-hour (g/hp-h) for engines with power ratings above 750 horsepower for total hydrocarbons (THC), carbon monoxide (CO), nitrogen oxides (NOx), and particulate matter (PM), and the opacity-of-smoke certification standards and certification values in percent (%) during acceleration (Accel), lugging (Lug), and the peak-values from either mode (Peak) for this engine family are as follows (Title 13, California Code of Regulations, Section 2423):

	<u>Exhaust Emissions (g/bhp-h)</u>				<u>Smoke Opacity (%)</u>		
	<u>THC</u>	<u>CO</u>	<u>NOx</u>	<u>PM</u>	<u>Accel</u>	<u>Lug</u>	<u>Peak</u>
Standard	1.0	8.5	6.9	0.4	20	15	50
Certification	0.1	0.8	6.4	0.1	--	--	--

BE IT FURTHER RESOLVED: That the listed engine models comply with "Exhaust Emission Standards and Test Procedures—Heavy-Duty Off-Road Diesel-Cycle Engines" (Title 13, California Code of Regulations, Section 2423) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed engine models also comply with "Emission Control Labels—1996 and Later Heavy-Duty Off-Road Diesel-Cycle Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Sections 2425 *et seq.*).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this 30th day of December 1999.



per R. B. Summerfield, Chief
Mobile Source Operations Division

Engine Model Summary Form

U-R-2-66

Manufacturer: Cummins Engine Company, Inc.
 Engine category: Nonroad CI
 EPA Engine Family: YCEXL015.ABA
 Mfr Family Name: B103
 Process Code: New Submission

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
CPL 2483								TC, EC
FR 10333	QSX15-G	775 @ 1800	435	260.5				TC, EC
FR 10209	QSX15-G9	755 @ 1800	416	249				
FR 10301	QSX15-G7	685 @ 1800	357	214				
FR 10299	QSX15-G5	610 @ 1800	312	187				
CPL 2867								
FR 10340	QSX15-G	775 @ 1800	435	260.5				
FR 10339	QSX15-G9	755 @ 1800	416	249				
FR 10334	QSX15-G7	685 @ 1800	357	214				
FR 10335	QSX15-G5	610 @ 1800	312	187				