

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER U-R-12-42

Relating to Certification of New Heavy-Duty Off-Road Equipment Engines

NAVISTAR INTERNATIONAL TRANSPORTATION CORPORATION

Pursuant to the authority vested in the Air Resources Board by Sections 43000.5, 43013 and 43018 of the Health and Safety Code; and,

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following Navistar International Transportation Corporation 2000 model-year engine, with rated power between 175 and 750 horsepower, and exhaust emission control systems are certified as described below for use in heavy-duty off-road equipment:

Typical Equipment Usage: Generator.

Fuel Type: Diesel

<u>Engine Family</u>	<u>Liters (Cubic Inches)</u>	<u>Exhaust Emission Control Systems and Special Features</u>
YNVXL0530ANC	8.7 (530)	Turbocharger Engine Control Model Charge Air Cooler

Engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The total hydrocarbons (THC), carbon monoxide (CO), nitrogen oxides (NOx), and particulate matter (PM) certification exhaust emission standards, in grams per brake horsepower-hour (g/bhp-hr), and the opacity of smoke emission standards, in percent (%), during acceleration (Accel), lugging (Lug), and peak (Peak) modes, for this engine family are (Title 13, California Code of Regulations, Section 2423):

<u>Exhaust Emissions (g/bhp-hr)</u>				<u>Smoke Opacity (%)</u>		
<u>THC</u>	<u>CO</u>	<u>NOx</u>	<u>PM</u>	<u>Accel</u>	<u>Lug</u>	<u>Peak</u>
1.0	8.5	6.9	0.4	20	15	50

The THC, CO, NOx and PM exhaust emission certification values, in g/bhp-hr, and the opacity of smoke emission certification values, in percent (%), for this engine family are:

<u>Exhaust Emissions (g/bhp-hr)</u>				<u>Smoke Opacity (%)</u>		
<u>THC</u>	<u>CO</u>	<u>NOx</u>	<u>PM</u>	<u>Accel</u>	<u>Lug</u>	<u>Peak</u>
0.1	0.3	5.6	0.1	-	3	-


BE IT FURTHER RESOLVED: That the listed engine models comply with the "Exhaust Emission Standards and Test Procedures--Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2423) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed engine models also comply with the "Emission Control Labels--1996 and Later Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2425 et seq.).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this 17th day of June 1999.

A handwritten signature in cursive script, appearing to read "John Kourliski for".

R. B. Summerfield, Chief
Mobile Source Operations Division

LARGE ENGINE MODEL SUMMARY

Manufacturer: **Navistar E. O. # U-R-12-42**

Process Code: **New Submission**

EPA Engine Family: **YNVXL0530ANC**

Manufacturer Family Name: **DTA-530E**

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque Device Per SAE J1930	9.Emission Control
		Advertised	Average value	Average value				
GCB330	GCB330	330 @ 1500	229.0	115.0				ECM, TC,CAC, DI
GCA325	GCA325	325 @ 1800	199.0	120.0				ECM, TC,CAC, DI
GCB310	GCB310	310 @ 1500	213.0	107.0				ECM, TC,CAC, DI
GCA305	GCA305	305 @ 1800	177.5	107.0				ECM, TC,CAC, DI
GCB300	GCB300	300 @ 1500	205.1	103.0				ECM, TC,CAC, DI
GCB275	GCB275	275 @ 1500	189.4	95.2				ECM, TC,CAC, DI
GCA270	GCA270	270 @ 1800	154.1	93.0				ECM, TC,CAC, DI
GCB250	GCB250	250 @ 1500	166.0	83.4				ECM, TC,CAC, DI
GCA250	GCA250	250 @ 1800	142.8	86.1				ECM, TC,CAC, DI
GCB230	GCB230	230 @ 1500	152.6	76.7				ECM, TC,CAC, DI
Dual Ratings		Can Be Either						
GCD325	GCD325	GCA325 OR GCB300						
GCD305	GCD305	GCA305 OR GCB275						
GCD270	GCD270	GCA270 OR GCB250						
GCD250	GCD250	GCA250 OR GCB230						