State of California AIR RESOURCES BOARD

EXECUTIVE ORDER U-R-2-77 Relating to Certification of New Off-Road Compression-Ignition Equipment Engines

CUMMINS ENGINE COMPANY, INC.

Pursuant to the authority vested in the Air Resources Board (Board) by Sections 430.13, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and exhaust emission control system produced by the manufacturer are certified as described below for use in off-road equipment:

Model Year: 2001

Typical Equipment Usage: Crane, Loader, Tractor, Dozer, Pump, Compressor and

Generator

Fuel Type: Diesel

	Engine		
	Displacement	Useful Life	Exhaust Emission Control
Engine Family	(liters)	(hours)	Systems and Special Features
1CEXL0505AAA	8.3	8000	Direct Diesel Injection
			Turbocharger
!			Charge Air Cooler

Engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The exhaust emission certification standards and certification values for total hydrocarbons (THC), carbon monoxide (CO), oxides of nitrogen (NOx), and particulate matter (PM) (units are expressed in grams per kilowatt-hour (g/kw-hr)), and the opacity-of-smoke certification standards and certification values in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family are as follows (Title 13, California Code of Regulations, Section 2423, as amended by Board approval on January 28, 2000):

Engine Power <u>Rating (kw)</u>	Emission Standard <u>Category</u>		<u>Ext</u>	<u>aust E</u> (g/kw	missio /-hr)	<u>ns</u>	<u>Smol</u>	(e O	pacity		
			THC	ÇO	<u>NOx</u>	РМ	Accel	Luq	<u>Peak</u>		
75 <u><</u> KW<130	Tier 1	Standard	N/A	N/A	9.2	N/A	20	15	50		
130 <u><</u> KW<225	Tier 1	Standard	1.3	11.4	9.2	0.54	20	15	50		
All Above		Certification	0.4	0.7	7.6	0.33	5	2	11		

(Page 2 of 2)

BE IT FURTHER RESOLVED: That, at the request of the manufacturer, the listed engine models are conditionally certified to, and shall be required to comply with, all amendments to Title 13, California Code of Regulations, Sections 2420 through 2427 adopted by the Board on January 28, 2000 at its hearing "TO CONSIDER AMENDMENTS TO OFF-ROAD COMPRESSION-IGNITION ENGINE REGULATIONS: 2000 AND LATER EMISSION STANDARDS, COMPLIANCE REQUIREMENTS AND TEST PROCEDURES." The listed engine models comply with all such amendments, including, but not limited to:

- the amended "Emission Control Labels-1996 and Later Off-Road Compression-Ignition Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model year;
- the Board's amended emission control system warranty provisions (Title 13, California Code of Regulations, Sections 2425 and 2426) for the listed engine models, as demonstrated by materials submitted by the manufacturer; and
- new California requirements for the Selective Enforcement Audit (SEA) for the listed engine models, as demonstrated by the manufacturer's submission of materials.

BE IT FURTHER RESOLVED: That the conditional certification described in the paragraph above is conditioned on the amendments being approved by the California Office of Administrative Law (OAL) pursuant to Government Code Section 11349.3, and where necessary, authorized by the Administrator of the U.S. Environmental Protection Agency (U.S. EPA) pursuant to Section 209(e)(2) of the Federal Clean Air Act.

- A. In the event that the OAL disapproves the amendments or the U.S. EPA decides not to authorize them, the ARB shall notify the manufacturer that the listed engine models must comply with the "California Exhaust Emission Standards and Test Procedures for 1996 and Later Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Sections 2420 through 2427) adopted on May 12, 1993, as applicable. Failure to demonstrate compliance within 45 days after notification by the Air Resources Board shall be cause for the Board to revoke the Executive Order and deem the listed engine models uncertified.
- B. In the event that the OAL disapproves the amendments or the U.S. EPA decides not to authorize them, the conditional certification herein of the listed engine models with rated power greater than or equal to 19 KW but less than 130 KW shall be deemed null and void.

The conditional certification described herein is not conditioned on further U.S. EPA action on amendments determined by the Board to be within the scope of an existing U.S. EPA authorization.

Engines certified under this Executive Order must conform to the above requirements under Title 13, California Code of Regulations, Chapter 9, Article 4, and all other applicable California emission laws and regulations.

Executed at El Monte, California this 22 nd day of December 2000.

B. Summerfield, Chief

Mobile Source Operations Division

Engine Model Sir mary Form

Manufacturer:

Cummins Engine Company

Engine category:

Nonroad Over 50 Hp

EPA Engine Family: 1CEXL0505AAA

Mfr Family Name: A412

Process Code:

New Submission

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: P (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control 6 Device Per SAE J1930
1943;FR9874	C8.3-C	215@2200		82.3	642@1500	127	64	DOI, TC, CAC
1943;FR90181	C8.3-C	215@2200	111	82.3	642@1500	127	64	l TC l
1943;FR90416	C8.3-C	215@2200	111	82.3	642@1500	127	64	TC
1943;FR9873	C8.3-C	205@2200	106	78.9	636@1500	125	63.4	TC
1943;FR90178	C8.3-C	205@2200	106	78.9	636@1500	125	63,4	TC
1943;FR90118	C8.3-C	205@2200	106	78.9	636@1500	125	63.4	TC
1943;FR9871	C8.3-C	190@2200	98	73	590@1500	116	58.5	TC
1943;FR90042	C8.3-C	185@2200	96	71	575@1500	110	55.8	TC
1943;FR9870	C8.3-C	185@2200	1 ₂ , 11 , 1 96	71	575@1500	110	55.8	TC
1943;FR90330	C8.3-C	185@2200	96	. 71	575@1500	110	55.8	TC
1943;FR90417	C8.3-C	185@2200	96	71	575@1500	110	55.8	TG
1943;FR9869	C8.3-C	170@2200	92	68	560@1500	111	56	TC
1943;FR90225	C8.3-C	170@2200	92	68	520@1500	105	52.9	TC
1943;FR90515	C8.3-C	215@2200	111	82.3	642@1500	127	64	TC
1943;FR90772	C8.3-C	190@2200	97	72.2	590@1500	113	57.1	TC
2060;FR90043	C8.3-C	205@2000	115	77.6	636@1500	126	63.9	TC
2060;FR90113	C8.3-C	195@1900	112	· 71.8	563@1600	115	62.2	TC
2060;FR90044	C8.3-C	180@2000	98	66.2	575@1500	126	63.9	TC
2060;FR90168	C8.3-C	181@2000	101	67.8	626@1500	124	62,7	TC
2060;FR90350	C8.3-C	165@2100	89	66.1	550@1400	109	51.6	TC
2060;FR90117	C8.3-C	150@2200	80	59.1	475@1500	85	43.2	TC
2060;FR90914	C8.3-C	170@1900	99	63.6	599@1500	121	61.4	TC
2061;FR90177	C8.3-C	201@2500	99	83.7	574@1500	110	• 55.8	TC 1
2061;FR90041	C8.3-C	177@2500	87	73.7	507@1500	98	49.5	TC
2185;FR90040	C8.3-C	215@2500	106	89.1	610@1500	119	60	TC
2120;FR90119	C8.3-C	173@2380	87	68.9	496@1600	98	51.8	TC
2120;FR90353	C8.3-C	173@2300	89	69	496@1500	99	50	V TC Ψ