State of California AIR RESOURCES BOARD

EXECUTIVE ORDER U-R-2-78 Relating to Certification of New Off-Road Compression-Ignition Equipment Engines

CUMMINS ENGINE COMPANY, INC.

Pursuant to the authority vested in the Air Resources Board (Board) by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and exhaust emission control system produced by the manufacturer are certified as described below for use in off-road equipment:

Model Year: 2001

Typical Equipment Usage: Crane, Loader, Tractor, Dozer, Pump, Compressor and

Generator

Fuel Type: Diesel

Engine Family 1CEXL0505ABB	Engine Displacement (<u>liters)</u> 8.3	Useful Life (hours) 8000	Exhaust Emission Control Systems and Special Features Direct Diesel Injection Turbocharger Charge Air Cooler
-------------------------------	---	--------------------------------	--

Engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The exhaust emission certification standards and certification values for total hydrocarbons (THC), carbon monoxide (CO), oxides of nitrogen (NOx), and particulate matter (PM) (units are expressed in grams per kilowatt-hour (g/kw-hr)), and the opacity-of-smoke certification standards and certification values in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family are as follows (Title 13, California Code of Regulations, Section 2423, as amended by Board approval on January 28, 2000):

Engine Power <u>Rating (kw)</u>	Emission Standard <u>Category</u>		Ext	naust E (g/kw	missio /-hr)	<u>ns</u>	<u>Smo</u>	Smoke Opacity (%)		
130 <u><</u> KW<225	Tier 1	Standard Certification	<u>THC</u> 1.3 0.4	<u>CO</u> 11.4 0.7	<u>NOx</u> 9.2 7.2	<u>PM</u> 0.54 0.25	<u>Accel</u> 20 7	<u>Lug</u> 15 2	<u>Peak</u> 50 16	

(Page 2 of 2)

BE IT FURTHER RESOLVED: That, at the request of the manufacturer, the listed engine models are **conditionally certified** to, and shall be required to comply with, all amendments to Title 13, California Code of Regulations, Sections 2420 through 2427 adopted by the Board on January 28, 2000 at its hearing "TO CONSIDER AMENDMENTS TO OFF-ROAD COMPRESSION-IGNITION ENGINE REGULATIONS: 2000 AND LATER EMISSION STANDARDS, COMPLIANCE REQUIREMENTS AND TEST PROCEDURES." The listed engine models comply with all such amendments, including, but not limited to:

- the amended "Emission Control Labels—1996 and Later Off-Road Compression-Ignition Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model year;
- the Board's amended emission control system warranty provisions (Title 13, California Code of Regulations, Sections 2425 and 2426) for the listed engine models, as demonstrated by materials submitted by the manufacturer; and
- new California requirements for the Selective Enforcement Audit (SEA) for the listed engine models, as demonstrated by the manufacturer's submission of materials.

BE IT FURTHER RESOLVED: That the conditional certification described in the paragraph above is conditioned on the amendments being approved by the California Office of Administrative Law (OAL) pursuant to Government Code Section 11349.3, and where necessary, authorized by the Administrator of the U. S. Environmental Protection Agency (U.S. EPA) pursuant to Section 209(e)(2) of the Federal Clean Air Act. In the event that the OAL disapproves the amendments or the U.S. EPA decides not to authorize them, the ARB shall notify the manufacturer that the listed engine models must comply with the "California Exhaust Emission Standards and Test Procedures for 1996 and Later Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Sections 2420 through 2427) adopted on May 12, 1993, as applicable. Failure to demonstrate compliance within 45 days after notification by the Air Resources Board shall be cause for the Board to revoke the Executive Order and deem the listed engine models uncertified.

The conditional certification described herein is not conditioned on further U.S. EPA action on amendments determined by the Board to be within the scope of an existing U.S. EPA authorization.

Engines certified under this Executive Order must conform to the above requirements under Title 13, California Code of Regulations, Chapter 9, Article 4, and all other applicable California emission laws and regulations.

Executed at El Monte, California this 22 nd day of December 2000.

R. B. Summerfield, Chief

Duc "

Mobile Source Operations Division

Cummins Engine Company Manufacturer:

Nonroad Over 50 Hp Engine category:

EPA Engine Family: 1CEXL0505ABB

Mfr Family Name: B413

New Submission Process Code:

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE .11930	ol 930
2062;FR9878	C8.3-C	240@2200	123	91.0	750@1500		71.8		♦
2062;FR90617	C8.3-C	240@2200	123	91.0	750@1500	142	71.8		
2062;FR90162	C8.3-C	240@2200	123	91.0	750@1500	142	71.8	2	
2062;FR90541	C8.3-C	240@2200	123	91.0	750@1500	142	71.8	TC 1	
2062;FR90387	C8.3-C	240@2200	123	91.0	750@1500	142	71,8	TC	
2062;FR90503	C8.3-C	240@2200	123	91.0	750@1500	142	71.8	2	
2062FR90048	C8.3-C	230@2200	118	87.3	730@1500	140	71.0	TC	
2062,FR9889	C8.3-C	230@2200	118	87.3	730@1500	140	71.0	TC	
2062;FR9886	C8.3-C	230@2200	81	87.3	730@1500	140	71.0		
2062;FR90049	C8.3-C	230@2200	118	87.3	730@1500	140	71.0	<u> </u>	·
2007;FR9875	C8.3-C	215@2200	110	81.8	668@1500	127	64.1	10	AT I
2007;FR90264	C8.3-C	215@2200	110	81.8	668@1500	127	64.1	TC	(AC
2007;FR90163	C8.3-C	215@2200	109	80.6	616@1500	118	59.5	ΩL	HV
2055;FR90050	C8.3-C	230@2000	125	84.4	720@1500	138	70.0	TC	NG
2056;FR90112	C8.3-C	215@1900	120	76.7	645@1500	123	62.0		MT.
2951;FR90803	C8.3-C	207 @ 1900	117	75.0	714 @ 1400	142	0.79	101	
2951;FR90804	C8.3-C	200 @ 1900	112	. 72.0	699 @ 1400	136	64.0	→ 2 →	`