

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER U-R-4-84
Relating to Certification of New Off-Road Compression-Ignition Engines

DEERE POWER SYSTEMS GROUP OF DEERE & COMPANY

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment:

Model Year: 2001

Typical Equipment Usage: Loader and pump

Fuel Type: Diesel

| <u>Engine Family</u> | Engine Displacement (liters) | Useful Life (hours) | Emission Control Systems and Special Features |
|----------------------|------------------------------------|------------------------|--|
| 1JDXL06.8014 | 4.5 and 6.8 | 8000 | Direct Diesel Injection Turbocharger |

Engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The exhaust emission certification standards and certification values for hydrocarbons (HC), oxides of nitrogen (NO_x), or non-methane hydrocarbons plus oxides of nitrogen (NMHC+NO_x), carbon monoxide (CO), and particulate matter (PM) (units are expressed in grams per kilowatt-hour (g/kw-hr)), and the opacity-of-smoke certification standards and certification values in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family are as follows (Title 13, California Code of Regulations, Section 2423):


| Engine Power Rating (kw) | Emission Standard Category | | Exhaust Emissions (g/kw-hr) | | | | | Smoke Opacity (%) | | |
|-----------------------------|----------------------------------|---------------|-----------------------------|-----------------|----------------------|------|------|-------------------|-----|------|
| | | | HC | NO _x | NMHC+NO _x | CO | PM | Accel | Lug | Peak |
| 37≤KW<130 | Tier 1 | Standard | N/A | 9.2 | N/A | N/A | N/A | 20 | 15 | 50 |
| | | Certification | -- | 7.2 | -- | -- | -- | 8 | 7 | 18 |
| 130≤KW<225 | Tier 1 | Standard | 1.3 | 9.2 | N/A | 11.4 | 0.54 | 20 | 15 | 50 |
| | | Certification | 0.4 | 7.2 | -- | 0.9 | 0.28 | 8 | 7 | 18 |

BE IT FURTHER RESOLVED: That the listed engine models also comply with "Emission Control Labels— 1996 and Later Off-Road Compression-Ignition Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Sections 2425 and 2426).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this 6th day of February 2001.


R. B. Summerfield, Chief
Mobile Source Operations Division

Return to template

Engine Model Summ. Template

Attachment
(pg 1 of 4)

1 FWR-4-8

| Engine Family | 1.Engine Code | 2.Engine Model | 3.BHP@RPM (SAE Gross) | 4.Fuel Rate: mm/stroke @ peak HP (for diesel only) | 5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only) | 6.Torque @ RPM (SEA Gross) | 7.Fuel Rate: mm/stroke@peak torque | 8.Fuel Rate: (lbs/hr)@peak torque | 9 | |
|-------------------------|----------------------|------------------|--------------------------|--|--|-------------------------------|--|--------------------------------------|--------------------|-----|
| 1JDXL06.8014 | 4045TN050 | 4045T | 106@2200 | 79.5 | 78@2200 | 38@2200 | 291@1400 | 88@1400 | 27@1400 | DOI |
| 1JDXL06.8014 | 4045TDW50 | 4045T | 114@2200 | 86 | 83@2200 | 40@2200 | 328@1400 | 103@1400 | 31@1400 | DOI |
| 1JDXL06.8014 | 4045TF150A | 4045T | 115@2500 | 86 | 77@2500 | 43@2500 | 291@1400 | 91@1400 | 28@1400 | DOI |
| 1JDXL06.8014 | 4045TF250A | 4045T | 125@2400 | 94 | 87@2400 | 46@2400 | 328@1400 | 101@1400 | 31@1400 | |
| 1JDXL06.8014 | 6068TRW50 | 6068T | 118@2100 | 88 | 60@2100 | 42@2100 | 384@1300 | 76@1300 | 33@1300 | |
| 1JDXL06.8014 | 6068TT050 | 6068T | 123@2200 | 92 | 61@2200 | 44@2200 | 388@1200 | 76@1200 | 30@1200 | |
| 1JDXL06.8014 | 6068TDW54 | 6068T | 126@2200 | 95 | 62@2200 | 45@2200 | 400@1200 | 80@1200 | 34@1200 | |
| 1JDXL06.8014 | 6068TRW51 | 6068T | 129@2100 | 97 | 66@2100 | 46@2100 | 419@1300 | 84@1300 | 36@1300 | |
| 1JDXL06.8014 | 6068TDW50 | 6068T | 142@2200 | 107 | 69@2200 | 51@2200 | 449@1400 | 90@1400 | 42@1400 | |
| 1JDXL06.8014 | 6068TRW52 | 6068T | 141@2100 | 106 | 72@2100 | 50@2100 | 458@1300 | 92@1300 | 40@1300 | |
| 1JDXL06.8014 | 6068TF150B | 6068T | 155@2500 | 114 | 70@2500 | 58@2500 | 425@1200 | 86@1200 | 34@1200 | |
| 1JDXL06.8014 | 6068TN051 | 6068T | 157@2200 | 118 | 76@2200 | 55@2200 | 450@1300 | 88@1300 | 39@1300 | |
| 1JDXL06.8014 | 6068TF150A | 6068T | 170@2500 | 128 | 78@2500 | 65@2500 | 448@1200 | 94@1200 | 41@1200 | |
| 1JDXL06.8014 | 6068TN050 | 6068T | 185@2400 | 139 | 86@2400 | 68@2400 | 486@1400 | 100@1400 | 46@1400 | |
| 1JDXL06.8014 | 6068TF250B | 6068T | 185@2400 | 139 | 86@2400 | 68@2400 | 494@1400 | 100@1400 | 46@1400 | |
| 1JDXL06.8014 | 6068TT052 | 6068T | 148@2100 | 111 | 76@2100 | 53@2100 | 441@1300 | 90@1300 | 39@1300 | |
| 1JDXL06.8014 | 6068TE050 | 6068T | 172@2300 | 129 | 82@2300 | 63@2300 | 482@1400 | 98@1400 | 45@1400 | |
| 1JDXL06.8014 | 6068TF150D | 6068T | 157@2200 | 118 | 76@2200 | 55@2200 | 450@1300 | 88@1300 | 38@1300 | |
| 1JDXL06.8014 | 6068TRW53 | 6068T | 118@2100 | 88 | 60@2100 | 42@2100 | 384@1300 | 76@1300 | 33@1300 | |
| 1JDXL06.8014 | 6068TRW54 | 6068T | 129@2100 | 97 | 66@2100 | 46@2100 | 419@1300 | 84@1300 | 36@1300 | |
| 1JDXL06.8014 | 4045TT061 | 4045T | 78@2100 | 59 | 62@2100 | 29@2100 | 263@1200 | 80@1200 | 21@1200 | |
| 1JDXL06.8014 | 4045TT067 | 4045T | 78@2100 | 59 | 62@2100 | 29@2100 | 263@1200 | 80@1200 | 21@1200 | |
| 1JDXL06.8014 | 4045TT057 | 4045T | 75@2200 | 56 | 57@2200 | 28@2200 | 242@1000 | 73@1000 | 16@1000 | |
| 1JDXL06.8014 | 4045TT058 | 4045T | 80@2200 | 60 | 61@2200 | 30@2200 | 258@1200 | 77@1200 | 20@1200 | |
| 1JDXL06.8014 | 4045TT054 | 4045T | 84@2200 | 63 | 64@2200 | 31@2200 | 255@1200 | 76@1200 | 20@1200 | |
| 1JDXL06.8014 | 4045TT064 | 4045T | 84@2200 | 63 | 64@2200 | 31@2200 | 255@1200 | 76@1200 | 20@1200 | |
| 1JDXL06.8014 | 4045TT056 | 4045T | 78@2200 | 59 | 59@2200 | 29@2200 | 247@1200 | 73@1200 | 19@1200 | |
| 1JDXL06.8014 | 4045TT050 | 4045T | 89@2200 | 67 | 66@2200 | 32@2200 | 272@1300 | 84@1300 | 24@1300 | |

12/1/10

| Engine Family | 1.Engine Code | 2.Engine Model | 3.BHP@RPM (SAE Gross) | 4.Fuel Rate: mm/stroke @ peak HP (for diesel only) | 5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only) | 6.Torque @ RPM (SEA Gross) | 7.Fuel Rate: mm/stroke@peak torque | 8.Fuel Rate: (lbs/hr)@peak torque | 9.D |
|-------------------------|----------------------|------------------|--------------------------|--|--|-------------------------------|--|--------------------------------------|--------------------|
| 1JDXL06.8014 | 4045TT060 | 4045T | 89@2200 | 67 | 66@2200 | 32@2200 | 272@1300 | 84@1300 | 24@1300 |
| 1JDXL06.8014 | 4045TT065 | 4045T | 89@2200 | 67 | 66@2200 | 32@2200 | 272@1300 | 84@1300 | 24@1300 |
| 1JDXL06.8014 | 4045TT062 | 4045T | 89@2100 | 67 | 69@2100 | 32@2100 | 282@1200 | 87@1200 | 23@1200 |
| 1JDXL06.8014 | 4045TT068 | 4045T | 89@2100 | 67 | 69@2100 | 32@2100 | 282@1200 | 87@1200 | 23@1200 |
| 1JDXL06.8014 | 4045TT053 | 4045T | 98@2200 | 74 | 72@2200 | 35@2200 | 299@1200 | 96@1200 | 25@1200 |
| 1JDXL06.8014 | 4045TT066 | 4045T | 98@2200 | 74 | 72@2200 | 35@2200 | 299@1200 | 96@1200 | 25@1200 |
| 1JDXL06.8014 | 4045TT063 | 4045T | 99@2100 | 74 | 77@2100 | 36@2100 | 307@1200 | 98@1200 | 26@1200 |
| 1JDXL06.8014 | 4045TT069 | 4045T | 99@2100 | 74 | 77@2100 | 36@2100 | 307@1200 | 98@1200 | 26@1200 |
| 1JDXL06.8014 | 6068TT055 | 6068T | 123@2200 | 92 | 61@2200 | 44@2200 | 388@1200 | 76@1200 | 30@1200 |
| 1JDXL06.8014 | 6068TF150G | 6068T | 129@2100 | 97 | 66@2100 | 46@2100 | 419@1300 | 84@1300 | 36@1300 |
| 1JDXL06.8014 | 4045TL054 | 4045T | 90@2300 | 69 | 66@2300 | 33@2300 | 274@1300 | 85@1300 | 24@1300 |
| 1JDXL06.8014 | 4045TL055 | 4045T | 99@2300 | 74 | 72@2300 | 36@2300 | 303@1400 | 93@1400 | 28@1400 |
| 1JDXL06.8014 | 4045TL056 | 4045T | 109@2300 | 82 | 79@2300 | 39@2300 | 331@1400 | 104@1400 | 32@1400 |
| 1JDXL06.8014 | 4045TL057 | 4045T | 114@2300 | 86 | 82@2300 | 41@2300 | 334@1600 | 102@1600 | 36@1600 |
| 1JDXL06.8014 | 4045TL062 | 4045T | 105@2300 | 79 | 76@2300 | 38@2300 | 319@1300 | 100@1300 | 29@1300 |
| 1JDXL06.8014 | 4045TL063 | 4045T | 84@2300 | 63 | 63@2300 | 31@2300 | 255@1100 | 78@1100 | 19@1100 |
| 1JDXL06.8014 | 4045TZ250 | 4045T | 107@2200 | 80 | 78@2200 | 39@2200 | 302@1400 | 95@1400 | 47@1400 |
| 1JDXL06.8014 | 4045TF152 | 4045T | 102@2400 | 77 | 72@2400 | 38@2400 | 277@1200 | 87@1200 | 22@1200 |
| 1JDXL06.8014 | 4045TF153 | 4045T | 97@2200 | 73 | 71@2200 | 34@2200 | 280@1400 | 84@1400 | 26@1400 |
| 1JDXL06.8014 | 4045TLV50 | 4045T | 89@2400 | 67 | 63@2400 | 33@2400 | 242@1400 | 73@1400 | 22@1400 |
| 1JDXL06.8014 | 6068TL053 | 6068T | 117@2300 | 88 | 58@2300 | 44@2300 | 365@1300 | 73@1300 | 31@1300 |
| 1JDXL06.8014 | 6068TF152 | 6068T | 156@2500 | 117 | 70@2500 | 35@2500 | 425@1200 | 86@1200 | 43@1200 |
| 1JDXL06.8014 | 6068TP051 | 6068T | 129@2100 | 97 | 66@2100 | 46@2100 | 419@1300 | 84.1@1300 | 36@1300 |
| 1JDXL06.8014 | 4045TF250C | 4045T | 114@2200 | 86 | 83@2200 | 40@2200 | 328@1400 | 103@1400 | 32@1400 |
| 1JDXL06.8014 | 6068TF150E | 6068T | 148@2100 | 111 | 76@2100 | 53@2100 | 442@1300 | 90@1300 | 39@1300 |
| 1JDXL06.8014 | 6068TF150F | 6068T | 126@2200 | 95 | 62@2200 | 45@2200 | 400@1300 | 80@1300 | 34@1300 |
| 1JDXL06.8014 | 6068TF250D | 6068T | 172@2300 | 129 | 82@2300 | 63@2300 | 483@1400 | 98@1400 | 45@1400 |
| 1JDXL06.8014 | 6068TF250E | 6068T | 142@2200 | 107 | 69@2200 | 51@2200 | 438@1400 | 90@1400 | 42@1400 |

SE required by R/C dated 12/1/00

Y

| Engine Family | 1.Engine Code | 2.Engine Model | 3.BHP@RPM (SAE Gross) | 4.Fuel Rate: mm/stroke @ peak HP (for diesel only) | 5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only) | 6.Torque @ RPM (SEA Gross) | 7.Fuel Rate: mm/stroke@peak torque | 8.Fuel Rate: (lbs/hr)@peak torque | 9. | |
|---------------|---------------|----------------|--------------------------|--|--|-------------------------------|--|--------------------------------------|---------|-----|
| 1JDXL06.8014 | 4045TF150E | 4045T | 89@2200 | 67 | 66@2200 | 32@2200 | 272@1300 | 84@1300 | 24@1300 | DDI |
| 1JDXL06.8014 | 4045TF150D | 4045T | 98@2200 | 74 | 72@2200 | 35@2200 | 299@1200 | 94@1200 | 25@1200 | |
| 1JDXL06.8014 | 6068TF250C | 6068T | 166@1800 | 85 | 94@1800 | 56@1800 | NA | NA | NA | |
| 1JDXL06.8014 | 4045TF150C | 4045T | 101@1800 | 76 | 88@1800 | 35@1800 | NA | NA | NA | |
| 1JDXL06.8014 | 4045TF250B | 4045T | 113@1800 | 85 | 100@1800 | 40@1800 | NA | NA | NA | |
| 1JDXL06.8014 | 6068TF150C | 6068T | 150@1800 | 113 | 86@1800 | 51@1800 | NA | NA | NA | |
| 1JDXL06.8014 | 6068TF151A | 6068T | 150@1800 | 113 | 86@1800 | 51@1800 | NA | NA | NA | |
| 1JDXL06.8014 | 4045TF150F | 4045T | 105@2300 | 79 | 74.8@2300 | 38@2300 | 295@1300 | 88.4@1300 | 26@1300 | |
| 1JDXL06.8014 | 6068TF150H | 6068T | 156@2400 | 117 | 71.5@2400 | 57@2400 | 448@1300 | 88.3@1300 | 38@1300 | |
| 1JDXL06.8014 | 6068TF150I | 6068T | 148@2300 | 111 | 69.8@2300 | 53@2300 | 438@1300 | 86.6@1300 | 37@1300 | |
| 1JDXL06.8014 | 4045TT850 | 4045T | 106@2200 | 80 | 77@2200 | 38@2200 | 291@1400 | 86@1400 | 27@1400 | |
| 1JDXL06.8014 | 4045TP052 | 4045T | 84@2200 | 63 | 64@2200 | 31@2200 | 255@1200 | 76@1200 | 20@1200 | |
| 1JDXL06.8014 | 6068TRW70 | 6068T | 141@2100 | 106 | 72@2100 | 50@2100 | 458@1300 | 92@1300 | 40@1300 | |
| 1JDXL06.8014 | 6068TT056 | 6068T | 123@2100 | 92 | 63.5@2100 | 44@2100 | 388@1200 | 76@1200 | 31@1200 | |
| 1JDXL06.8014 | 6068TF159 | 6068T | 129@2100 | 97 | 66@2100 | 46@2100 | 419@1300 | 84@1300 | 35@1300 | |
| 1JDXL06.8014 | 6068TT850 | 6068T | 185@2400 | 139 | 86@2400 | 68@2400 | 494@1400 | 100@1400 | 46@1400 | |
| 1JDXL06.8014 | 6068TRW72 | 6068T | 148@2100 | 111 | 74@2100 | 53@2100 | 479@1400 | 95.4@1400 | 45@1400 | |
| 1JDXL06.8014 | 4045TT083 | 4045T | 102@2200 | 77 | 74@2200 | 37@2200 | 299@1200 | 94@1200 | 25@1200 | |
| 1JDXL06.8014 | 4045TF150G/1 | 4045T | 110@1800 | 83 | 94.2@1800 | 38@1800 | NA | NA | NA | |
| 1JDXL06.8014 | 4045TF250D/2 | 4045T | 122@1800 | 92 | 107.6@1800 | 43@1800 | NA | NA | NA | |
| 1JDXL06.8014 | 6068TF150J/15 | 6068T | 165@1800 | 124 | 94.3@1800 | 57@1800 | NA | NA | NA | |
| 1JDXL06.8014 | 6068TF250F/2 | 6068T | 190@1800 | 142 | 109.3@1800 | 66@1800 | NA | NA | NA | |
| 1JDXL06.8014 | 4045TF151A | 4045T | 101@1800 | 76 | 88@1800 | 35@1800 | NA | NA | NA | |
| 1JDXL06.8014 | 4045TF151C | 4045T | 111@2000 | 83 | 88@2000 | 39@2000 | NA | NA | NA | |
| 1JDXL06.8014 | 6068TF151C | 6068T | 165@2000 | 124 | 86@2000 | 57@2000 | NA | NA | NA | |
| 1JDXL06.8014 | 4045TLV51 | 4045T | 89@2400 | 67 | 63@2400 | 33@2400 | 242@1400 | 73@1400 | 22@1400 | |
| 1JDXL06.8014 | 4045TF161 | 4045T | 98@2200 | 74 | 72@2200 | 35@2200 | 299@1200 | 94@1200 | 25@1200 | |
| 1JDXL06.8014 | 4045TT091 | 4045T | 98@2200 | 74 | 72@2200 | 35@2200 | 299@1200 | 94@1200 | 25@1200 | V |

| Engine Family | 1.Engine Code | 2.Engine Model | 3.BHP@RPM (SAE Gross) | 4.Fuel Rate: mm/stroke @ peak HP (for diesel only) | 5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only) | 6.Torque @ RPM (SEA Gross) | 7.Fuel Rate: mm/stroke@peak torque | 8.Fuel Rate: (lbs/hr)@peak torque | |
|---------------|---------------|----------------|--------------------------|--|--|-------------------------------|--|--------------------------------------|---------|
| 1JDXL06.8014 | 4045TT080 | 4045T | 78@2200 | 58 | 59@2200 | 29@2200 | 247@1200 | 73@1200 | 19@1200 |
| 1JDXL06.8014 | 4045TT081 | 4045T | 89@2200 | 67 | 66@2200 | 32@2200 | 272@1300 | 84@1300 | 24@1300 |
| 1JDXL06.8014 | 4045TT082 | 4045T | 98@2200 | 74 | 72@2200 | 35@2200 | 299@1200 | 94@1200 | 25@1200 |
| 1JDXL06.8014 | 4045TKV50 | 4045T | 89@2400 | 67 | 63@2400 | 33@2400 | 242@1400 | 73@1400 | 22@1400 |
| 1JDXL06.8014 | 4045TKV51 | 4045T | 89@2400 | 67 | 63@2400 | 33@2400 | 242@1400 | 73@1400 | 22@1400 |
| 1JDXL06.8014 | 6068TT851 | 6068T | 185@2400 | 139 | 86@2400 | 68@2400 | 494@1400 | 100@1400 | 46@1400 |
| 1JDXL06.8014 | 4045TE051 | 4045T | 115@2500 | 118 | 77@2500 | 43@2500 | 291@1400 | 91@1400 | 28@1400 |
| 1JDXL06.8014 | 6068TF250A | 6068T | 194@2400 | 146 | 90@2400 | 71@2400 | 507@1400 | 104@1400 | 48@1400 |
| 1JDXL06.8014 | 4045TE050 | 4045T | 100@2500 | 75 | 69@2500 | 38@2500 | 275@1400 | 83@1400 | 26@1400 |
| 1JDXL06.8014 | 4045TF150B | 4045T | 100@2500 | 75 | 69@2500 | 38@2500 | 275@1400 | 83@1400 | 26@1400 |

Engine Model Summary Form

EDF U-R-4-84

Manufacturer: Deere Power Systems Group of Deere & Company

Engine category: Nonroad CI

EPA Engine Family: 1JDXL06.8014

Mfr Family Name: 350TA

Process Code: Running Change

| 1.Engine Code | 2.Engine Model | 3.BHP @RPM (SAE Gross) | 4.Fuel Rate: mm/stroke @ peak HP (for diesel only) | 5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only) | 6.Torque @ RPM (SEA Gross) | 7.Fuel Rate: mm/stroke@peak torque | 8.Fuel Rate: (lbs/hr)@peak torque | 9.Emission Control Device Per SAE J1930 |
|---------------|----------------|---------------------------|--|--|-------------------------------|--|--------------------------------------|--|
| 6068TP054 | 6068T | 109@2100 | 55.8@2100 | 39@2100 | 346@1400 | 66.4@1400 | 31@1400 | EM, TC |
| 4045TP060 | 4045T | 97@2100 | 72.9@2100 | 34@2100 | 308@1400 | 93.9@1400 | 30@1400 | EM, TC |
| 4045TL070 | 4045T | 84@2300 | 62.1@2300 | 31@2300 | 257@1500 | 76.7@1500 | 25@1500 | EM, TC |
| 4045TL071 | 4045T | 93@2300 | 67.3@2300 | 34@2300 | 281@1500 | 84.2@1500 | 28@1500 | EM, TC |
| 4045TL073 | 4045T | 703@2300 | 74.4@2300 | 37@2300 | 313@1400 | 97.1@1400 | 29@1400 | EM, TC |
| 4045TL075 | 4045T | 105@2300 | 76@2300 | 38@2300 | 319@1300 | 99.2@1300 | 29@1300 | EM, TC |
| 6068TL071 | 6068T | 117@2300 | 56.7@2300 | 42@2300 | 322@1500 | 64.4@1500 | 31@1500 | EM, TC |

Engine Model Summary Form

Manufacturer: Deere Power Systems Group of Deere & Company
Engine category: Nonroad CI
EPA Engine Family: 1JDXL06.8014
Mfr Family Name: 350TA
Process Code: Running Change

ED# 4-R-4-84

| 1.Engine Code | 2.Engine Model | 3.BHP@RPM (SAE Gross) | 4.Fuel Rate: mm/stroke @ peak HP (for diesel only) | 5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only) | 6.Torque @ RPM (SEA Gross) | 7.Fuel Rate: mm/stroke@peak torque | 8.Fuel Rate: (lbs/hr)@peak torque | 9.Emission Control Device Per SAE J1930 |
|---------------|----------------|--------------------------|--|--|-------------------------------|--|--------------------------------------|--|
| 6068TE051 | 6068T | 182@2300 | 83.5@2300 | 85@2300 | 486@1400 | 100@1400 | 46@1400 | EM,TC |
| 4045TF250E | 4045T | 134@1800 | 120@1800 | 49@1800 | | | | EM |