

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER U-R-6-30

Relating to Certification of New Off-Road Compression-Ignition Equipment Engines

ISUZU MOTORS LIMITED

Pursuant to the authority vested in the Air Resources Board (Board) by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and exhaust emission control system produced by the manufacturer are certified as described below for use in off-road equipment:

Model Year: 2001

Typical Equipment Usage: Crane, Loader and Other Industrial Equipment

Fuel Type: Diesel

<u>Engine Family</u>	<u>Engine Displacement (liters)</u>	<u>Useful Life (hours)</u>	<u>Exhaust Emission Control Systems and Special Features</u>
1SZXL09.8ATB	9.8	8000	Direct Diesel Injection Turbocharger

Engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The exhaust emission certification standards and certification values for total hydrocarbons (THC), carbon monoxide (CO), oxides of nitrogen (NOx), and particulate matter (PM) (units are expressed in grams per kilowatt-hour (g/kw-hr)), and the opacity-of-smoke certification standards and certification values in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family are as follows (Title 13, California Code of Regulations, Section 2423, as amended by Board approval on January 28, 2000):

<u>Engine Power Rating (kw)</u>	<u>Emission Standard Category</u>		<u>Exhaust Emissions (g/kw-hr)</u>				<u>Smoke Opacity (%)</u>		
			<u>THC</u>	<u>CO</u>	<u>NOx</u>	<u>PM</u>	<u>Accel</u>	<u>Lug</u>	<u>Peak</u>
75≤KW<130	Tier 1	Standard	N/A	N/A	9.2	N/A	20	15	50
130≤KW<225	Tier 1	Standard	1.3	11.4	9.2	0.54	20	15	50
All Above		Certification	0.7	1.4	9.0	0.30	17	9	29

BE IT FURTHER RESOLVED: That, at the request of the manufacturer, the listed engine models are **conditionally certified** to, and shall be required to comply with, all amendments to Title 13, California Code of Regulations, Sections 2420 through 2427 adopted by the Board on January 28, 2000 at its hearing "TO CONSIDER AMENDMENTS TO OFF-ROAD COMPRESSION-IGNITION ENGINE REGULATIONS: 2000 AND LATER EMISSION STANDARDS, COMPLIANCE REQUIREMENTS AND TEST PROCEDURES." The listed engine models comply with all such amendments, including, but not limited to:

- the amended "Emission Control Labels—1996 and Later Off-Road Compression-Ignition Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model year;
- the Board's amended emission control system warranty provisions (Title 13, California Code of Regulations, Sections 2425 and 2426) for the listed engine models, as demonstrated by materials submitted by the manufacturer; and
- new California requirements for the Selective Enforcement Audit (SEA) for the listed engine models, as demonstrated by the manufacturer's submission of materials.


BE IT FURTHER RESOLVED: That the conditional certification described in the paragraph above is conditioned on the amendments being approved by the California Office of Administrative Law (OAL) pursuant to Government Code Section 11349.3, and where necessary, authorized by the Administrator of the U. S. Environmental Protection Agency (U.S. EPA) pursuant to Section 209(e)(2) of the Federal Clean Air Act.

- A. In the event that the OAL disapproves the amendments or the U.S. EPA decides not to authorize them, the ARB shall notify the manufacturer that the listed engine models must comply with the "California Exhaust Emission Standards and Test Procedures for 1996 and Later Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Sections 2420 through 2427) adopted on May 12, 1993, as applicable. Failure to demonstrate compliance within 45 days after notification by the Air Resources Board shall be cause for the Board to revoke the Executive Order and deem the listed engine models uncertified.
- B. In the event that the OAL disapproves the amendments or the U.S. EPA decides not to authorize them, the conditional certification herein of the listed engine models with rated power greater than or equal to 19 KW but less than 130 KW shall be deemed null and void.

The conditional certification described herein is not conditioned on further U.S. EPA action on amendments determined by the Board to be within the scope of an existing U.S. EPA authorization.

Engines certified under this Executive Order must conform to the above requirements under Title 13, California Code of Regulations, Chapter 9, Article 4, and all other applicable California emission laws and regulations.

Executed at El Monte, California this 27th day of December 2000.


R. B. Summerfield, Chief
Mobile Source Operations Division

Engine Model Summary Form

ATTACH. ENT

Manufacturer: **Isuzu Motors Limited**
 Engine category: **Nonroad CI**
 EPA Engine Family: **1SZXL09.8ATB**
 Mfr Family Name: **NA**
 Process Code: **New Submission**

U-R-6-30

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
6SD1TAAAB-01	B-6SD1T	250.8@2200	130.5@2200	95.8@2200	704.4@1600	139.0@1600	74.2@1600	EM,TC,DFI
6SD1TAAAB-02	B-6SD1T	226.6@1750	139.0@1750	81.2@1750	704.4@1600	139.0@1600	74.2@1600	EM,TC,DFI
6SD1TAAAB-03	B-6SD1T	190.4@2200	99.1@2200	72.8@2200	523.7@1600	103.7@1600	55.3@1600	EM,TC,DFI
6SD1TAAAB-04	B-6SD1T	174.3@1750	103.7@1750	60.6@1750	523.7@1600	103.7@1600	55.3@1600	EM,TC,DFI
6SD1TAAAB-05	B-6SD1T	235.3@2000	126.9@2000	84.7@2000	672.7@1600	134.0@1600	71.5@1600	EM,TC,DFI
6SD1TAAAB-06	B-6SD1T	245.5@2000	137.6@2000	91.8@2000	704.4@1600	139.0@1600	74.2@1600	EM,TC,DFI
6SD1TAAAB-07	B-6SD1T	214.0@2100	113.3@2100	79.4@2100	624.9@1600	122.5@1600	65.4@1600	EM,TC,DFI