DETROIT DIESEL CORPORATION

EXECUTIVE ORDER U-R-007-0065 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR			FUEL TYPE	USEFUL LIFE (hours)		
2001	1DDXL08.5YJD	8.5	Diesel	8000		
	FEATURES & EMISSION (CONTROL SYSTEMS	TYPICAL EQUIPMENT	APPLICATION		
Direct Diesel Injection, Turbocharger, Charge Air Cooler, Engine Control Module			Crane, Loader, Tractor, Pump, Compressor, Generator			
ENGINE MODELS (rated power in kilowatts, kw)			See Attachment			

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

EMISSION STANDARD		EXHAUST (g/kw-hr)				OPACITY (%)			
CATEGORY Tier 2		HC	NOx	NMHC+NOx	СО	РМ			PEAK
Tier 2	STD	N/A	N/A	6.6	3.5	0.20			<u> </u>
Tier 2	STD	N/A	N/A						50
	CERT			4.7	0.9	0.11	17	15	50 34
	STANDARD CATEGORY Tier 2	STANDARD CATEGORY Tier 2 STD Tier 2 STD	STANDARD CATEGORY HC Tier 2 STD N/A Tier 2 STD N/A	STANDARD	STANDARD HC NOx NMHC+NOx	STANDARD HC NOx NMHC+NOx CO	STANDARD CATEGORY	STANDARD CATEGORY HC NOx NMHC+NOx CO PM ACCEL Tier 2 STD N/A N/A 6.6 3.5 0.20 20 Tier 2 STD N/A N/A 6.4 3.5 0.20 20	STANDARD CATEGORY EXHAUST (g/kw-hr) OPACITY (% CATEGORY) HC NOx NMHC+NOx CO PM ACCEL LUG Tier 2 STD N/A N/A 6.6 3.5 0.20 20 15 Tier 2 STD N/A N/A 6.4 3.5 0.20 20 15

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

_ day of July 2001.

R. B. Summerfield, Chief

Mobile Source Operations Division

Engine Model 5 nmary Form

Manufacturer:

Detroit Diesel Corporation

Engine category:

Nonroad CI

EPA Engine Family: 1DDXL08.5YJD

Mfr Family Name: SERIES 50 (TIER 2)

Process Code:

New Submission

ATTACHMENT

						•		
1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torqu	9.Emission Control Device Per SAE J1930
A22	Series 50	350 @ 2200 (2	61 (cw) 278.8	136.0	1050 @ 1350	314.5	THE PERSON OF CONCESSION AS ABOVE MADE AND A SECURE AS	
· A18		350 @ 1800 `	319.4	127.5	1050 @ 1350	314.5	94.1 94.1	dDI, TC, CAC, EC (all ratings)
B22		315 @ 2200	258.0	125.8	1050 @ 1350	312.4	93.5	
B18		315 @ 1800	292.1	116.6	1050 @ 1350	312.4	93.5 93.5	
C21		350 @ 2100	285.5	132.9	1050 @ 1350	313.7	93.9	
C18		350 @ 1800	319.1	127.3	1050 @ 1350	313.7	93.9	
D21		315 @ 2100	261.9	121.9	1050 @ 1350	313.1	93.7	
D18		315 @ 1800	292.5	116.7	1050 @ 1350	313.1	93.7	
E21		300 @ 2100	249.4	116.1	1000 @ 1350	298.1	89.2	
E18		300 @ 1800	279.4	111.5	1000 @ 1350	298.1	89.2	
F21		275 @ 2100	229.8	107.0	900 @ 1350	268.4	80.3	1
F18		275 @ 1800	255.0	101.8	900 @ 1350	268.4	80.3	
· G21		250 @ 2100 (\8	(6 kw) _{209.9}	97.7	800 @ 1350	242.1	72.5	
G18		250 @ 1800	229.7	91.7	800 @ 1350	242.1	72.5	
		•						
· GS1	Series 50	350 @ 1800	315.1	125.8	NA	NA	NA	
GS2		315 @ 1800	285.6	114.0	NA	NA	NA	
GS3		250 @ 1800	229.4	91.5	NA	NA	NA .	V