#### State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER U-R-22-3 Relating to Certification of New Off-Road Compression-Ignition Engines

### PERKINS ENGINES COMPANY LTD.

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment:

Model Year: 2001

Typical Equipment Usage: Other Industrial Equipment

1

Fuel Type: Diesel

	Engine		
<u>Engine Family</u> 1PKXL03.0UA1	Displacement (liters) 2.955	Useful Life <u>(hours)</u> 8000	Emission Control Systems and Special Features Direct Diesel Injection

Engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The exhaust emission certification standards and certification values for hydrocarbons (HC), oxides of nitrogen (NOx), or non-methane hydrocarbons plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) (units are expressed in grams per kilowatt-hour (g/kw-hr)), and the opacity-of-smoke certification standards and certification values in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family are as follows (Title 13, California Code of Regulations, Section 2423):

Engine Power	Emission Standard		Exhaust Emissions (g/kw-hr)					Smoke	Smoke Opacity (%)		
<u>Rating (kw)</u> 37 <u>≤</u> KW<130	<u>Category</u> Tier 1	Standard	<u>НС</u> N/А	<u>NOx</u> 9.2	<u>NMHC+NOx</u> N/A	<u>CQ</u> N/A	<u>PM</u> N/A	<u>Accel</u> 20	<u>Lug</u> 15	<u>Peak</u> 50	
		Certification		8.1				2	10	10	

BE IT FURTHER RESOLVED: That the listed engine models also comply with "Emission Control Labels— 1996 and Later Off-Road Compression-Ignition Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Sections 2425 and 2426).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this

Ī

day of January 2001.

R. B. Summerfield, Chief Mobile Source Operations Division

## ATI., CHMENT

# Engine Model Sunmary Form

U-R-22-3

. .

:

Manufacturer: Perkins Engines Company Ltd

Engine category: Nonroad CI

EPA Engine Family: 1PKXL03.0UA1

Mfr Family Name: AS EPA

¥

Process Code: New Submission

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J193
	1881/2200	59.7 @ 2200	44.0	21.3	149.6@1600	48.0	16.9	
	1881/2300	61.0 @ 2300	43.4	21.7	149.6@1600	48.0	16.9	个 NA
	1881/2400	61.7 @ 2400	42.4	22.4	149.6 @ 1600	48.0	16.9	
	1881/2500	62.4 @ 2500	41.8	23.0	149.6@1600	48.0	16.9	
	1881/2600	62.4 @ 2600	40.8	23.2	149.6 @ 1600	48.0	16.9	NA NA
	1927/2400	57.0 @ 2400	39.0	20.5	140.1 @ 1800	42.0	16,9 16,7	
	1927/2500	57.5 @ 2500	38.4	21.1	140.1 @ 1800	42.0	16.7	NA.
	1927/2600	57.7 @ 2600	37.4	21.3	140.1 @ 1800	42.0		I NA
	2071/2500	62.0 @ 2500	41.8	23.0	149.6 @ 1600	48.0	16.7	DDT NA
	2071/2600	62.4 @ 2600	40.8	23.2	149.6 @ 1600	48.0	16.9	NA
	2072/2600	57.7 @ 2600	37.5	21.3	140.1 @ 1600	42.0	16.9	NA
	2073/2600	52.3 @ 2600	33.5	19.0	131.1 @ 1600	39.8	14.8	NA
	Caterpillar 3034	62.4 @ 2600	40.8	23.2	149.6 @ 1600		13.9	NA NA
	Caterpillar 3034	57.7 @ 2600	37.5	21.3	140.1 @ 1600	48.0	16.9	NA NA
	Caterpillar 3034	52.3 @ 2600	33.5	19.0	131.1 @ 1600	42.0 39.8	16.7 13.9	