State of California AIR RESOURCES BOARD

EXECUTIVE ORDER U-R-34-5 Relating to Certification of New Off-Road Compression-Ignition Engines

MOTORENFABRIK HATZ GMBH & CO. KG

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment:

Model Year: 2001

Typical Equipment Usage: Generator set and compressor

Fuel Type: Diesel

| | Engine | | |
|-------------------------------|--|--------------------------------|--|
| Engine Family 1HZXL3.43A37 | Displacement (liters) 2.574 and 3.432 | Useful Life (hours) 8000 | Emission Control Systems <u>and Special Features</u> Direct Diesel Injection |

Engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The exhaust emission certification standards and certification values for hydrocarbons (HC), oxides of nitrogen (NOx), or non-methane hydrocarbons plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) (units are expressed in grams per kilowatt-hour (g/kw-hr)), and the opacity-of-smoke certification standards and certification values in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family are as follows (Title 13, California Code of Regulations, Section 2423):

| Engine Power | Emission Standard | Exhaust Emissions (g/kw-hr) | | | | | | <u>Smok</u> | Smoke Opacity (%) | | |
|--|---------------------------|-----------------------------|-----------|-------------------|-----------------|------------------|-----------|-------------|-------------------|------------|--|
| <u>Rating (kw)</u> 37 <u><</u> KW<75 | <u>Category</u> Tier 1 | Standard | HC N/A | <u>NOx</u> 9.2 | NMHC+NOx N/A | <u>ÇO</u> N/A | PM N/A | Accel 20 | <u>Lug</u> 15 | Peak 50 | |
| | | Certification | | 8.4 | | | | 9 | 12 | 10 | |

BE IT FURTHER RESOLVED: That the listed engine models also comply with "Emission Control Labels— 1996 and Later Off-Road Compression-Ignition Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Sections 2425 and 2426).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this

day of March 2001.

Ř. B. Summerfield, Chief

Mobile Source Operations Division

Model Year:

2001

Manufacturer: Engine Family: Motorenfabrik Hatz GmbH & Co. KG

1HZXL3.43A37

Issued:

Revised:

E.O. Number:

11/29/2000

ED# U-R-34-5

Small Off-Road Engine Model Summary Form

Attachment

Units for Table: hp

| Worst | 47. Model | 48. Sales | 49. Displ | 50. Bore/ | 51. Ignition | 52. Max | 53. Rated Speed | 54. Rated | 55. Torque Spec | 56. ed Emiss |
|-------|--------------|--------------|--------------|--------------|-----------------|------------|--------------------|--------------|--------------------|-------------------|
| Case? | Designation | Code | (cc) | Stroke | Timing | Power | (RPM) | Torque | (RPM) | Control Sys |
| | 4M41 | Calif. Only | 3432 | 102 / 105 | 10+1° static | 71.2 | 3000 | 125 | 3000 | OOL EM |
| | 4M41 | Calif. Only | 3432 | 102 / 105 | 10+1° static | 64.0 | 3000 | 112 | 3000 | PPE-EM |
| | 4M41Z | Calif. Only | 3432 | 102 / 105 | 10+1° static | 69.1 | 3000 | 123 | 3000 | DDE EM |
| | 4M41Z | Calif. Only | 3432 | 102 / 105 | 10+1° static | 62.0 | 3000 | 110 | 3000 | ODE EM |
| | 4L41C | Calif. Only | 3432 | 102 / 105 | 10+1° static | 65.4 | 3000 | 115 | 3000 | DOI EW |
| | 4L41C | Calif. Only | 3432 | 102 / 105 | 10+1° static | 58.9 | 3000 | 104 | 3000 | |
| | 4M41 | Calif. Only | 3432 | 102 / 105 | 10+1° static | 69.7 | 2300 | 160 | 2300 | DOT EW |
| | 4M41 | Calif. Only | 3432 | 102 / 105 | 10+1° static | 62.7 | 2300 | 144 | 2300 | DDI EM |
| | 4M41Z | Calif. Only | 3432 | 102 / 105 | 10+1° static | 68.3 | 2300 | 158 | 2300 | |
| | 4M41Z | Calif. Only | 3432 | 102 / 105 | 10+1° static | 61.4 | 2300 | 142 | | hor |
| | 4L41C | Calif. Only | 3432 | 102 / 105 | 10+1° static | 63.0 | 2300 | 144 | 2300 | 00f EM |
| | 4L41C | Calif. Only | 3432 | 102 / 105 | 10+1° static | 56.7 | 2300 | 130 | | DDÎ EM |
| | 4M41 | Calif. Only | 3432 | 102 / 105 | 10+1° static | 49.6 | 1800 | 149 | | DOT EW |
| | 3M41 | Calif. Only | 2574 | 102 / 105 | 10+1° static | 53.3 | 3000 | 94 | | DOE EM |
| | 3M41Z | Calif. Only | 2574 | 102 / 105 | 10+1° static | 52.4 | 3000 | 92 | | ODS EM |
| | 3M41 | Calif. Only | 2574 | 102 / 105 | 10+1° static | 52.1 | 2300 | 112 | • | 001 EW |
| Χ . | 3M41Z | Calif. Only | 2574 | 102 / 105 | 10+1° static | 51.2 | 2300 | 110 | • | ODI EM |

EPA cart. NO. HZX-NRCI-01-01