State of California AIR RESOURCES BOARD

EXECUTIVE ORDER U-R-35-14 Relating to Certification of New Off-Road Compression-Ignition Engines

MITSUBISHI HEAVY INDUSTRIES, LTD.

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment:

Model Year: 2001

Typical Equipment Usage: Other Industrial Equipment

Fuel Type: Diesel

	Engine		
<u>Engine Family</u>	Displacement	Useful Life	Emission Control Systems
1MVXL02.3AAA	<u>(liters)</u>	<u>(hours)</u>	<u>and Special Features</u>
(K4N-D)	2.3	5000	Direct Diesel Injection

Engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The exhaust emission certification standards and certification values for hydrocarbons (HC), oxides of nitrogen (NOx), or non-methane hydrocarbons plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) (units are expressed in grams per kilowatt-hour (g/kw-hr)), and the opacity-of-smoke certification standards and certification values in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family are as follows (Title 13, California Code of Regulations, Section 2423):

Engine Power <u>Rating (kw)</u>	Emission Standard		Smoke	Smoke Opacity (%)						
19 <kw<37< td=""><td><u>Category</u> Tier 1</td><td></td><td><u>HC</u></td><td><u>NOx</u></td><td><u>NMHC+NOx</u></td><td><u>C0</u></td><td><u>PM</u></td><td>Accel</td><td>Lug</td><td>Peak</td></kw<37<>	<u>Category</u> Tier 1		<u>HC</u>	<u>NOx</u>	<u>NMHC+NOx</u>	<u>C0</u>	<u>PM</u>	Accel	Lug	Peak
		Standard Certification	N/A	N/A	9.5	5.5	0.80	20	15	50
					7.4	2.7	0.58	5	8	9

28

BE IT FURTHER RESOLVED: That the listed engine models also comply with "Emission Control Labels— 1996 and Later Off-Road Compression-Ignition Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Sections 2425 and 2426).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this

22' day of February 2001.

R. B. Summerfield, Chief Mobile Source Operations Division

ATIACHMENT

Engine Model Su....ary Form

•

Mitsubishi Heavy Industries,Ltd Manufacturer:

Nonroad Cl Engine category:

EPAEngine Family: 1MVXL02.3AAA

Mitr Family Name: K4N-D

New Submission Process Code:

c	, <u> </u>			1 1 :				_ ,						-		 					
8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAF .11930			1																	1	
AF Co			_								Ì					ļ					
SSIO	ũ															Ì					
vice I			د+																		
0 0		ור									.										
anbi															· .						
tate: ak to	0	4 0	1 5												1						
uel F Øpe:	10.5		13.31																		
8.F s/hr)(ŀ									•				
ଶ୍ୱ							1			ļ											
ak									ļ												
čate: Øpe	4	•	6														-				
^c uet Rat stroke@ torque	32.4	37.4	34.3						[
7.Fueł Rate: mm/stroke@peak torque																.					
2																					
ž		Q												1							
6.Torque @ RPM (SEA Gross)	106.6@1400	106.6@1400	107,8@1500			ł										İ					
A Gr	60	000				l				ļ											
Torg (SE	8	00	10				ľ									- 					
ġ							-														
₽∽																					
ate: eak F			G							•											
ese Ses	141	14.1	16.96																	2.	
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)														1 + 							
				·**																	
дĦ														ļ							
ate: peak onty)	_	_											·						-		
el Ra	32.4	32.4	32.1																		
4.Fuel Rate: mm/stroke @ peak HP (for diese! only)					1. 1.																
t) (t													 								
									ĺ												•
(ss	Ő	8	8										1.5						ŀ		
600	<u>@</u> 2(<u>@</u> 2(027												·						
3.BHP@RPM (SAE Gross)	38.0 @ 2000	38.0@2000	42.9@2400										<u>с</u> н. Н		1						į
- cə	က	3	4																		
-									ł				at a ca			4					
ode										1						·					1
e C	K4N-D	Q'N	K4N-D					2	-	-											
ngir	Σ	₹ 4	₹																		
2.Engine Model	-																				
								-													Ì
)ode	_	1ES	S																		
D er	ž	De	DS								>					•					
1.Engine Code	K4N-Y1D	K4N-Y1D61ES	K4N-Y1DSCM																		
1 1 1	×	Y AN	₹																	1	
Ĺ		_							<u> </u>							ļ				1	ļ

W-R-35-14