

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2002	2CEXL0505ABC	8.3	Diesel	8000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Direct Diesel Injection, Turbocharger, Charge Air Cooler, Powertrain Control Module			Tractor	

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):


RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
130 ≤ KW < 225	Tier 1	STD	1.3	9.2	N/A	11.4	0.54	20	15	50
		FEL	N/A	6.2	N/A	N/A	0.19	N/A	N/A	N/A
		CERT	0.2	5.2	--	0.8	0.12	6	1	10

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 26th day of December 2001.


 R. B. Summerfield, Chief
 Mobile Source Operations Division

Engine Model Summary Form

ATTACHMENT

Manufacturer: Cummins Inc.
 Engine category: Nonroad Over 50 Hp
 EPA Engine Family: 2CEXL0505ABC
 Mfr Family Name: D413
 Process Code: New Submission

U-R-002-0156

1. Engine Code	2. Engine Model	3. BHP@RPM (SAE Gross)	4. Fuel Rate: mm ³ /stroke @ peak I/P (for diesel only)	5. Fuel Rate: (lbs/hr) @ peak I/P (for diesels only)	6. Torque @ RPM (SEA Gross)	7. Fuel Rate: mm ³ /stroke@peak torque	8. Fuel Rate: (lbs/hr)@peak torque	9. Emission Control Device Per SAE J1930
2892;FR90262	QSC8.3-C	300@2200	139	103.0	1000@1400	189	89.3	DDZ, PCM,TC,CAC
2892;FR90958	QSC8.3-C	300@2100	148	104.5	1000@1400	193	91.1	PCM,TC,CAC
2892;FR90690	QSC8.3-C	285@2200	131	97.1	935@1400	178	83.9	PCM,TC,CAC
2892;FR90778	QSC8.3-C	285@2200	131	97.1	935@1400	178	83.9	PCM,TC,CAC
2892;FR90817	QSC8.3-C	285@2200	131	97.1	1000@1400	189	89.3	PCM,TC,CAC
2892;FR90569	QSC8.3-C	280@2200	131	97.5	1000@1400	189	89.3	PCM,TC,CAC
2892;FR90915	QSC8.3-C	280@2200	131	97.5	1000@1400	189	89.3	PCM,TC,CAC
2892;FR90963	QSC8.3-C	280@2200	131	97.5	1000@1400	189	89.3	PCM,TC,CAC
2299;FR90308	QSC8.3-C	260@2200	122	90.4	870@1400	169	79.9	PCM,TC,CAC
2299;FR90816	QSC8.3-C	260@2200	122	90.4	870@1400	169	79.9	PCM,TC,CAC
2299;FR90959	QSC8.3-C	245@1800	138	83.8	870@1400	168	79.4	PCM,TC,CAC
2299;FR90568	QSC8.3-C	240@2200	113	84.0	870@1400	156	73.5	PCM,TC,CAC
2299;FR90957	QSC8.3-C	240@2200	113	84.0	800@1400	153	72.1	PCM,TC,CAC
2299;FR90962	QSC8.3-C	240@2200	113	84.0	800@1400	153	72.1	PCM,TC,CAC
8152;FR91063	QSC8.3-C	300@2200	139	103.0	1000@1400	189	89.3	PCM,TC,CAC
8152;FR90965	QSC8.3-C	300@2100	148	104.5	1000@1400	189	89.3	PCM,TC,CAC
8152;FR91064	QSC8.3-C	280@2200	131	97.5	1000@1400	189	89.3	PCM,TC,CAC
8152;FR91107	QSC8.3-C	285@2200	131	97.1	935@1400	178	83.9	PCM,TC,CAC
8153;FR91065	QSC8.3-C	260@2200	122	90.4	870@1400	169	79.9	PCM,TC,CAC
8153;FR91066	QSC8.3-C	240@2200	113	84.0	800@1400	153	72.1	PCM,TC,CAC
8153;FR91108	QSC8.3-C	245@1800	138	83.8	870@1400	168	79.4	PCM,TC,CAC
8088;FR91022	QSC8.3-C	251@2200	123	91.0	904@1400	174	82.0	PCM,TC,CAC
8088;FR91023	QSC8.3-C	283@2000	137	102.0	1022@1400	199	94.0	PCM,TC,CAC
8179;FR91105	QSC8.3-C	278@2000	138	93.0	1022@1400	191	90.2	PCM,TC,CAC