



Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

**IT IS ORDERED AND RESOLVED:** That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2002	2JDXL12.5035	12.5	Diesel	8000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Electronic Control Module, Direct Diesel Injection, Turbocharger, Charge Air Cooler			Tractor	

The engine models and codes are attached.

The following are the exhaust certification standards (STD, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr); and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):


RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
225 ≤ KW < 450	Tier 2	STD	N/A	N/A	6.4	3.5	0.20	20	15	50
		CERT	--	--	6.2	0.7	0.15	12	2	24

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

**This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.**

Executed at El Monte, California on this 27<sup>th</sup> day of December 2001.

  
R. B. Summerfield, Chief  
Mobile Source Operations Division

Engine Model Summary Form

Attachment

U-R-4-105

Manufacturer: Deere Power Systems Group of Deere and  
 Engine category: Nonroad CI  
 EPA Engine Family: 2JDXL12.5035  
 Mir Family Name: 650HD  
 Process Code: New Submission

1. Engine Code	2. Engine Model	3. BHP @ RPM (SAE Gross)	4. Fuel Rate: mm <sup>3</sup> /stroke @ peak IIP (for diesel only)	5. Fuel Rate: (lbs/hr) @ peak IIP (for diesels only)	6. Torque @ RPM (SEA Gross)	7. Fuel Rate: mm <sup>3</sup> /stroke @ peak torque	8. Fuel Rate: (lbs/hr) @ peak torque	9. Emission Control Device Per SAE J1930
6125HF070A	6125H	504.22@2100	247.00@2100	174.16@2100	1843.66@1575	369@1575	195.99@1575	EM EC CAC
6125HRW16A	6125H	331.23@2100	159.00@2100	112.43@2100	1143.07@1575	230@1575	122.35@1575	EM EC TC
6125HRW16B	6125H	421.08@2100	200.00@2100	141.09@2100	1450.59@1575	281@1575	149.47@1575	EM EC CAC
6125HRW17A	6125H	477.40@2100	230.00@2100	160.93@2100	1649.71@1575	323@1575	171.52@1575	EM EC CAC
6125HRW17B	6125H	504.22@2100	241.00@2100	169.75@2100	1741.15@1575	338@1575	179.45@1575	EM EC CAC
6125HF070K	6125H	442.54@1800	242.00@1800	145.50@1800				EM EC CAC
6125HF070L	6125H	482.77@1800	268.00@1800	160.93@1800				EM EC CAC
6125HF070M	6125H	563.23@1800	328.00@1800	198.41@1800				EM EC CAC
6125HF070N	6125H	616.87@1800	376.00@1800	227.07@1800				EM EC CAC
6125HRW05	6125H	309.78@2100	156.00@2100	110.23@2100	1090.71@1575	221@1575	117.28@1575	EM EC TC
6125HZ004	6125H	488.13@2200	218.00@2200	160.93@2200	1410.03@1600	225@1600	149.03@1600	EM EC CAC
6125HRW13A	6125H	331.23@2100	159.00@2100	112.43@2100	1143.07@1575	230@1575	122.35@1575	EM EC TC
6125HRW13B	6125H	421.08@2100	200.00@2100	141.09@2100	1450.59@1575	281@1575	149.47@1575	EM EC CAC
6125HRW15A	6125H	477.40@2100	230.00@2100	160.93@2100	1649.71@1575	323@1575	171.52@1575	EM EC CAC
6125HRW15B	6125H	504.22@2100	241.00@2100	169.75@2100	1741.15@1575	338@1575	179.45@1575	EM EC CAC
6125HF070F	6125H	399.62@2100	189.00@2100	132.28@2100	1348.82@1500	265@1500	134.04@1500	EM EC CAC
6125HF070H	6125H	450.58@2100	212.00@2100	149.91@2100	1520.65@1500	303@1500	153.44@1500	EM EC CAC
6125HF070I	6125H	474.72@2100	224.00@2100	156.53@2100	1603.24@1500	321@1500	162.48@1500	EM EC CAC
6125HF070J	6125H	500.20@2100	236.00@2100	165.34@2100	1688.79@1500	341@1500	172.62@1500	EM EC CAC
6125HRW06	6125H	395.60@2100	188.00@2100	132.28@2100	1349.56@1575	271@1575	143.74@1575	EM EC CAC
6125HRW07	6125H	359.39@2100	171.00@2100	121.25@2100	1227.14@1575	246@1575	130.95@1575	EM EC CAC
6125HRW08	6125H	468.02@2100	224.00@2100	156.53@2100	1613.57@1575	320@1575	169.97@1575	EM EC CAC
6125HRW09	6125H	425.10@2100	204.00@2100	143.30@2100	1466.81@1575	290@1575	154.32@1575	EM EC CAC
6125HT001	6125H	354.03@1800	196.00@1800	116.84@1800	1359.88@1300	251@1300	119.05@1300	EM EC CAC
6125HF070B	6125H	300.39@2100	150.00@2100	105.82@2100	1014.01@1500	202@1500	102.07@1500	EM EC CAC
6125HF070C	6125H	324.53@2100	152.00@2100	105.82@2100	1098.08@1500	218@1500	110.45@1500	EM EC CAC

DDI ↓