

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2002	2NVXL0530ANA	8.7	Diesel	8000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Direct Diesel Injection, Turbocharger, Charge Air Cooler and Engine Control Module			Loader and Tractor	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
130≤KW<225	Tier 1	STD	1.3	9.2	N/A	11.4	0.54	20	15	50
		CERT	0.1	7.1	--	0.6	0.06	9	1	28

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 12th day of December 2001.



R. B. Summerfield, Chief
 Mobile Source Operations Division

ATTACHMENT 1 OF 1

Engine Model Summary Form

Manufacturer: International E. O. # U-R-12-52
 Engine category: Nonroad CI
 EPA Engine Family: 2NVXL0530ANA
 Mfr Family Name: DTA 530E
 Process Code: New Submission

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)		5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)		6.Torque @ RPM (SEA Gross)		7.Fuel Rate: mm/stroke@peak torque		8.Fuel Rate: (lbs/hr)@peak torque		9.Emission Control Device Per SAE J1930
			Advertised	Average	Average	Average	Advertised	Average	Average	Average	Average		
ICH250D	ICH250D	250 @ 2000	133.2	89.3	850 @ 1300	162.6	70.8	ECM,TC,CAC,					
ICH265D	ICH265D	265 @ 2200	130.6	96.3	850 @ 1300	161.7	70.4	ECM,TC,CAC,					
IC265D	IC265D	265 @ 2100	135.0	95.0	831 @ 1500	160.8	80.8	ECM,TC,CAC,					
ICL265D	ICL265D	265 @ 2200	132.2	97.4	822 @ 1700	155.3	88.4	ECM,TC,CAC,					
IC240D	IC240D	240 @ 2200	118.7	87.5	775 @ 1300	148.1	64.5	ECM,TC,CAC,					
IC250D	IC250D	250 @ 2200	126.2	93.0	755 @ 1600	147.6	79.1	ECM,TC,CAC,					